

## Process analysis of AuCl 4 - sorption leading to gold nanoparticle synthesis by Shewanella putrefaciens

Jeet Chandrakant Varia, Asfaw Zegeye, Sharon Velasquez-Orta, Steve Bull

### ▶ To cite this version:

Jeet Chandrakant Varia, Asfaw Zegeye, Sharon Velasquez-Orta, Steve Bull. Process analysis of AuCl 4 - sorption leading to gold nanoparticle synthesis by Shewanella putrefaciens. Chemical Engineering Journal, 2016, 288, pp.482 - 488. 10.1016/j.cej.2015.12.001 . hal-01780363

## HAL Id: hal-01780363 https://hal.univ-lorraine.fr/hal-01780363

Submitted on 29 Apr 2021

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

## Accepted Manuscript

Process analysis of AuCl<sub>3</sub> <sup>-</sup> sorption leading to gold nanoparticle synthesis by *Shewanella putrefaciens* 

Jeet Varia, Asfaw Zegeye, Sharon Velasquez-Orta, Steve Bull

PII: S1385-8947(15)01658-7

DOI: http://dx.doi.org/10.1016/j.cej.2015.12.001

Reference: CEJ 14504

To appear in: Chemical Engineering Journal

Received Date: 8 March 2014
Revised Date: 30 October 2015
Accepted Date: 1 December 2015



Please cite this article as: J. Varia, A. Zegeye, S. Velasquez-Orta, S. Bull, Process analysis of AuCl<sub>3</sub> - sorption leading to gold nanoparticle synthesis by *Shewanella putrefaciens*, *Chemical Engineering Journal* (2015), doi: http://dx.doi.org/10.1016/j.cej.2015.12.001

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Process analysis of AuCl<sub>3</sub> sorption leading to gold nanoparticle synthesis by Shewanella putrefaciens

Jeet Varia<sup>1,2</sup>, Asfaw Zegeye<sup>3</sup>, Sharon Velasquez-Orta<sup>2</sup>, Steve Bull<sup>2</sup>

<sup>1</sup> School of Biosciences, Birmingham University, Edgbaston, Birmingham, West Midlands, B15 2TT,

United Kingdom

<sup>2</sup> School of Chemical Engineering and Advanced Materials, Newcastle University, Newcastle upon

Tyne, Tyne and Wear NE1 7RU

<sup>3</sup> French National Centre for Scientific Research, Paris, LCPME UMR 7564

Corresponding author: Jeet Varia

Email: jeetvaria@gmail.com

Tel: 07950250150

#### **Abstract**

A process evaluation of AuCl<sub>4</sub> (< 300 mg/L, < pH 3, H<sub>2</sub> e-donor) sorption kinetics and mass transfer analysis by initially viable Shewanella putrefaciens is presented here. Following on from previous reports of a thermodynamically spontaneous reaction, high sorption capacity of 1346 mg/g and significant evidence of zero valent gold nanoparticles (AuNPs) deposited within the bacterial cell wall. Linear and non-linearized kinetic modelling of the data shows a good fit to a pseudo second-order model and theoretical analysis of diffusional limiting steps suggest diffusion on the surface or through the cell wall to be the process rate limiting step. Process analysis of microbial gold synthesis, provides a foundation for the design of smart reactor systems for process intensification.

1

#### 1. Introduction

A variety of phenomena has been reported regarding the interactions of bacterial cells and metal ions such as adsorption, absorption, ion exchange, entrapment, reduction/oxidation and methylation [1]. Such phenomena could be combined in series or in parallel and usually grouped under the umbrella term, biosorption [2]. Technological application from these investigations has focused principally on (a) environmental remediation of heavy metals and radioactive pollutants in aqueous waters [3]; and (b) state of art biohydrometallurgical methods. Bacteria applied principally to oxidise and leach metals from primary ores, labelled "microbial mining" [4, 5].

In contrast the microbial-mediated sorption and transformation by faradaic reduction of metal ions, to metallic nanoparticle (NP) zero-valent and oxide precipitates, has been reported extensively [6]. The reduction of precious metal ions such as AuCl<sub>4</sub> studied here to zero-valent Au<sup>0</sup> NPs (AuNPs) is ubiquitous in the microbiological kingdom from fungi [7], yeast [8], archaea [9], algae [10] and especially for bacteria. Including proteobacteria [11-13], cyanobacteria [14], actinobacteria [15], firmicutes [16] and thermotogae [9].

Such phenomena have technological and monetary importance from two overlapping perspectives. First, from the recovery perspective. Microbial reduction and precipitation of metal ions can be capitalised for metal recovery from urban mining leachates and industrial and mining effluents. These aqueous solutions typically of low pH and low metal ion concentration (< 1 g L<sup>-1</sup>) [17]. Secondary, from NP synthesis perspectives. Here microbial cells are applied as green eco-friendly "nano-factories", following a green bottom-up methodology [18]. Processes in this case, carried out at ambient temperatures without the need for chemical additives such as capping or stabilising agents. For example in all cases microbial synthesis lead to biogenic NP surrounded by a proteinaceous capping/stabilizing agent [19].

From nanotechnological standpoints AuNPs are focused on here in light of their exceptional optical, chemical, photochemical and electronic properties [20]. AuNPs have a long history, with scientific reports dating back to the legendary 1857 lecture by Michael Faraday [21]. From an anthropogenic standpoint one can go even further back. With application of gold nanoparticles in gold bhasma [22] used for medical purposed in the Indian continent as far as the Vedic period and for decorative purposes by Roman artisans from the 4<sup>th</sup> century [23]. In the contemporary era they have shown vast

present and potential future application as ideal building blocks for future nanotechnological self-assembling systems [20].

The Shewanella Genus applied in this study was chosen as an archetypal dissimilative metal reducing bacterium [24]. Reported to reduce not only AuCl<sub>3</sub><sup>-</sup> [25-27] but also other precious metals such as Ag<sup>+</sup> [28], PGMs such as Pt<sup>4+</sup> [29] and Pd<sup>2+</sup> [30] and chalcogens such as Se<sup>4+</sup> [31] to biogenic zero valent nanoparticles (NPs), predominantly in the bacterial cell wall. Providing for ease for their separation using mild detergents and/or sonication [16].

Mechanistic studies of AuCl<sub>4</sub> sorption and AuNP synthesis by the Shewanella Genus have been reported to be mediated with an electron donor such as H<sub>2</sub> or formate [25, 32]. Solution pH and metal ion concentration was also shown to effect AuNP synthesis location, size and geometry. Further understanding and elucidation of metal nucleation and NP formation mechanisms would be interesting. Firstly, from scientific perspectives in understanding the quintessence of the phenomena and secondly for the formulation of protocols for synthesis of NPs with diverse physicochemical properties.

This study nethertheless aims to provide a process analysis of the sorption process, shown to lead to AuNP synthesis. Under specific conditions of low pH (< 3), with  $H_2$  as the electron donor and low metal ion concentration (< 300 mg/L). As a basis for further process optimisation and intensification of the specific case. For these conditions, high removal capacity up to 1346 mg/g-cells and thermodynamically spontaneous ( $\Delta G \approx -24$  kJ/mol) process has been reported [27]. Furthermore as illustrated by Fig. 1, AuCl<sub>4</sub><sup>-1</sup> where precipitated predominantly in the cell wall periplasm with average diameters of 7.42  $\pm$  0.16 nm (No. NPs = 401) [27, 33]. Off note bacterial cell membrane are not ruptured after 24 hours' incubation with solutions of low pH though the outer leaf is compromised. This would suggest that bacterial cells may retain some viability for solutions of low pH (<3) for extended periods of time.

The methodology described here would be applicable for the recovery of other precious and PGM metals by other microbial cells for various in-vitro conditions. Laying foundations for simulation and design of smart methodologies and reactors for efficient and intensified recovery of metals and/or synthesis of NPs. The vision for such a process would be for a "one pot" green methodology uniting paradigms of metal remediation, recovery and synthesis.

Furthermore, although the synthesis of AuNPs by deactivated cells has been reported [27, 32], our vision would be the application of live cells [34]. The long term viability of bacterial cells is undoubtedly called into question in aqueous systems of low pH, but analysis of initial metal removal (0 - 4 hrs) should provide some clues as to sorption and transformation process kinetics and mass transfer by initially viable bacterial cells. This in-lieu of prospective future application of synthetic bacterial cells. Designed and programed [35] from the "bottom up" in function and utility and able to sustain life in a range of in-vitro environments.

#### 2. Materials and methods

Details of apparatus, experimental set up, microbial strain, medium and cultivation can be found elsewhere [27]. Briefly *S. putrefaciens* CN32 (American Type Culture Collection) were revived under aerobic conditions. Grown to a stationary growth phase, harvested, concentrated in 0.070 L, 0.9 % w/v NaCl and purged for 0.5 hr with  $N_2$ . Metal solutions were prepared from stock solutions, diluted to final volumes of 0.050 L, adjusted to a pH between 1-3, poured into 0.100 L vials and autoclaved at 121°C for 15 min. Aqueous metal solutions and washed bacterial cells suspensions were made anoxic by bubbling for 1 hr with  $N_2$  and then purged with  $H_2$  for approximately 20 seconds, prior to the addition of bacterial cells. Typically 0.005 L of 1 x  $10^{10}$  cells/L was added to metal solutions, placed in an incubator at 25°C and gently shaken. Samples were taken periodically, filtered through 0.2  $\mu$ m filters and analysed for  $AuCl_4$  using ICP-OES (Vista-MPX, UK). Assays were also performed to check for changes in solution pH in the presence of bacteria cells.

#### 2.1 Statistical analysis

To sufficiently use the theoretical assumptions behind applied mathematical equations, used to model the data, error functions were used to adequately measure goodness of fit. In this study the correlation of determination ( $R^2$ ) Eq. 1 was applied for linearized curve fitting of model kinetic equations. Linear fitting and non-linearized optimization were also evaluated using a chi-squared statistic test ( $\chi^2$ ) (Eq. 2), sum of squared errors (SSE) (Eq. 3) and average relative error (ARE) (Eq. 4). Appropriately applied in similar investigations [27, 36].

$$R^{2} = \frac{(q_{cal} - \overline{q})}{\sum_{i=1}^{n} (q_{cal} - \overline{q}) + \sum_{i=1}^{n} (q - \overline{q})}$$
(1)

$$\chi^2 = \sum_{i=1}^n \frac{(q_{cal} - q)^2}{q}$$
 (2)

$$SSE = \sum_{i}^{n} (q_{cal} - q)^2 \tag{3}$$

$$ARE = \frac{100}{n} \sum_{i}^{n} \left| \frac{q - q_{cal}}{q} \right| \tag{4}$$

#### 3. Results and discussion

Understanding of pertaining reaction process and limiting steps for specific conditions would be important for further process intensification, optimization, manipulation and/or imitation. For example, the selection of a unit operation to conduct this process will be done on the basis of the limitations shown on its kinetics. A process that is diffusion limited emphasises the need for efficient mixing, while a process limited a rate of reaction could benefit from external input energy to increase its performance. Fig. 2 illustrates the microbiological interface, with basic architectural aspects of the cell wall [24]. A basic mechanism was first proposed by pioneering work of Beveridge and co-workers investigating bacterial metal mineralization [37]. They designated a two-step mechanism, involving electrostatic interactions with anionic sites in the cell wall, consequently acting as spots for metal nucleation, leading to metal nucleation and precipitation within the cell wall. This shows some multidisciplinary parallel to investigations of electrochemical gold deposition [38] and nucleation [39], extensively modelled using a three dimensional diffusion controlled mechanism [40]. Accordingly, we propose four key steps of an overall reaction process illustrated in Fig. 2.

Step 1: <u>Film diffusion</u> - Transport of the AuCl<sub>4</sub> ion from the bulk solution, through a stagnant aqueous thin film bordering the bacterial cell wall.

Step 2: <u>Pore diffusion</u> - Transport of the ion through the cell wall (lipopolysaccharide (LPS) layer, OM, PS, IM and/or cytoplasm. To protein enzyme metal recognition peptide motifs sorption and nucleation sites.

Step 3: <u>AuCl<sub>4</sub> reduction</u> - Electron transfer to metal ions located at redox active site of membrane proteins such as cytochromes or hydrogenase leading to a phase change of AuCl<sub>4</sub> to Au<sup>0</sup>.

Step 4: <u>AuNP nucleation</u> - Reduced Au<sup>0</sup> behaving as nucleation sites for formation of Au<sup>0</sup> crystals and finally nanoscale particles.

If the last steps are assumed rapid [41, 42], either mass transfer steps 1 and 2 could be rate limiting. Analysis of sorption dynamics can provide valuable insight into reaction pathways [43, 44]. Furthermore, sorption kinetics allows prediction of solute uptake rate, which is important for process

intensification, engineering scale up and process scheduling. Sorption kinetics were fitted with a pseudo first-order model of Lagergren [45], a pseudo second-order model [43] and intra-particular diffusion model [46].

#### 3.1 Solution pH

Solution pH has been implicated as one of the most important factors in the bio-sorption process. Protons in solution would affect properties of the cell wall such as charged ionic groups in outer leaf of the OM, composed largely of lipopolysaccharide (LPS). LPS of the Shewanella genus contain acid function groups [47] such as -OH<sup>-</sup>, -COO<sup>-</sup>, -H<sub>2</sub>PO<sub>4</sub><sup>-</sup>, and -NH<sub>4</sub><sup>+</sup>, which would play an important role in metal binding [48]. The pH would also effect the speciation of the Au<sup>3+</sup> ion [49]. With AuCl<sub>4</sub><sup>-</sup> the dominate species bellow pH 6. No buffers were applied in this study to represent of real wastewater effluents. As illustrated by Fig. 3 pH of metal assays where not significantly affected.

#### 3.2 Sorption kinetics

The pseudo first and second-order model have been used extensively in the literature to describe metal ion uptake under non-equilibrium conditions [50]. Especially for classical adsorbents such as activated carbon [51]. Here bacterial cells could be perceived as living activated carbon particles. Although some attempts have been made to give a theoretical bases to the equations [50]. Our current understanding is limited in comparison to that of uptake thermodynamics. The intraparticular diffusion model, also used here to fit the data, has also shown some relevance [51-53] and is based on the assumption that film diffusion is negligible and intraparticular diffusion to be rate limiting.

# 3.3 Linear modelling of the pseudo first-order, pseudo second-order and intra-particular diffusion model

The amount of metal ions adsorbed for a given volume of solvent and mass of bacterial cells is described by Eq. 5. Where  $q_t$  (mg/g) is the amount of metal ions sorbed at time t,  $C_0$  and  $C_t$  is the initial and final concentration at time t of metal ions in solution and V (0.050 L) is the volume of the solution. M is the mass of adsorbent added to solution based on a cell weight of 1.281 x  $10^{-13}$  g/cell, evaluated previously using allometric correlations [27].

$$q_t = (C_O - C_t) \frac{V}{M} \tag{5}$$

The pseudo first order model can be described by Eq. 6, where  $q_e$  (mg/g) is the amount of metal ions sorbed at equilibrium and  $k_1$  (1/hr) is the first order rate constant. The pseudo second order model can be described by Eq. 7, where  $k_2$  (g / (mg hr) is the seconds order constant.

$$\frac{dq_t}{dt} = k_1(q_e - q_t) \tag{6}$$

$$\frac{dq_t}{dt} = k_2(q_e - q_t)^2$$

Integrating Eq. 6 and 7 using the boundary conditions t = 0,  $q_t = 0$  and t = t,  $q = q_t$ , yields Eq. 8 and 9 respectively. Linear modelling can thus be carried out with plots of  $Log(q_e-q_t)$  vs. 1/t and 1/ $q_t$  vs. t for the pseudo first-order or pseudo second-order model respectively. Such plots should be straight if the models fit the data and allow estimation of model parameters  $k_1$ ,  $k_2$  and  $q_e$ .

$$Log(q_e - q_t) = Log(q_e) - \frac{k_1}{2.303t}$$
 (8)

$$\frac{t}{q_t} = \frac{1}{q_e} + \frac{1}{q_e^2 k_2 t} \tag{9}$$

The intra-particular model was first proposed by Weber and Morris [46] (Eq. 10) and further developed for various sorption systems [54]. Linearization of Eq. 10, yields Eq. 11, a plot of  $Log(q_e)$  vs. 0.5 Log(t), should give a straight line if this model can be applied.

$$q_t = k_{ip} t^{0.5}$$
 (10)

$$Log(q_t) = Log(k_{ip}) + 0.5Log(t)$$
(11)

#### 3.4 Non-Linear modelling of kinetic models

Linear regression assumes a Gaussian distribution of error at each point. However linearization of the data implicitly alters the error structure and may also violate the error variance and normality assumption [55]. Therefore a non-linear optimization method was also applied in this study, optimization was performed using the solver add-in of Microsoft Excel® which uses a generalized reduced gradient algorithm [56].

#### 3.5 Model of best fit

Non-linearized modelling of the data presented, on the whole gave better fits as summarized in Table 1. The pseudo second order equation in general showed the highest overall correlation ( $X^2 < 25.5$ , ARE < 6.99) and fit among the three kinetic models evaluated, with the first order second best ( $X^2 < 25.5$ , ARE < 15.1) and intraparticular model last ( $X^2 > 249$ , ARE > 15.6). Fig. 4-5 illustrates non-linear  $2^{nd}$  order modelling of gold sorption assays. For assay of 247 mg/L AuCl<sub>4</sub>-, pH 2, the sudden drop in q from 866 mg/L to 515 mg/L (Fig. 2) from 1 hr to 2 hr could be due to significant changes in cell viability for such systems of low pH. Modelling of this assay was only carried out for measurements up 1 hr based on this assumption. Values of the rate constant  $k_2$  between 0.009 and 0.451 mg/(g hr) compares well with previous reports of metal ion removal of 200 mg/L  $C^{6+}$  by *Rhizopus arrhizus* [57] of 0.04 mg/(g hr) and 200 mg/L  $C^{6+}$  removal by immobilized *Saccharomyces cerevisiae* [58] of 0.13 mg/(g hr). Furthermore, Ho and McKay report a pseudo second order model to point to processes of chemical sorption or chemisorption involving valence forces through sharing or exchange of electrons between the sorbent and sorbate [43]. This is compelling in light of the evident AuNPs nucleation within and extracellular of the cell wall [27].

#### 3.6 Diffusion process

On the assumption that reaction steps 3 and 4 are rapid two potential rate limiting steps are evident. Namely (a) related to diffusion of metal ions through a stagnant aqueous thin film sounding the bacterial cell wall (Step 1, Fig. 2) and (b) related to diffusion of metal ion at or through the cell wall to metal recognition sorption and nucleation sites (Step 2, Fig. 2). Attempts were made therefore to calculate coefficients of respective processes. Using methods described by Bhattacharya et al., [51] for removal of cadmium by activated carbon and applied by Mohan, Ramanaiah and Sarma [42] for biosorption of azo dye by Spirogyra sp. Such analysis was first elucidated by Helfferich [59] and is based on the work of Cranks [60]. Assuming an approximation of sorbent spherical geometry, the overall rate constant of the process can be correlated with the pore and film diffusion coefficient independently as described by Eq. 12 and 13 respectively.

$$D_{p} = 0.03 \left[ \frac{R_{p}^{2}}{t^{1/2}} \right] \tag{12}$$

$$D_f = 0.23 \left[ \frac{R_p \zeta}{t^{1/2}} \frac{C_e}{C_0} \right] \tag{13}$$

Where the radius ( $R_p$ ) of the sorbent bacterial cell taken as 0.387  $\mu m$  from allometric analysis of 12 bacterial cells [27], based on an average bacteria volume of 0.243  $\mu m^3$ . The film thickness ( $\zeta$ ) was estimated as 10.0  $\mu m$  [59]. The half time of removal ( $t_{1/2}$ ) was calculated using parameters obtained from best fit model, pseudo second-order Eq. 7.

If film diffusion was to be the rate limiting step than  $D_f$  values should be of the range  $10^{-10}$  to  $10^{-12}$  m<sup>2</sup>/s while if pore diffusion is the rate limiting step  $D_p$  should be in the range  $10^{-15}$  to  $10^{-18}$  m<sup>2</sup>/s [42]. Magnitudes of evaluated coefficients summarized in Table 2, clearly suggest a pore diffusion to be the rate-limiting step since  $D_p$  values range from  $2.49 \times 10^{-16}$  m<sup>2</sup>/s to  $7.24 \times 10^{-18}$ . This would indicate that metal ion diffusion through or at the surface of the cell wall "bottlenecks" the overall reaction rate.

Modification via genic engineering of the cell wall interface would be an astute step forward to enhance the case here [61]. Furthermore, electroactive bacteria such as that of the Shewanella Genus could be grown as biofilms on carbon electrodes. As applied extensively in microbial electrochemical technologies [62]. In most cases electroactive bacteria including the Shewanella Genus have been applied as catalysis of organic substrates in the anode compartment [63]. In contrast, bacterial cells grown on cathodes could be applied for AuNP recovery and/or synthesis. Here electrodes stepped to negative potentials could be applied to support cells. For example, as direct electron donors to bacterial cells or the in-situ production of electron donors such as H<sub>2</sub>. Furthermore, diffusion of metal ions to bacterial cells immolated on electrodes could be improved by capacitive deionisation [64]. Finally, acid functional groups or cell wall enzymes implicated in metal sorption and reduction could be influenced by applied potential. Providing a basis for selective sorption and the metal reduction process.

#### 4. Conclusions

This study completes an analysis of process thermodynamic (previous study), kinetic and mass transfer (this study). For AuCl<sub>4</sub> removal and AuNP synthesis by *S. putrefaciens*, for specific conditions of solution low pH and metal ion concentrates with H<sub>2</sub> present as the electron donor. Analysis and modelling of initial metal ion removal kinetics indicate a strong fit to a pseudo second-order model.

Evaluation of diffusional coefficients deemed metal ion diffusion at/through the bacterial cell wall (pore diffusion) to be the rate limiting step of the proposed process. This work provides quantitative foundations of the process for specific conditions. With the intension of future process optimization and intensification. Further studies of bacterial viability, separation methods and yield of AuNPs from the cell wall would be a sensible continuation, building on the elementary process analysis for the Shewanella case, provided in this study. Leading to the commercial application of metal sorption, recovery and microbial nanoparticles synthesis.

#### 5. References

- [1] Gadd GM. Metals, minerals and microbes: geomicrobiology and bioremediation. Microbiology. 2010;156:609-43.
- [2] Volesky B. Biosorption of heavy metals. Boca Raton, Fla.: CRC Press; 1990.
- [3] Gadd GM, White C. Microbial treatment of metal pollution a working biotechnology? Trends in Biotechnology. 1993;11:353-9.
- [4] Brierley CL. Microbiological mining. Scientific American. 1982;247:44-53.
- [5] Curtin ME. Microbial mining and metal recovery: corporations take the long and cautious path. Nature Biotechnology. 1983;1:228-35.
- [6] Korbekandi H, Iravani S, Abbasi S. Production of nanoparticles using organisms. Critical Reviews in Biotechnology. 2009;29:279-306.
- [7] Mukherjee P, Ahmad A, Mandal D, Senapati S, Sainkar SR, Khan MI, et al. Bioreduction of AuCl4–ions by the fungus, Verticillium sp. and surface trapping of the gold nanoparticles formed. Angewandte Chemie International Edition. 2001;40:3585-8.
- [8] Bhambure R, Bule M, Shaligram N, Kamat M, Singhal R. Extracellular Biosynthesis of Gold Nanoparticles using Aspergillus niger its Characterization and Stability. Chemical Engineering & Technology. 2009;32:1036-41.
- [9] Kashefi K, Tor JM, Nevin KP, Lovley DR. Reductive Precipitation of Gold by Dissimilatory Fe (III)-Reducing Bacteria and Archaea. Applied and Environmental Microbiology. 2001;67:3275-9.
- [10] Sicard C, Brayner R, Margueritat J, Hemadi M, Coute A, Yepremian C, et al. Nano-gold biosynthesis by silica-encapsulated micro-algae: a "living" bio-hybrid material. Journal of Materials Chemistry. 2010;20:9342-7.
- [11] Watterson JR. Preliminary evidence for the involvement of budding bacteria in the origin of Alaskan placer gold. Geology. 1992;20:315-8.

- [12] Reith F, Etschmann B, Grosse C, Moors H, Benotmane MA, Monsieurs P, et al. Mechanisms of gold biomineralization in the bacterium Cupriavidus metallidurans. Proceedings of the National Academy of Sciences. 2009;106:17757-62.
- [13] Deplanche K, Merroun ML, Casadesus M, Tran DT, Mikheenko IP, Bennett JA, et al. Microbial synthesis of core/shell gold/palladium nanoparticles for applications in green chemistry. Journal of the Royal Society Interface. 2012;9:1705-12.
- [14] Govindaraju K, Basha S, Kumar V, Singaravelu G. Silver, gold and bimetallic nanoparticles production using single-cell protein (Spirulina platensis) Geitler. Journal of Materials Science. 2008;43:5115-22.
- [15] Kalabegishvili TL, Kirkesali El, Rcheulishvili AN, Ginturi EN, Murusidze IG, Pataraya DT, et al. Synthesis of gold nanoparticles by some strains of Arthrobacter genera. Journal of Materials Science and Engineering A: Structural Materials: Properties, Microstructure and Processing. 2012;2:164-73.
- [16] Krishnamurthy S, Yun Y-S. Recovery of microbially synthesized gold nanoparticles using sodium citrate and detergents. Chemical Engineering Journal. 2013;214:253-61.
- [17] Pletcher D, Walsh FC. Industrial electrochemistry: Springer Science & Business Media; 1990.
- [18] Lloyd JR, Byrne JM, Coker VS. Biotechnological synthesis of functional nanomaterials. Current Opinion in Biotechnology. 2011;22:509-15.
- [19] Suresh AK, Pelletier DA, Wang W, Broich ML, Moon J-W, Gu B, et al. Biofabrication of discrete spherical gold nanoparticles using the metal-reducing bacterium Shewanella oneidensis. Acta Biomaterialia. 2011;7:2148-52.
- [20] Hutchings GJ, Brust M, Schmidbaur H. Gold-an introductory perspective. Chemical Society Reviews. 2008;37:1759-65.
- [21] Faraday M. The Bakerian Lecture: Experimental Relations of Gold (and Other Metals) to Light. Philosophical Transactions of the Royal Society of London. 1857;147:145-81.
- [22] Dube RK. Gold powder: Its preparation & application as described in ancient Sanskrit texts. Gold Bull. 1991;24:95-102.
- [23] Freestone I, Meeks N, Sax M, Higgitt C. The Lycurgus cup—a roman nanotechnology. Gold Bull. 2007;40:270-7.
- [24] Fredrickson JK, Romine MF, Beliaev AS, Auchtung JM, Driscoll ME, Gardner TS, et al. Towards environmental systems biology of Shewanella. Nat Rev Micro. 2008;6:592-603.
- [25] Konishi Y, Tsukiyama T, Ohno K, Saitoh N, Nomura T, Nagamine S. Intracellular recovery of gold by microbial reduction of AuCl4– ions using the anaerobic bacterium Shewanella algae. Hydrometallurgy. 2006;81:24-9.

- [26] Konishi Y, Tsukiyama T, Tachimi T, Saitoh N, Nomura T, Nagamine S. Microbial deposition of gold nanoparticles by the metal-reducing bacterium Shewanella algae. Electrochimica Acta. 2007;53:186-92.
- [27] Varia J, Zegeye A, Roy S, Yahaya S, Bull S. Shewanella putrefaciens for the remediation of Au3+, Co2+ and Fe3+ metal ions from aqueous systems. Biochemical Engineering Journal. 2014;85:101-9.
- [28] Suresh AK, Pelletier DA, Wang W, Moon J-W, Gu B, Mortensen NP, et al. Silver nanocrystallites: biofabrication using Shewanella oneidensis, and an evaluation of their comparative toxicity on gramnegative and gram-positive bacteria. Environmental Science & Technology. 2010;44:5210-5.
- [29] Konishi Y, Ohno K, Saitoh N, Nomura T, Nagamine S, Hishida H, et al. Bioreductive deposition of platinum nanoparticles on the bacterium Shewanella algae. Journal of Biotechnology. 2007;128:648-53.
- [30] Windt WD, Aelterman P, Verstraete W. Bioreductive deposition of palladium (0) nanoparticles on Shewanella oneidensis with catalytic activity towards reductive dechlorination of polychlorinated biphenyls. Environmental Microbiology. 2005;7:314-25.
- [31] Klonowska A, Heulin T, Vermeglio A. Selenite and tellurite reduction by Shewanella oneidensis. Applied and Environmental Microbiology. 2005;71:5607-9.
- [32] De Corte S, Hennebel T, Verschuere S, Cuvelier C, Verstraete W, Boon N. Gold nanoparticle formation using Shewanella oneidensis: a fast biosorption and slow reduction process. Journal of Chemical Technology & Biotechnology 2011;86:547-53.
- [33] Varia J. Bio-electrochemical Systems for the Remediation of Metal-ion Effluents. 2012.
- [34] Anushree M. Metal bioremediation through growing cells. Environment International. 2004;30:261-78.
- [35] Gibson DG, Glass JI, Lartigue C, Noskov VN, Chuang R-Y, Algire MA, et al. Creation of a bacterial cell controlled by a chemically synthesized genome. Science. 2010;329:52-6.
- [36] Foo KY, Hameed BH. Insights into the modeling of adsorption isotherm systems. Chemical Engineering Journal. 2010;156:2-10.
- [37] Beveridge T, Fyfe W. Metal fixation by bacterial cell walls. Canadian Journal of Earth Sciences. 1985;22:1893-8.
- [38] Harrison JA, Thompson J. The kinetics of gold deposition from chloride solution. Journal of Electroanalytical Chemistry and Interfacial Electrochemistry. 1975;59:273-80.
- [39] Varia J, Martinez SS, Velasquez-Orta S, Bull S. Microbiological influence of metal ion electrodeposition: studies using graphite electrodes, [AuCl4]— and Shewanella putrefaciens. Electrochimica Acta.

- [40] Scharifker B, Hills G. Theoretical and experimental studies of multiple nucleation. Electrochimica Acta. 1983;28:879-89.
- [41] Selatnia A, Boukazoula A, Kechid N, Bakhti M, Chergui A, Kerchich Y. Biosorption of lead (II) from aqueous solution by a bacterial dead< i> Streptomyces rimosus</i> biomass. Biochemical Engineering Journal. 2004;19:127-35.
- [42] Mohan SV, Ramanaiah S, Sarma P. Biosorption of direct azo dye from aqueous phase onto< i>Spirogyra</i> sp.< i> 102</i> Evaluation of kinetics and mechanistic aspects. Biochemical Engineering Journal. 2008;38:61-9.
- [43] Ho YS, McKay G. Pseudo-second order model for sorption processes. Process Biochemistry. 1999;34:451-65.
- [44] Febrianto J, Kosasih AN, Sunarso J, Ju Y-H, Indraswati N, Ismadji S. Equilibrium and kinetic studies in adsorption of heavy metals using biosorbent: A summary of recent studies. Journal of Hazardous Materials. 2009;162:616-45.
- [45] Yuh-Shan H. Citation review of Lagergren kinetic rate equation on adsorption reactions. Scientometrics. 2004;59:171-7.
- [46] Weber W, Morris J. Advances in water pollution research. Proceedings of the First International Conference on Water Pollution Research1962. p. 231.
- [47] MOULE AL, WILKINSON SG. Composition of lipopolysaccharides from Alteromonas putrefaciens (Shewanella putrefaciens). Journal of general microbiology. 1989;135:163-73.
- [48] Langley S, Beveridge TJ. Effect of O-side-chain-lipopolysaccharide chemistry on metal binding. Applied and Environmental Microbiology. 1999;65:489-98.
- [49] Thompson W, Kaye M, Bale C, Pelton A. Pourbaix Diagrams for Multielement Systems. Uhlig's Corrosion Handbook. 2000.
- [50] Liu Y, Liu Y-J. Biosorption isotherms, kinetics and thermodynamics. Separation and Purification Technology. 2008;61:229-42.
- [51] Arun KB, Venkobachar C. Removal of Cadmium (II) by Low Cost Adsorbents. Journal of Environmental Engineering. 1984;110:110-22.
- [52] Selatnia A, Bakhti MZ, Madani A, Kertous L, Mansouri Y. Biosorption of Cd2+ from aqueous solution by a NaOH-treated bacterial dead Streptomyces rimosus biomass. Hydrometallurgy. 2004;75:11-24.
- [53] Selatnia A, Boukazoula A, Kechid N, Bakhti MZ, Chergui A. Biosorption of Fe3+ from aqueous solution by a bacterial dead Streptomyces rimosus biomass. Process Biochemistry. 2004;39:1643-51.
- [54] Poots VJP, McKay G, Healy JJ. Removal of Basic Dye from Effluent Using Wood as an Adsorbent. Journal (Water Pollution Control Federation). 1978;50:926-35.

- [55] Porter JF, McKay G, Choy KH. The prediction of sorption from a binary mixture of acidic dyes using single- and mixed-isotherm variants of the ideal adsorbed solute theory. Chemical Engineering Science. 1999;54:5863-85.
- [56] Fylstra D, Lasdon L, Watson J, Waren A. Design and Use of the Microsoft Excel Solver. Interfaces. 1998;28:29-55.
- [57] Preetha B, Viruthagiri T. Batch and continuous biosorption of chromium(VI) by Rhizopus arrhizus. Separation and Purification Technology. 2007;57:126-33.
- [58] Mack CL, Wilhelmi B, Duncan JR, Burgess JE. A kinetic study of the recovery of platinum ions from an artificial aqueous solution by immobilized Saccharomyces cerevisiae biomass. Minerals Engineering. 2008;21:31-7.
- [59] Helfferich FG. Ion exchange: Dover Publications; 1995.
- [60] Crank J. The mathematics of diffusion: Clarendon Press; 1979.
- [61] Kuroda K, Ueda M. Molecular design of the microbial cell surface toward the recovery of metal ions. Current Opinion in Biotechnology. 2011;22:427-33.
- [62] Rabaey K. Bioelectrochemical systems: from extracellular electron transfer to biotechnological application. London; New York: IWA Publishing; 2010.
- [63] Kim HJ, Park HS, Hyun MS, Chang IS, Kim M, Kim BH. A mediator-less microbial fuel cell using a metal reducing bacterium, Shewanella putrefaciens. Enzyme and Microbial Technology. 2002;30:145-52.
- [64] Gregory KB, Lovley DR. Remediation and recovery of uranium from contaminated subsurface environments with electrodes. Environmental science & technology. 2005;39:8943-7.




Figure 1 : TEM images (a-c) with respective close-up of the CW (i) – (iii) of *S. putrefaciens* before (a) and after (b) – (c) incubation with 170 mg/L AuCl<sub>3</sub>, pH 3 after 24 hrs. Scale bar for (a) – (c) = 100 nm, for (i) – (iii) = 50 nm. Fig. 5(d) histogram % frequency NPs sizes determined using ImageJ precipitated intra- and extra cellular by initially *S. putrefaciens* cells after 24hrs incubation with 170 mg/L AuCl<sub>4</sub>, pH 3




Figure 2: Illustration of the microbial reduction interface and metal sorption and transformation process steps, taken from different levels of heiritical resolution. (a) Bacterial cell interface, (b) cell wall interface and (c) protein interface.




Figure 3: Changes in pH of metal solutions injected with 5ml of 1x10<sup>10</sup>CFU/ml *S. putrefaciens* cells.




Figure 4: Non-linearized fit of pseudo second-order to initial metal removal for assays of concentration > 200 mg/L of various pH. Fitting of assay 265 mg/L AuCl<sub>4</sub> is for only 0 – 1 hr. Data points replicated from a preliminary publication [1]




Figure 5 : Non-linearized fit of pseudo second-order to initial metal removal for assay of concentration ≈ 160 mg/L, of pH 1, 2 and 3. Data points replicated from a preliminary publication [1]

[1] Varia J, Zegeye A, Roy S, Yahaya S, Bull S. Shewanella putrefaciens for the remediation of Au3+, Co2+ and Fe3+ metal ions from aqueous systems. Biochemical Engineering Journal. 2014;85:101-9.



		C <sub>o</sub> mg/L	рН	SSE	$\chi^2$	ARE	$R^2$		Rate constant	q <sub>e</sub> g/mg
Pseudo first-order		276	3	2.35 x 10⁴	43.4	15.1		 K <sub>1</sub> 1/hr	3.69	586
	Non- lineariz ed	247	2	$3.23 \times 10^2$	0.497	0.98	n/a		4.33	651
		265	1	$7.24 \times 10^2$	0.824	0.87			80.6	878
		162	3	2.11 x 10 <sup>3</sup>	5.61	4.55			8.81	378
		166	1	5.60 x 10 <sup>3</sup>	14.0	6.14			5.29	417
		166	2	$7.50 \times 10^3$	19.2	6.90			13.7	391
	Lineari	276	3	9.49 x 10 <sup>5</sup>	1.83 x 10 <sup>3</sup>	104	0.816 0.667 0.282 0.740 0.902		6.75 x 10 <sup>-2</sup>	908
		247	2	1.71 x 10 <sup>5</sup>	340	25.3			2.95 x 10 <sup>-1</sup>	1.01 x 10 <sup>3</sup>
		265	1		n/a					
	zed	162	3	$2.78 \times 10^5$	755	53.6			9.14 x 10 <sup>-2</sup>	1.02 x 10 <sup>3</sup>
		166	1	$2.62 \times 10^5$	692	37.4			$6.15 \times 10^{-1}$	282
		166	2	5.51 x 10 <sup>5</sup>	1.45 x 10 <sup>3</sup>	73.0			$3.47 \times 10^{-1}$	172
Pseudo second-order		276	3	1.34 x 10 <sup>4</sup>	25.5	6.99			9.49 x 10 <sup>-3</sup>	634
	Non-	247	2	$4.99 \times 10^{2}$	0.768	1.25	n/a (i4 b) / bu /		1.27 x 10 <sup>-2</sup>	672
	lineariz ed	265	1	$6.56 \times 10^{2}$	0.746	0.80			4.51 x 10 <sup>-1</sup>	884
		162	3	$2.42 \times 10^{3}$	6.50	5.14			$2.48 \times 10^{-1}$	377
		166	1	$4.03 \times 10^3$	9.95	5.18			$2.65 \times 10^{-2}$	438
		166	<u>2</u> 3	4.82 x 10 <sup>3</sup>	12.5	5.48		5.72 x 10 <sup>-2</sup>	418	
ě	Lineari zed	276		1.79 x 10 <sup>4</sup>	38.2	8.10		5.63 x 10 <sup>-3</sup>	667	
0		247	2	$3.83 \times 10^{3}$	7.49	4.05		A1	$2.25 \times 10^{-2}$	667
ğ		265	1	$9.90 \times 10^{5}$	$113 \times 10^3$	31.4	1.000 🗳 0.992 0.947	$3.38 \times 10^{-3}$	769	
Pseu		162	3	$2.58 \times 10^{3}$	6.93	4.79			9.66 x 10 <sup>-2</sup>	385
		166	1	$7.37 \times 10^3$	19.7	5.18			$1.10 \times 10^{-2}$	476
		166	2	$7.73 \times 10^3$	21.5	7.51	0.995		2.42 x 10 <sup>-2</sup>	455
Intraparticular model	Non- lineariz ed	276	3	$7.98 \times 10^4$	249	15.8		/(g hr <sup>0.5</sup> )	454	
		247	2	$6.86 \times 10^4$	257	15.6	n/a		431	
		265	1	$2.93 \times 10^5$	454	42.4			1.18 x 10 <sup>3</sup>	
		162	3	$8.62 \times 10^4$	433	28.8			283	
		166	1	$6.10 \times 10^4$	295	19.7			310	
		166	2	$1.09 \times 10^5$	629	30.1		<u>[g</u>	324	
	Lineari zed	276	3	1.04 x 10 <sup>5</sup>	224	17.9	0.874	)g	525	
		247	2	$1.28 \times 10^{5}$	250	20.5	0.948 0.716 0.637 0.645	K <sub>ip</sub> mg/(	565	
		265	1	$6.70 \times 10^5$	1.13 x 10 <sup>3</sup>	69.0			747	
		162	3	$1.38 \times 10^5$	419	38.3			378	
		166	1	$9.77 \times 10^4$	286	24.7			389	
		166	2	1.36 x 10 <sup>5</sup>	554	32.9	0.854		391	_

Table 1 : Summary of data evaluated by different kinetic models

$C_o$		$t_{(1/2)}$	$D_p$	$D_f$		
mg/L	рΗ	1/hr	$m^2/s$			
276	3	0.332	3.76 x 10 <sup>-18</sup>	5.52 x 10 <sup>-14</sup>		
247	2	0.234	5.34 x 10 <sup>-18</sup>	8.31 x 10 <sup>-14</sup>		
265	1	0.005	2.49 x 10 <sup>-16</sup>	5.10 x 10 <sup>-12</sup>		
162	3	0.021	5.84 x 10 <sup>-17</sup>	5.10 x 10 <sup>-13</sup>		
166	1	0.172	7.24 x 10 <sup>-18</sup>	7.34 x 10 <sup>-14</sup>		
166	2	0.084	1.49 x 10 <sup>-17</sup>	1.44 x 10 <sup>-13</sup>		

.d param .el Table 2: Summary of evaluated diffusion coefficients using parameters fitted from

### Highlights

- Kinetic modelling of AuCl<sub>4</sub> uptake by Shewanella putrefaciens
- Theoretical analysis of plausible diffusional rate limiting steps
- Geometrical analysis of observed biogenic AuNPs

