

Study and modeling of fluctuating dissolved oxygen concentration impact on Corynebacterium glutamicum growth in a scale-down bioreactor

Abdoul Karim Kaboré, Stéphane Delaunay, Fabrice Blanchard, Emmanuel Guedon, Michel Fick, Eric Olmos

▶ To cite this version:

Abdoul Karim Kaboré, Stéphane Delaunay, Fabrice Blanchard, Emmanuel Guedon, Michel Fick, et al.. Study and modeling of fluctuating dissolved oxygen concentration impact on Corynebacterium glutamicum growth in a scale-down bioreactor. Process Biochemistry, 2018, 10.1016/j.procbio.2018.10.016. hal-01924081

HAL Id: hal-01924081 https://hal.univ-lorraine.fr/hal-01924081v1

Submitted on 21 Oct 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Study and modeling of fluctuating dissolved oxygen concentration impact on Corynebacterium glutamicum growth in a scale-down bioreactor.

Abdoul Karim Kaboré^{a,b}, Stéphane Delaunay^{a,b}, Fabrice Blanchard^{a,b}, Emmanuel Guedon^{a,b}, Michel Fick^{a,b}, Eric Olmos^{a,b,*}

^aCNRS, Laboratoire Réactions et Génie des Procédés, UMR 7274, 2 avenue de la forêt de Haye, TSA 40602, Vandœuvre-lès-Nancy, F-54518, France

^bUniversité de Lorraine, LRGP, UMR 7274, 2 avenue de la forêt de Haye, TSA 40602, Vandœuvre-lès-Nancy, F-54518, France

Preprint submitted to Process Biochemistry

October 10, 2018

^{*}Corresponding author: eric.olmos@univ-lorraine.fr

Abstract

In this study, the impact of dissolved oxygen concentrations oscillations on Corynebacterium glutamicum 2262 Δ ldhA growth was studied experimentally and modeled. Aiming at this, a dedicated two-compartment scale down set-up composed of two interconnected aerobic/anaerobic stirred tank bioreactors was used. The mean residence time of bacteria in each compartment was modified by adapting circulation rates and culture volumes in each bioreactor and the resulting temporal ratio of aeration was calculated. The five growth kinetics were then modeled using an original kinetic model coupling Monod growth modeling and the Residence Time Distributions. Our study showed that the microbial growth rate and macroscopic yields were clearly linked to the temporal ratio of aeration, allowing the definition of simple but robust law for process scale-up purpose. It was also revealed that the model proposed precisely agreed with the experimental growth data, whatever the fractions of aeration time imposed experimentally.

Keywords

Scale-down, kinetic model, Corynebacterium glutamicum

1. Introduction

Whereas the first step of process development generally consists in the research 2 of value-added products production at the laboratory scale by selecting productive microbial strains for instance, scale-up of bioreactor is the second paramount step to allow the large-scale synthesis of the targeted molecule. However, using a constant power dissipation per unit of volume as criterion for bioreactor scale-up entails an increase of mixing times at larger scales [1], that potentially promotes concentration heterogeneities. Therefore, prediction, at lab-scale, of possible impact of concentration gradients on microbial performance is of great interest before scale-up and was the subject of major publications these last years [2, 3, 4, 5, 6]. The concentration gradients observed may concern dissolved oxygen concentrations [7, 8, 9], pH [10] or 11 nutrients such as carbon source [11]. Among the previous parameters identified, dis-12 solved oxygen is one of the most critical, due to heterogeneity of the oxygen injection, 13 to spatial variation of hydrostatic pressure and thus of oxygen transfer capacities and 14 to high oxygen consumption rates when high biomass concentrations are encountered [12]. To investigate the physiological effects of chronic exposure of microorganisms to the heterogeneous distribution of micro-environmental conditions, scale-down models were then introduced as rational and practical approaches to simulate the dynamic micro-environment (also called 'lifelines') experienced by the cells at large scale by 19 using small-scale set-ups. In most studies, fluctuating environments are controlled by combining two or three small-scale bioreactors [2]. In this study, the behaviour of Corynebacterium glutamicum subjected to fluctuations of dissolved oxygen concentrations, is studied using a scale-down approach.

Corynebacterium glutamicum is a gram-positive bacterium isolated in 1950s, used for the production of millions tons of amino acid per year including, glutamate, lysine, valine and alanine [13, 14]. Currently, the interest for C. glutamicum as an efficient organic acids producer under deprived oxygen conditions is increasing [15, 16]. To meet the demand of bio-based products, optimized large-scale bioreactors are required, thus leading to the occurrence of possible spatial concentration gradients. Until now, only few scale-down approaches have been carried out with C. glutamicum. Schilling et al. [17] investigated the performance of L-lysine production by C. 31 qlutamicum under substrate gradients while glucose and oxygen oscillations impact on C. glutamicum metabolism have been analyzed recently in a Continuous Stirred Tank (CST) bioreactor connected to Plug Flow (PF) bioreactor [18, 19, 20] or connected to another CST [21]. In all these works, the robustness of C. glutamicum 35 towards fluctuations of carbon source or oxygen concentrations was noticed. How-36 ever, although no modification at transcriptomic, proteomic and metabolomics levels 37 was noticed [18], oscillations induced a modification in the carbon fluxes resulting in an accumulation of side-products such as lactate [19, 20, 21]. These negative effects were increased when C. glutamicum was cultivated in a complex medium. In 40 this culture conditions, in a three-compartment scale-down reactor, a significative decrease in the product yield, a stop of growth and an accumulation of lactate and acetate were observed [20]. Otherwise, Buchholz et al. [22] focused on C. qlutamicum metabolic and transcriptional response when exposed to carbon dioxide gradients in a three stirred tank compartment set-up. They reported that the dissolved $[CO_2]$ gradients expected at industry-relevant residence times, of about 3.6 min, did not

hamper the process performances in comparison to lab-scale reference. However, transcriptional analysis have revealed up to 66 differentially expressed genes already after a 3.6 min dissolved [CO₂] gradient exposure; the genes expression was also related to gradient intensity and residence time of the cells. More recently, advanced CFD simulations using Euler-Lagrangian approaches were performed to determine the substrate concentrations encountered by cells in industrial scale bioreactors by Haringa et al. [23, 24, 25]. These approaches allow the design of adapted and representative scale-down set-ups. In our previous work, the variation of DOC imposed between fully-aerobic growth and oxygen-limited production phases was shown to play 55 an important role in the succinic acid production process [26]. Therefore, it seems of great importance to also determine this impact when the bacteria are exposed to chronic gradients, as encountered in large-scale bioreactors. The present work is 58 thus dedicated to the study of C. glutamicum response when this microorganism is 59 subjected to DOC oscillations, by using a CSTR-CSTR scale-down set-up. Whereas 60 one CSTR operate in anaerobiosis, the second one operates in fully-aerobiosis. As presented by Limberg et al. [21], CST are characterized by a high back-mixing, offering high level of flexibility for the adjustment of mean residence time and the control of DOC, temperature and pH in both compartments. However, as the Residence Time Distribution (RTD) of CSTR are strongly spread around the mean residence time, with a standard deviation equal to the mean residence time τ , it is necessary to consider the impact of RTDs on the real DOC fluctuations imposed to the cells. 67 To manage this, our study proposes an approach that takes into account the DOC fluctuations along bacteria lifelines and their impact on microbial growth, in the CSTR-CSTR loop. The results of this model are then compared to the experimental measurements.

2. Material and methods

2.1. Bacterial strain, culture media and inoculum preparation

Batch cultures of a mutant strain of C. glutamicum 2262, deleted for lactate dehy-74 drogenase gene ($\Delta ldhA$) were performed in a modified MCGC mineral salt medium 75 in which citrate was replaced by deferoxamine. This mutant strain is built using 76 the minimal genetic modification to redirect the carbon flux towards the succinate production as presented in a previous paper [27]. Final concentrations of nutrients and medium preparation details are provided in a previous study [26]. The mutant strain was constructed via a two-step homologous recombination procedure using the 80 vector pK19mobsacB Δ ldh 34. This plasmid was constructed using the suicide vector 81 pK19mobsacB as previously described [28]. The culture medium was supplemented with glucose as carbon and energy source at the desired concentration. Inoculum culture is obtained from glycerol stocks used in different preculture steps in mineral 84 salts medium and described in the study of Kaboré et al. [26].

86 2.2. Experimental set-up and culture conditions

To impose oscillating dissolved oxygen concentration (DOC) to cultures of C.

glutamicum 2262 Δ ldhA, a scale-down bioreactor system was used. This system

consisted of two interconnected stirred tank bioreactors (Tryton, Pierre Guerin Tech
nologies, France). One bioreactor was maintained at a constant DOC of 50 % of air

saturation (Bio_{O2}) while the second was set at DOC = 0 % of air saturation (Bio_{N2})

to mimic transition from aerobic to anaerobic environments (Figure 1). The culture broth continuously looped between both vessels at given recirculation flow rates Q 93 through a low gas permeability tubing (Exacanal, 5 mm internal diameter, 2.5 m long 94 and volume V_{tube} = 50 mL) using two peristaltic pumps (Masterflex, Cole-Parmer, Barrington IL, USA). Depending on liquid volume, each bioreactor was equipped with two or three four-bladed Rushton turbines (diameter D = 0.06 m). DOC was measured in both bioreactors using sterilizable polarographic probes (Mettler-toledo, ISM technology, Switzerland). In the aerobic Bio_{O2} bioreactor, DOC was maintained 99 constant by sparging air or pure oxygen through a ten-orifice diffuser and by adjust-100 ing gas flow rate. Anaerobic conditions were ensured in Bio_{N2} bioreactor by sparging 101 pure nitrogen through a porous diffuser. Liquid volumes V_1 and V_2 and residence 102 times $\tau_1 = V_1/Q$ and $\tau_2 = V_2/Q$ in aerobic and anaerobic bioreactors respectively 103 were set-up according to Table 1. Agitation rates were set to constant values of 104 900 rpm and 500 rpm respectively for Bio_{O2} and Bio_{N2} . pH was measured using 105 sterilizable glass electrode (Mettler-toledo, ISM technology, InPro3253, Switzerland) 106 and regulated in the two compartments at a set-point of 7.6 by automatic addition 107 of a 10 N KOH solution or 2 N HCl with a peristaltic pump connected to an on/off 108 pH controller. The foam formation was controlled by manual addition of drops of 109 pure polypropylene glycol (ppg) in both vessels with respect to final concentration 110 less than 1.2 mL ppg L^{-1} of broth. The temperature of cultures was maintained at 111 33°C by automatic cool and hot water circulation in the jacket of the bioreactors. 112 Biomass concentrations, glucose and organic acids concentrations were measured fol-113 lowing the protocols detailed in the work of Kaboré et al. [27]. The precision of

biomass concentration determination was 5 % and the one of glucose and organic acid concentrations was 3 %. Three different control cultures were first performed 116 at constant DOC. The first one, Bio_{ref1} , consisted of a culture performed using a 117 single aerobic bioreactor and thus without medium circulation; this experiment was 118 identified as reference for biomass growth maximization. To assess the impact of twocompartment experimental set-up on microbial response, a second reference culture Bio_{ref2} consisting of two identical aerobic CSTRs connected by the continuous recir-121 culation was studied (Table 1). For the third reference culture Bio_{ref3} , two CSTRs 122 operating in anaerobic conditions were interconnected and were considered as refer-123 ence cultures of C. glutamicum 2262 $\Delta ldhA$ regarding organic acids production. In 124 addition to these three reference cultures, six culture conditions imposing fluctuating 125 oxygenation conditions were defined. These experiments could be described by their 126 mean aeration ratios and residence times:

$$\alpha \simeq \frac{\tau_1 + V_{tube}/Q}{\tau_1 + \tau_2 + 2V_{tube}/Q} \tag{1}$$

Lastly, to quantify the culture performance in terms of growth, uptake and production, maximal specific growth rate μ_{max} and maximal yield of biomass on glucose $Y_{max}^{X/S}$ were determined using method of Kaboré et al. [27].

3. Results

3.1. Control cultures at constant dissolved oxygen concentration

Kinetics of growth, consumption of glucose, production of organic acids for the anaerobic culture, pH and DOC profiles are shown in Figure 2 for the three reference

cultures detailed in Table 1. Biomass concentration increased exponentially until exhaustion of glucose with maximal biomass concentrations of 18.2 and 19.8 g_{CDW} 136 L^{-1} , respectively obtained in one aerobic and two aerobic interconnected bioreactors 137 (Figure 2A 2B). Only minor amounts of organic acids were detected in the aerobic 138 control cultures including pyruvate, acetate with maximal concentrations of 0.4 g L^{-1} approximately and succinate with a maximal concentration of 1 g L^{-1} . For the 140 anaerobic reference culture Bio_{Ref3} , a negligible growth with maximal biomass concentration of $0.7 \,\mathrm{g}_{CDW} \,\mathrm{L}^{-1}$ was measured after 50 h of culture (Figure 2C). Whereas for the aerobic cultures the initial amount of glucose was completely exhausted, only 143 29 mM (4.3 g L^{-1}) were consumed for the anaerobic culture (Figure 2D). In these 144 anaerobic conditions, the glucose consumed was mainly converted into organic acids. 145 After 50 h of culture also, the maximal concentrations of pyruvate, acetate and suc-146 cinate were respectively 4.6 mM (0.4 g L^{-1}), 10.9 mM (0.7 g L^{-1}) and 14.6 mM (1.7 147 g L^{-1}) (Figure 2D). These concentrations were similar to the one measured in aero-148 bic conditions but with 30 times less of biomass. The linearity of the organic acids 149 production kinetics seemed to indicate that this production was mainly related to 150 biomass concentration and not to specific growth rate. From the results obtained, it 151 could be concluded that (i) similar results were obtained in the two-compartment and 152 single compartment aerobic bioreactors, (ii) in fully-anaerobic cultures, no growth 153 but organic acids production was observed, (iii) in fully-aerobic culture conditions, 154 exponential growth but no significant organic acids production could be measured. 155

156 3.2. Modeling of oxygen fluctuations imposed to C. glutamicum

For the experiments with aeration ratios $0 < \alpha < 1$ (experiments 1 to 6 in Table 1), 157 fluctuations of DOC were imposed by continuously circulating cells from the aerobic 158 bioreactor operating at a DOC of 50 % of air saturation to the anaerobic bioreactor 159 (DOC = 0 % and N_2 sparging). Regarding bioreactors geometry, agitation and cir-160 culation conditions, it could be assumed as a first approximation that the two mixing 161 vessels used were similar to homogeneous Continuous Stirred-Tank Reactor (CSTR) 162 vessels while connection tubes could be assumed to real plug-flow bioreactors. Using 163 a constant power number in the turbulent regime for the impeller $(N_{p0}=4)$ and the 164 model proposed by Nienow [1], the mixing times in both vessels were also estimated 165 between 1 and 2 s. Thus, these values were two orders of magnitude lower than the 166 mean residence time (Table 1). Lastly, the characteristic time of oxygen consump-167 tion from 50 to 0 % of air saturation was previously estimated at 25 s [27], which is 168 one order of magnitude higher than the mixing time. This confirms the validity of 169 bioreactor homogeneity for the set-up proposed. 170

Usually, the mean residence time is used in scale-down studies to characterize the set-up and the period of dissolved oxygen (or other substrates) oscillations of concentration. However, mixed bioreactors also perform a mixing of the microbial populations through the residence time distributions (RTD) imposed. While in the case of PF bioreactors, it could be supposed that RTD only consists in a delay function, in the case of CSTR, for a mean residence time τ , the RTD E(t) takes the well-known following form:

$$E(t) = \frac{1}{\tau} \exp\left(-t/\tau\right) \tag{2}$$

Supposing that the bacteria perfectly followed the liquid flow, the succession of 178 DOC oscillations encountered was thus specific to each bacterium and related to the 179 RTD distributions in each CSTR, which indeed represented the probability for a given 180 entity to spend a time t in the bioreactor. It is thus necessary to first validate the robustness of the set-up by quantifying the dispersion of the aeration ratio α around its mean value given by equation (1). Aiming at this, the oscillations encountered by a statistically representative population of 1,000 microbial sub-populations were 184 modeled using a dedicated Matlab script. From the oscillations profiles obtained, it 185 was then possible to calculate the dynamic fraction of time spent in aerobic conditions 186 $\beta(j,M)$ for each sub-population j after M circulations or turns inside the set-up. 187 Regarding the residence time in each connection pipe, it was considered that the 188 pipe connecting aerobic compartment to anaerobic one promoted aerobic culture 189 conditions while the other one applied anaerobic environment. Thus, the dynamic 190 ratio $\beta(j, M)$ was determined using the following expression:

$$\beta(j,M) = \frac{\sum_{i=1}^{M} \left[t_1(i,j) \right] + \left(MV_{tube} \right) / Q}{\sum_{i=1}^{M} \left[t_1(i,j) + t_2(i,j) \right] + \left(2MV_{tube} \right) / Q} j \in 1...1,000$$
 (3)

With $t_1(i,j)$ and $t_2(i,j)$ the times spent by each individual bacteria group j in aerobic and anaerobic conditions. The values of $t_1(i,j)$ and $t_2(i,j)$ were randomly determined in the distribution functions provided by equation 2 and by using the dedicated function of the Statistics and Machine Learning toolbox of Matlab2018 software. The value of M was chosen to match the simulation time to the experimental culture duration. The variation of β obtained for $\alpha = 0.33$ (experiment 4) and $\alpha = 0.67$ (experiment 5) are given in Figure 3A-B. It can be noticed that, as ex-

pected each dynamic profile of aerobic fractions progressively converged to the mean value α (equation 1) but also that some of the bacteria may exhibit sensibly higher 200 or lower values of aeration fraction, especially during the first hours of culture. 201 As a complementary result, the equivalent RTD of the scale-down set-up was deter-202 mined using closed-loop equivalent model, simulated using the Simulink package of 203 Matlab software. Details of the model the model are given in Supplementary 1. At 204 time t=0, a Dirac pulse of numerical tracer was injected at the inlet of compart-205 ment 1 while its concentration was record at the outlet of compartment 2. Each 206 CSTR compartment was modeled using a first-order model in Laplace space while 207 pipes were described by a pure delay model. Volume-averaged tracer concentration 208 $\langle c \rangle$ was also calculated. Simulation results are reported in Figure 4. Simulations 3-5 209 and 4-6, which only consisted in a permutation of compartments 1 and 2 provided 210 the same RTD distributions as compartment order has no impact on the result-211 ing RTD. These distributions show that the number-averaged value of aeration rate 212 progressively reach the equilibrium value with a time varying from 600 s to 2000 s 213 approximately, depending on the operating conditions applied. However, it should 214 be kept in mind that, once this mean value reached, some discrepancies may still 215 exist from one sous-group to another, as indicated by results of Figure 3. 216

3.3. Cultures under oscillating DOC conditions

To study the impact of dissolved oxygen gradients encountered by cells in largescale bioreactors, C. glutamicum 2262 $\Delta ldhA$ was continuously circulated between the aerobic and anaerobic compartments of the scale-down set-up. The impact of DOC oscillations on microbial growth kinetics and glucose consumption were de-

picted in Figure 5. When the cells were cultivated in fully aerobic conditions (reference culture), the maximal biomass concentration reached a value of 19 g_{CDW} 223 L^{-1} (Figure 5A). For a mean aeration fraction $\alpha = 0.67$, no significant difference 224 was observed between experiments 5 and 6 and the maximal biomass accumulated 225 was 16.3 g_{CDW} L⁻¹. Compared to the reference culture, circulation between aerobic 226 and anaerobic environment with this mean aeration fraction resulted in a biomass 227 concentration decrease of approximately 14 \%. Similar growth were also obtained 228 comparing mean aeration fractions of $\alpha = 0.33$ (experiments 3 and 4) but, compara-229 tively to reference culture, a decrease of 31 % in maximal biomass concentration was 230 noticed. Thus, experiments 3 to 6 seemed to indicate that, in the range of culture 231 conditions studied, increasing the residence time while maintaining mean aeration 232 fraction had no sensible influence on bacterial growth. For lowest mean aeration frac-233 tions of α =0.25 and 0.2, an important decrease of maximal biomass concentration 234 was observed with a 37 % and 51 % decrease in comparison with reference culture, 235 respectively. Lastly, when C. glutamicum 2262 $\Delta ldhA$ was cultured in two anaer-236 obic bioreactors (α =0), no sensible growth was observed, resulting in a loss of 96 237 % of the maximal biomass concentration compared to the reference culture (Figure 238 5A). Moreover, Figure 6 showed that μ_{max} increased linearly with the mean aeration 239 fraction α and varied between 0.02 h⁻¹ and 0.6 h⁻¹ for $\alpha = 0$ and $\alpha = 1$, respec-240 tively. This would indicate that the apparent specific growth rate of the bacteria was 241 strongly related to mean fraction of aeration and would thus also impact the time 242 necessary to reach the maximal biomass concentration $t(X_{max})$. Indeed, the report of the quantity $1/t(X_{max})$ also indicated a linear relationship between both variables

(Figure 6). It could be thus suggested that the aerobic oxidative metabolism of the bacteria could sequentially operate, without lag phase but with a loss of productivity, 246 as indicated by the decrease of the maximal biomass concentration (Figure 5). This 247 may indicate an apparent and number-averaged metabolism able to rapidly switch 248 from aerobic to anaerobic culture conditions; this will be further discussed in the 249 paragraph dedicated to kinetics modeling (paragraph 3.5). 250 Influence of DOC oscillations on the organic acids production by C. glutamicum 251 $2262 \Delta ldhA$ was also investigated. No significant concentrations of organic acids 252 were measured for aeration fraction strictly higher than 0. This could probably be 253 explained by the fact that the rapid transition from aerobic to anaerobic culture 254 conditions do not promote organic acids production, as demonstrated in a preceding 255 paper [26] but also that, faced to low glucose concentrations, C. glutamicum 2262 256 $\Delta ldhA$ may use organic acids as carbon source for its growth [27]. Concerning glu-257 cose consumption and according to Figure 5B, the fastest glucose consumption was 258 obtained for the reference culture ($\alpha = Bio_{Ref1}$ and Bio_{Ref2}) with a total glucose ex-259 haustion, which was observed within 10 hours. For the lower mean aeration ratios, 260 glucose was also totally consumed later than for the reference cultures. Indeed, in 261 the absence of aeration ($\alpha = 0$), 90 % of glucose remained in the culture (Figure 262 5B). According to substrate flux distribution, when cultivated under one aerobic or 263 two interconnected aerobic bioreactors, the carbon was thus mainly converted into 264 biomass with maximal biomass on glucose yield $Y_{X/S}$ of 0.5 g_{CDW} $g_{glucose}^{-1}$ (Figure 265 7). This yield progressively decreased when the mean fraction of aeration also de-266 creased. Thus, in comparison with the fully aerobic reference culture, maximal yield

showed a 56 % decrease in the scale-down experiment with mean aeration fraction of 0.2. Indeed, this yield dropped to $0.07 \text{ g}_{CDW} \text{ g}_{glucose}^{-1}$ for the fully anaerobic culture. It could be also noted that maximal biomass concentration and maximal specific glucose consumption rate exhibited similar linear trends while, similarly to maximal specific growth rate, maximal biomass to glucose yield was not linearly linked to the mean fraction of aeration. This would thus further suggest the hypothesis of 'on/off' oxidative metabolism of C. glutamicum during their culture in the scale-down set-up.

275 3.4. Growth kinetic modeling using a RTD-Monod model

To get further insight in the microbial physiological response, it was proposed to couple the results of RTD modeling with a Monod growth kinetic model. First, Monod law was applied to model the growth of each simulated bacteria i, characterized by their concentration X_i :

$$\frac{dX_i}{dt} = \mu_{max} \frac{[Gluc]}{[Gluc] + K_s} X_i - k_d X_i, \quad i \in \{1 \dots 1, 000\}$$
 (4)

A cell death rate was added in the growth kinetics to model the decrease of biomass concentration observed experimentally (Figure 5A) and the shape of growth kinetics for each mean fraction of aeration; death kinetics of group i was thus modeled using a first-order kinetic equation $k_d X_i$. The total biomass concentration was then directly obtained by summing the concentration of each group $i: X = \sum_{i=1}^{N} X_i$. For glucose consumption, a constant biomass to glucose yield was supposed:

$$\frac{d[Gluc])}{dt} = -\frac{\mu X}{Y_{X/S}} \tag{5}$$

The kinetic modeling was thus based on these hypotheses.

286

296

297

298

299

301

303

304

305

- 1. Only N=1000 groups of bacteria were tracked inside the two bioreactors to 287 decrease calculation time. Each group thus represented an initial biomass con-288 centration of X_0/N g_{CDW} L⁻¹. 289
- 2. Kinetic parameters, namely maximal specific growth rate μ_{max} , biomass on 290 substrate yield $Y_{X/S}$, death rate k_d and half-velocity constant K_s were main-291 tained constant whatever the culture modeled. Whereas μ_{max} , $Y_{X/S}$ and k_d 292 were determined using kinetic data of the fully aerobic reference culture, K_s was given by Seletzky [29]. The values of the kinetic parameters were given in 294 Table 2. 295
 - 3. In the aerobic bioreactor, bacteria grew and consumed glucose, whatever the DOC oscillations imposed before (no history effect) and following equations 4 and 5. It was also assumed that transition from an aerobic to aerobic metabolism was immediate.
- 4. In the anaerobic bioreactor, bacteria neither grew nor produced organic acids 300 nor consumed glucose and only the death rate was applied on biomass concentration. In fact, at every run, the bacteria switched promptly from aerated 302 to non-aerated zones, whereas a suitable induction of anaerobic metabolism requires a progressive transition from aerobic to anaerobic [26]. Growth and glucose consumption were thus supposed immediately stopped when the microorganisms entered the anaerobic bioreactor.
- The results obtained by the RTD-kinetic model were given in Figure 8. It can be 307 noted that the results were in very good agreement with the experimental mea-

surement of biomass concentrations. In particular, the coupled RTD-growth kinetic model was able to satisfactory predict the decrease of maximal biomass concentra-310 tion X_{max} and the increase of the time necessary to reach X_{max} when the mean 311 fraction of aeration was increased. This result confirmed the fact that, if a 'on/off' 312 metabolism was supposed for the oxidative metabolism of each bacterium, the global 313 physiological response of the whole microbial population was matching the experimental observations. As noticed before, the operating mode of culture chosen in the 315 present paper was batch for the culture medium despite the fed-batch mode is now 316 preferred at the industrial scale. The main consequence of this choice was an earlier 317 depletion of glucose and thus of microbial growth. However, as the focus was mainly 318 put on the impact of DOC oscillations during the growth phase, this had no impact 319 on the results of the model. Furthermore the earlier death after glucose depletion 320 was taken into account in the model through the death rate k_d . 321

322 4. Discussion

This study provided new insights into growth responses of C. glutamicum 2262 $\Delta ldhA$ when subjected to quantified oscillating DOC. The comparison of reference fully aerobic cultures either performed in a single aerobic compartment or two interconnected aerobic bioreactors revealed unchanged growth and metabolic responses (Figure 2A-D). However, subjecting C. glutamicum 2262 $\Delta ldhA$ to various mean aeration fractions α by continuously circulating bacterial cells between an aerobic and an anaerobic bioreactor had various impacts on cell growth and organic acids production. For instance, for experiments 5 and 6 ($\alpha = 0.67$), DOC oscillations with

residence times in the anaerobic bioreactor of 138 s and 551 s respectively (Table 1 and Figure 3) resulted only in a small decrease (14 %) of maximal biomass con-332 centration and glucose uptake rate despite the bacteria were oxygenated only 67 % 333 of total culture time. Scale-down experiments using stirred tank bioreactor (STR) and plug flow reactor (PFR) for the culture of C. glutamicum ATCC 13032 under 335 DOC oscillations with residence times in anaerobic vessel of 45 and 87 s with total 336 oxygenation ratio of 82 %, have also reported unchanged growth yields [30]. In our 337 case, the time spent in anaerobic bioreactor was sensibly higher, which could explain 338 the decrease observed. It is also interesting to notice that biomass concentration 339 decrease was also observed in scale-down systems, with anaerobic residence times of 340 the same order of magnitude, but for other microorganisms such as Saccharomyces 341 cerevisiae [31]. When the anaerobic residence time was increased to 551 s while 342 aerobic residence time was 138 s (condition $\alpha = 0.2$ in Table 1) or anaerobic resi-343 dence of 616 s associated to aerobic residence time of 206 s (condition $\alpha = 0.25$ in 344 Table 1), detrimental consequences on microbial growth and glucose consumption 345 were observed (Figure 5). In two-compartment scale-down experiment, comparing 346 plug-flow and stirred tank characteristics, Limberg et al. [21] observed a 25 % de-347 crease in growth rate and noted an interesting similarity between that decrease and 348 the two-compartment volume proportion. Like in our study, the reduction was ex-349 plained by growth stop in the oxygen-deprived compartment. By simulating DOC 350 oscillations effects on B. subtilis, using a scale-down approach, Amanullah et al. [32] 351 reported a similar decrease in maximal biomass concentration and specific growth 352 rate when the circulation time was increased at a constant ratio of volume aerobic 353

reactor/volume anaerobic reactor. Decreasing the mean aeration ratio resulted in 354 lengthening the culture time. Similarly to our results, Oosterhuis et al. [33] reported 355 detrimental influence of oscillating DOC, not only on gluconic acid productivity but 356 also on the rate of growth of Gluconobacter oxydans. In our scale-down study, minor 357 quantities of organic acids were obtained when C. qlutamicum was subjected to DOC 358 fluctuations. Indeed, in C. glutamicum, it is well known that the lack of oxygen and 359 nitrate as external electron acceptors in such conditions resulted in cell growth stop 360 but still in fermentation of carbohydrates into organic acids [15, 34, 35]. When C. 361 $qlutamicum 2262 \Delta ldhA$ was cultured in two interconnected anaerobic bioreactors 362 $(\alpha = 0)$, the concentration of organic acids was maximal although growth was al-363 most undetectable. For the other experiments $(\alpha > 0)$, organic acids were produced 364 and re-consumed as a second substrate as already reported in previous work [27] in 365 shaking flasks. Metabolization of produced organic acids have also been reported 366 in STR - PFR scale down of C. glutamicum; the majority of glucose entering the 367 PFR was indeed transformed into lactate in the PFR and which was further quickly 368 metabolized once the bacteria were in the aerated STR again [30]. Through the dif-369 ferent scale-down experiments, our results showed that decreasing the volume ratio 370 resulted in a negative impact on growth performance while fermentation products 371 accumulation were slightly enhanced but still anecdotic. Recent scale-down stud-372 ies involving different strains of C. qlutamicum performed in a two compartment 373 STR-PFR system, revealed no loss of process performance with DOC oscillation 374 frequencies in the minute range. Indeed, analysis of proteome, metabolome, tran-375 scriptome indicated that no change was noted in the response to DOC oscillations. 376

Therefore, they emphasized the robustness of C. glutamicum in comparison to other industrial microorganisms [18, 30]. This conclusion was verified in our study when 378 experiments were performed with mean aeration fractions between 0.67 and 1. For 379 these conditions, the physiological response of C. glutamicum was not significantly 380 different from those of fully-aerobic reference culture (Figure 5). However, when 381 mean aeration fraction were below 0.33, maximal substrate uptake rate decreased from 1.3 g g_{CDW}^{-1} h^{-1} to 0.2 g g_{CDW}^{-1} h^{-1} (Figure 7) associated to bacterial growth 383 performance loss and overflow of side product increase. However, although C. qlu-384 tamicum showed robustness, Lemoine et al. [19] showed in two and three scale-down 385 that mimic substrate and oxygen gradients, alterations in extra and intra-cellular 386 metabolite concentrations. For example, lysine product yield was seen to be reduced 387 in scale-down cultivation compared to cultivations at homogeneous conditions. To 388 deepen the understanding on C. glutamicum performance in scale down tailoring the 389 industrial conditions, Lemoine et al. [20] applied their three-compartment system 390 with complex medium based on several carbon sources and observed drastic reduc-391 tion of growth and volumetric product yield of a cadaverine with accumulation of 392 many short chain fatty acids. Finally, C. glutamicum has been demonstrated to be 393 able to switch with 100 s from aerobic respiration to fermentative pathways [36, 37] 394 ; these times were similar to the ones studied in the present work and thus confirm 395 the agreement of our results with literature data. Lastly, our study proposed an 396 original coupled RTD-growth model that considered independently 1000 microbial 397 groups based on their respective residence time in each vessel. A very good agree-398 ment was obtained between our experimental data and model simulations results. In

particular, this suggested that the growth of C. glutamicum 2262 $\Delta ldhA$ observed in our scale-down set-up could be modeled by considering kinetic parameters (maximal specific growth rate, biomass on glucose yield) that were independent of the mean aeration fraction. Thus, these parameters could be determined in aerobic culture conditions and their use extended to scale-down experiments. To our knowledge, growth kinetics modeling in scale-down systems, considering the RTD of the systems is, to date, original in literature.

5. Conclusion

Using a two CSTR scale-down set-up, the impact of mean aeration fraction on C. glutamicum 2262 $\Delta ldhA$ growth and organic acids production was experimentally studied and modeled using a RTD-kinetic model. Our results showed that, in the range of culture conditions studied, C. glutamicum 2262 $\Delta ldhA$ was strongly related to the value of mean aeration fraction but that the organic acids production was non-significant due to microbial reuptake. The model results were in excellent agreement without kinetic parameter fitting. Indeed, it could be shown that fully aerobic kinetic data could be directly transposed to oscillating DOC culture conditions.

416 6. Acknowledgments

The authors would like to thank the french ICEEL Carnot Institute for its financial support.

Nomenclature

	Variables		
	DOC	Dissolved Oxygen Concentration	(% air sat.)
	k_d	Death rate	(s^{-1})
	M	Number of circulations	()
	N	Agitation rate	(s^{-1})
	Np_0	Power number	()
	Q	Circulation flow rate	$(m^3 s^{-1})$
	P	Power dissipation	(W)
	Re	Reynolds number	()
	V_1	Volume of aerobic bioreactor	(m^3)
	V_2	Volume of anaerobic bioreactor	(m^3)
	V_{tube}	Volume connection tube	(m^3)
420	vvm	Volume of gas per volume of liquid and per minute	$(L L^{-1} h^{-1})$
	X_f	Fitted biomass concentration	$(g_{CDW} L^{-1})$
	X	Biomass concentration	$(g_{CDW} L^{-1})$
	Greek letters		
	α	Aeration ratio	()
	β	Dynamic fraction of aeration	()
	η	Dynamic viscosity	(Pa s)
	ho	Density	$({\rm kg~m^{-3}})$
	μ	Specific growth rate	(h^{-1})
	$ au_1$	Mean residence time in compartment 1	(s)
	$ au_2$	Mean residence time 22 compartment 2	(s)

References

- [1] A. Nienow, On impeller circulation and mixing effectiveness in the turbulent flow regime, Chemical Engineering Science 52 (1997) 2557–2565.
- [2] A. R. Lara, E. Galindo, O. T. Ramírez, L. A. Palomares, Living with heterogeneities in bioreactors, Molecular Biotechnology 34 (2006) 355–381.
- [3] A. Sweere, K. C. A. Luyben, N. Kossen, Regime analysis and scale-down: tools to investigate the performance of bioreactors, Enzyme and Microbial Technology 9 (1987) 386–398.
- [4] P. K. Namdev, N. Irwin, B. Thompson, M. R. Gray, Effect of oxygen fluctuations on recombinant *Escherichia coli* fermentation, Biotechnology and Bioengineering 41 (1993) 666–670.
- ⁴³³ [5] F. Bylund, F. Guillard, S.-O. Enfors, C. Trägårdh, G. Larsson, Scale down of recombinant protein production: a comparative study of scaling performance,
 ⁴³⁴ Bioprocess and Biosystems Engineering 20 (1999) 377–389.
- et al., Studies related to the scale-up of high-cell-density *Escherichia coli* fed-batch fermentations using multiparameter flow cytometry: Effect of a changing microenvironment with respect to glucose and dissolved oxygen concentration,

 Biotechnology and Bioengineering 70 (2000) 381–390.
- [7] N. Oosterhuis, N. Kossen, Dissolved oxygen concentration profiles in a

- production-scale bioreactor, Biotechnology and Bioengineering 26 (1984) 546–550.
- [8] E. A. Sandoval-Basurto, G. Gosset, F. Bolívar, O. T. Ramírez, Culture of Escherichia coli under dissolved oxygen gradients simulated in a two-compartment scale-down system: Metabolic response and production of recombinant protein,
 Biotechnology and Bioengineering 89 (2005) 453–463.
- 448 [9] A. R. Lara, L. Leal, N. Flores, G. Gosset, F. Bolívar, O. T. Ramírez, Transcriptional and metabolic response of recombinant *Escherichia coli* to spatial dissolved oxygen tension gradients simulated in a scale-down system, Biotechnology and Bioengineering 93 (2006) 372–385.
- ⁴⁵² [10] C. Langheinrich, A. W. Nienow, et al., Control of ph in large-scale, free suspen-⁴⁵³ sion animal cell bioreactors: alkali addition and ph excursions, Biotechnology ⁴⁵⁴ and Bioengineering 66 (1999) 171–179.
- [11] F. Bylund, E. Collet, S.-O. Enfors, G. Larsson, Substrate gradient formation in
 the large-scale bioreactor lowers cell yield and increases by-product formation,
 Bioprocess Engineering 18 (1998) 171–180.
- ⁴⁵⁸ [12] J. Bryant, The characterization of mixing in fermenters, Advances in Biochemical Engineering 5 (1977) 101–123.
- ⁴⁶⁰ [13] L. Eggeling, H. Sahm, L-glutamate and l-lysine: traditional products with ⁴⁶¹ impetuous developments, Applied Microbiology and Biotechnology 52 (1999) ⁴⁶² 146–153.

- ⁴⁶³ [14] T. Hermann, Industrial production of amino acids by coryneform bacteria,

 ⁴⁶⁴ Journal of Biotechnology 104 (2003) 155–172.
- Metabolic analysis of Corynebacterium glutamicum during lactate and succinate productions under oxygen deprivation conditions, Journal of Molecular Microbiology and Biotechnology 7 (2004) 182–196.
- ⁴⁶⁹ [16] B. Litsanov, M. Brocker, M. Bott, Toward homosuccinate fermentation:

 metabolic engineering of *Corynebacterium glutamicum* for anaerobic production

 of succinate from glucose and formate, Applied and Environmental Microbiology

 78 (2012) 3325–3337.
- ⁴⁷³ [17] B. Schilling, W. Pfefferle, B. Bachmann, W. Leuchtenberger, W.-D. Deckwer, A ⁴⁷⁴ special reactor design for investigations of mixing time effects in a scaled-down ⁴⁷⁵ industrial l-lysine fed-batch fermentation process, Biotechnology and bioengi-⁴⁷⁶ neering 64 (1999) 599–606.
- F. Käß, I. Hariskos, A. Michel, H.-J. Brandt, R. Spann, S. Junne, W. Wiechert,
 P. Neubauer, M. Oldiges, Assessment of robustness against dissolved oxygen/substrate oscillations for *Corynebacterium glutamicum* dm1933 in twocompartment bioreactor, Bioprocess and Biosystems Engineering 37 (2014)
 1151–1162.
- ⁴⁸² [19] A. Lemoine, N. Maya Martinez-Iturralde, R. Spann, P. Neubauer, S. Junne, Re-⁴⁸³ sponse of *Corynebacterium glutamicum* exposed to oscillating cultivation condi-

- tions in a two-and a novel three-compartment scale-down bioreactor, Biotechnology and Bioengineering 112 (2015) 1220–1231.
- Performance loss of Corynebacterium glutamicum cultivations under scale-down conditions using complex media, Engineering in Life Sciences 16 (2016) 620–632.
- tank reactor flow characteristics in two-compartment scale-down bioreactor:

 Setup-specific influence on the metabolic phenotype and bioprocess performance
 of corynebacterium glutamicum, Engineering in Life Sciences 16 (2016) 610–619.
- ⁴⁹³ [22] J. Buchholz, M. Graf, A. Freund, T. Busche, J. Kalinowski, B. Blombach,
 R. Takors, Co₂/hco₃- perturbations of simulated large scale gradients in a

 ⁴⁹⁵ scale-down device cause fast transcriptional responses in *Corynebacterium glu-*⁴⁹⁶ tamicum, Applied Microbiology and Biotechnology 98 (2014) 8563–8572.
- ⁴⁹⁷ [23] C. Haringa, W. Tang, A. T. Deshmukh, J. Xia, M. Reuss, J. J. Heijnen, R. F. Mudde, H. J. Noorman, Euler-lagrange computational fluid dynamics for (bio) reactor scale down: an analysis of organism lifelines, Engineering in life sciences 16 (2016) 652–663.
- ⁵⁰¹ [24] C. Haringa, A. T. Deshmukh, R. F. Mudde, H. J. Noorman, Euler-lagrange ⁵⁰² analysis towards representative down-scaling of a 22 m3 aerobic s. cerevisiae ⁵⁰³ fermentation, Chemical Engineering Science 170 (2017) 653–669.
- 504 [25] C. Haringa, H. J. Noorman, R. F. Mudde, Lagrangian modeling of

- hydrodynamic-kinetic interactions in (bio) chemical reactors: practical implementation and setup guidelines, Chemical Engineering Science 157 (2017) 159– 168.
- ⁵⁰⁸ [26] A.-K. Kaboré, E. Olmos, M. Fick, F. Blanchard, E. Guedon, S. Delaunay,
 ⁵⁰⁹ Aerobiosis–anaerobiosis transition has a significant impact on organic acid pro⁵¹⁰ duction by *Corynebacterium glutamicum*, Process Biochemistry 52 (2017) 10–21.
- 511 [27] A. K. Kaboré, E. Olmos, F. Blanchard, M. Fick, S. Delaunay, E. Guedon, Impact
 512 of gas-liquid mass transfer on organic acids production by *Corynebacterium*513 glutamicum in unbaffled shake flasks, Biochemical Engineering Journal 101
 514 (2015) 237-247.
- ⁵¹⁵ [28] A. Schäfer, A. Tauch, W. Jäger, J. Kalinowski, G. Thierbach, A. Pühler, Small mobilizable multi-purpose cloning vectors derived from the *Escherichia coli* plasmids pk18 and pk19: selection of defined deletions in the chromosome of *Corynebacterium glutamicum*, Gene 145 (1994) 69–73.
- 519 [29] J. M. Seletzky, U. Noak, J. Fricke, E. Welk, W. Eberhard, C. Knocke, J. Büchs,
 520 Scale-up from shake flasks to fermenters in batch and continuous mode with
 521 Corynebacterium glutamicum on lactic acid based on oxygen transfer and ph,
 522 Biotechnology and Bioengineering 98 (2007) 800–811.
- [30] F. Käß, S. Junne, P. Neubauer, W. Wiechert, M. Oldiges, Process inhomogeneity leads to rapid side product turnover in cultivation of *Corynebacterium*[524] glutamicum, Microbial Cell Factories 13 (2014b) 6.

- ⁵²⁶ [31] S. George, G. Larsson, S.-O. Enfors, A scale-down two-compartment reactor with controlled substrate oscillations: metabolic response of *Saccharomyces cere-*⁵²⁸ *visiae*, Bioprocess and Biosystems Engineering 9 (1993) 249–257.
- [32] A. Amanullah, B. C. Buckland, A. W. Nienow, Mixing in the fermentation and cell culture industries, Wiley Online Library, 2004.
- 531 [33] N. Oosterhuis, N. Kossen, A. Olivier, E. Schenk, Scale-down and optimization 532 studies of the gluconic acid fermentation by *Gluconobacter oxydans*, Biotech-533 nology and Bioengineering 27 (1985) 711–720.
- 534 [34] H. B. T. Khuat, A. K. Kabore, E. Olmos, M. Fick, J. Boudrant, J.-L. Goergen,
 535 S. Delaunay, E. Guedon, Lactate production as representative of the fermen536 tation potential of *Corynebacterium glutamicum* 2262 in a one-step process,
 537 Bioscience, Biotechnology and Biochemistry 78 (2014) 343–349.
- ing oxygen limited growth of *Corynebacterium glutamicum* and the consequences for amino acid overproduction, Biotechnology Letters 15 (1993) 449–454.
- [36] S. Okino, M. Inui, H. Yukawa, Production of organic acids by Corynebacterium
 glutamicum under oxygen deprivation, Applied Microbiology and Biotechnology
 68 (2005) 475–480.
- ⁵⁴⁴ [37] S. Yamamoto, M. Sakai, M. Inui, H. Yukawa, Diversity of metabolic shift in response to oxygen deprivation in *Corynebacterium glutamicum* and its close relatives, Applied Microbiology and Biotechnology 90 (2011) 1051–1061.

Table legends

- Table 1. Scale-down culture conditions.
- Table 2. Values of the optimized parameters for kinetic modeling.

550 Tables

Table 1

Table 1: Scale-down culture conditions.								
			Compartment 1		Compartment 2			
Experiment	α	Q	V_1	$ au_1$	$\mathrm{DOC^1}$	V_2	$ au_2$	DOC^2
		(mL/s)	(L)	(s)	(% air sat.)	(L)	(s)	(% air sat)
reference Bio_{ref1}	$1^{(4)}$	n/a	1.5	n/a	50	n/a	n/a	$\overline{\mathrm{n/a}}$
reference Bio_{ref2}	$1^{(3)}$	7.3	1.5	205	50	1.5	205	50
reference Bio_{ref3}	0	7.3	1.5	205	$0^{(1)}$	1.5	205	0
1	0.2	7.3	1	137	50	4	548	0
2	0.25	7.3	1.5	205	50	4.5	616	0
3	0.33	7.3	1	137	50	2	274	0
4	0.33	1.8	1	556	50	2	1111	0
5	0.67	7.3	2	274	50	1	137	0
6	0.67	1.8	2	1111	50	1	556	0

⁽¹⁾ In this case, once the oxygen probe was calibrated, the culture was started without $\operatorname{air/oxygen}$ sparging nor nitrogen sparging whereas the Bio_{N2} compartment was sparged continuously with nitrogen.

⁽²⁾ Nitrogen was sparged continuously to warrant anaerobic conditions.

⁽³⁾ Corresponded to two aerobic bioreactors interconnected.

⁽⁴⁾ Corresponded to a single anaerobic bioreactor.

Table 2

Table 2: Values of the optimized parameters for kinetic modeling

Parameter	μ_{max} (h ⁻¹)	$Y_{X/S}$ (g g $^{-1}_{CDW}$)	$K_s ext{ (g L}^{-1})$	$k_d (\mathrm{h}^{-1})$
Value	0.55*	0.4*	0.0045**	0.0005*

^(*) Parameters determined using the fully aerobic reference culture ${
m Bio}_{Ref1}$. (**) Value given by [29].

53 Figure legends

Figure 1. Experimental set-up.

555

Figure 2. Reference culture kinetics of C. glutamicum 2262 $\Delta ldhA$ under con-556 stant dissolved oxygen concentration. Temporal profiles of biomass concentration 557 and glucose concentrations in a single bioreactor with constant dissolved oxygen 558 concentration of 50 % of air saturation (A) and in two interconnected stirred tank 559 bioreactors with constant dissolved oxygen concentration of 50 \% of air saturation 560 (B). Temporal profiles of biomass concentration and glucose concentration (C) and 561 organic acids concentration (D) in two interconnected stirred anaerobic bioreactors. 562 The different symbols represent: glucose (\Box) , biomass (\bullet) , succinate (*), acetate (\blacktriangleleft) , 563 pyruvate (\spadesuit) .

565

Figure 3. Variation of the dynamic fraction of aeration β for 10,000 bacteria in function of time for mean aeration fractions α =0.33 (A) and α =0.67 (B).

568

Figure 4. Modeled Residence Time Distribution in the scale-down set-up normalized by volume-averaged tracer concentration $\langle c \rangle$. Operating conditions as given by Table 1 were experiment 1, (\cdots) , experiment 2 $(\cdot - \cdots)$, experiment 3 and 5 $(- - \cdots)$, experiments 4 and 6 (-).

573

Figure 5. Influence of dissolved oxygen oscillation on C. glutamicum 2262 $\Delta ldhA$ growth and substrate consumption during a scale-down cultures. (A). Growth kinet-

```
ics; (B). Glucose uptake profiles. The mean aerobic fractions \alpha are: 0 (×), 0.2 (*), 0.25 (\blacktriangleright), 0.33 - experiment 3 (\blacklozenge), 0.33 - experiment 4 (\diamondsuit), 0.67 - experiment 5 (\blacksquare), 0.67 - experiment (\square) 0.67, 1a (\bullet), 1b (\circ).
```

579

Figure 6. Relationship between mean fraction of aeration α , $1/t(X_{max})$ (\square) and maximal specific growth rate μ_{max} (Δ).

582

Figure 7. Relationship between mean fraction of aeration α , maximal biomass concentration X_{max} (\square), maximal specific glucose consumption rate (\circ) and maximal biomass on glucose yield $Y_{X/S}$ (Δ).

586

Figure 8. Comparison of experimental and modeled growth kinetics and impact of DOC oscillations. Dots are experimental values while continuous lines are modeled kinetics. Mean aerobic fractions α are 0.2 (\square , -••-), 0.25 (\diamondsuit , - - -), 0.33 - experiment 3 (\triangle ,-•-), 0.67 - experiment 5 (*,••), 1 (+, —).

Figure 1




Figure 1: Experimental set-up




Figure 2: Reference culture kinetics of C. glutamicum 2262 $\Delta ldhA$ under constant dissolved oxygen concentration. Temporal profiles of biomass concentration and glucose concentrations in a single bioreactor with constant dissolved oxygen concentration of 50 % of air saturation (A) and in two interconnected stirred tank bioreactors with constant dissolved oxygen concentration of 50 % of air saturation (B). Temporal profiles of biomass concentration and glucose concentration (C) and organic acids concentration (D) in two interconnected stirred anaerobic bioreactors. The different symbols represent: glucose (\square), biomass (\bullet), succinate (*), acetate (\blacktriangleleft), pyruvate (\blacklozenge).

596




Figure 3: Variation of the dynamic fraction of aeration β for 10,000 bacteria in function of time for mean aeration fractions α =0.33 (A) and α =0.67 (B).

598




Figure 4: Modeled Residence Time Distribution in the scale-down set-up normalized by volume-averaged tracer concentration $\langle c \rangle$. Operating conditions as given by Table 1 were experiment 1, (\cdots) , experiment 2 (---), experiment 3 and 5 (---), experiments 4 and 6 (---).

600




Figure 5: Influence of dissolved oxygen oscillation on C. $glutamicum\ 2262\ \Delta ldhA$ growth and substrate consumption during a scale-down cultures. (A). Growth kinetics; (B). Glucose uptake profiles. The mean aerobic fractions α are: $0\ (\times),\ 0.2\ (*),\ 0.25\ (\blacktriangleright),\ 0.33$ - experiment $3\ (\spadesuit),\ 0.67$ - experiment $5\ (\blacksquare),\ 0.67$

602




Figure 6: Relationship between mean fraction of aeration α , $1/t(X_{max})$ (\square) and maximal specific growth rate μ_{max} (Δ).

604




Figure 7: Relationship between mean fraction of aeration α , maximal biomass concentration X_{max} (\square), maximal specific glucose consumption rate (\circ) and maximal biomass on glucose yield $Y_{X/S}$ (Δ).




Figure 8: Comparison of experimental and modeled growth kinetics and impact of DOC oscillations. Dots are experimental values while continuous lines are modeled kinetics. Mean aerobic fractions α are 0.2 (\square , -••-), 0.25 (\Diamond , - - -), 0.33 - experiment 3 (Δ ,-•-), 0.67 - experiment 5 (*,••), 1 (+, -).

608 Supplementary figure

The Simulink model defined for each culture condition was reported on Figure 9.






Figure 9: Modeling of scale-down set-up using Simulink software.




Modelling of lagrangian tracking of the bacteria



Experimental study of C. glutamicum growth in a two-compartment scale-down bioreactor, imposing fluctuating dO_2 .





Kinetic modelling of growth curves under various mean aeration fractions.