



HAL
open science

A critical review of the influence of groundwater level fluctuations and temperature on LNAPL contaminations in the context of climate change

Amélie Cavelan, Fabrice Golfier, Stéfán Colombano, Hossein Davarzani,
Jacques Deparis, Pierre Faure

► To cite this version:

Amélie Cavelan, Fabrice Golfier, Stéfán Colombano, Hossein Davarzani, Jacques Deparis, et al.. A critical review of the influence of groundwater level fluctuations and temperature on LNAPL contaminations in the context of climate change. *Science of the Total Environment*, 2022, 806, pp.150412. 10.1016/j.scitotenv.2021.150412 . hal-03352335

HAL Id: hal-03352335

<https://hal.univ-lorraine.fr/hal-03352335>

Submitted on 23 Sep 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial - NoDerivatives 4.0 International License

1 **A critical review of the influence of groundwater level fluctuations and temperature on LNAPL**
2 **contaminations in the context of climate change**

3 Amélie CAVELAN^{1*}, Fabrice GOLFIER², Stéfan COLOMBANO³, Hossein DAVARZANI³,
4 Jacques DEPARIS³, Pierre FAURE¹

5 ¹ Université de Lorraine, CNRS, LIEC, F-54000 Nancy, France

6 ² Université de Lorraine, CNRS, GeoRessources, F-54000 Nancy, France

7 ³ BRGM (French Geological Survey), F-45100 Orléans, France

8 * Corresponding author: amelie.cavelan@univ-lorraine.fr

9 **Abstract**

10 The intergovernmental panel on climate change (IPCC) predicts significant changes in
11 precipitation patterns, an increase in temperature, and groundwater level variations by 2100. These
12 changes are expected to alter light non-aqueous phase liquid (LNAPL) impacts since groundwater level
13 fluctuations and temperature are known to influence both the mobility and release of LNAPL
14 compounds to air and groundwater. Knowledge of these potential effects is currently dispersed in the
15 literature, hindering a clear vision of the processes at play. This review aims to synthesize and discuss
16 the possible effects of the increase in temperature and groundwater level fluctuations on the behavior of
17 LNAPL and its components in a climate change context. In summary, a higher amplitude of groundwater
18 table variations and higher temperatures will probably increase biodegradation processes, the LNAPL
19 mobility, and spreading across the smear zone, favoring the release of LNAPL compounds to the
20 atmosphere and groundwater but decreasing the LNAPL mass and its longevity. Outcomes will,
21 nevertheless, vary greatly across arid, cold, or humid coastal environments, where different effects of
22 climate change are expected. The effects of the climate change factors linked to soil heterogeneities,
23 local conditions, and weathering processes will govern LNAPL behavior and need to be further clarified.

24 **Keywords:** Light non-aqueous phase liquids; Groundwater; Dissolution, Biodegradation;
25 Volatilization.

26 **1. Introduction**

27 Over the last century, the development of chemical and petroleum industries has led to numerous
28 accidental spills of petroleum products that have greatly affected the long-term quality of groundwater
29 (Güler, 2019). Light non-aqueous phase liquids (LNAPLs), are one the most common source of
30 groundwater pollution (Rivett et al., 2014). When released, LNAPLs redistribute by migrating through
31 the saturated (SZ) and unsaturated zone (USZ) and interacting with groundwater. Redistribution of
32 LNAPL and partitioning of its components cause significant groundwater and soil pollutions (Huntley
33 and Beckett, 2002; Lee and Chrysikopoulos, 1998; McCarthy and Johnson, 1993; Mobile et al., 2012;
34 Nambi and Powers, 2003; Oostrom et al., 2007; Patterson and Davis, 2009). Several petroleum LNAPL
35 compounds are carcinogenic (e.g., benzene) affecting plants, microorganisms, animals, and human
36 health, and making groundwater unsuitable for both agriculture and drinking water supply. Remediation
37 of LNAPL contaminated sites can be prolonged and expensive since LNAPL fuels and oils are usually
38 a complex multi-component mixture with variable physical properties (Newell, 1995). The processes
39 controlling LNAPL remobilization and degradation at contaminated sites are numerous and the relation
40 between them is not always clear (Garg et al., 2017; Sookhak Lari et al., 2019). Better understanding
41 the controlling factors of LNAPL mobilization and remediation processes became, therefore, a major
42 scientific goal these last decades (Alazaiza et al., 2020; Benioug et al., 2019; Chen et al., 2010; Dobson
43 et al., 2007; Ismail et al., 2020; McAlexander and Sihota, 2019; Sookhak Lari et al., 2016b, 2020; Sun,
44 2016; Werner and Höhener, 2002; Zeman et al., 2014).

45 Numerous laboratory, modeling, and field studies have demonstrated that seasonal or pump-
46 induced groundwater level fluctuations may affect LNAPL migration and redistribution (Davis et al.,
47 1993; Lenhard et al., 2019, 2018, 2017; Steffy et al., 1998, 1995), component dissolution rates (Davis
48 et al., 1993; Kechavarzi et al., 2005; Lekmine et al., 2014; Lenhard et al., 2004; Mobile et al., 2012;
49 Teramoto and Chang, 2017), volatilization (Davis et al., 2005; Guo et al., 2019; Illangasekare et al.,
50 2014; McCarthy and Johnson, 1993; Picone et al., 2012; Qi et al., 2020; Soucy and Mumford, 2017;
51 Werner and Höhener, 2002; Zhang et al., 2021), or biodegradation (Dobson et al., 2007; Gupta et al.,
52 2019; Ismail et al., 2020; Rainwater et al., 1993). These works showed that fluctuating groundwater

53 level conditions and/or soil moisture changes affect the vertical dispersion and redistribution of the
54 LNAPL compounds at the capillary fringe, modifying their release into the environment. However, the
55 dynamic nature and the intensity of groundwater level variations may change significantly in the coming
56 decades in response to climate change (Goderniaux et al., 2009; Green et al., 2011; Jarsjö et al., 2020;
57 Smerdon, 2017). Depending on local climatic conditions, more intense groundwater level fluctuations
58 may occur over the next century in response to variations in rainfall intensity and frequency and the
59 increasing use of water resources (Christensen and Christensen, 2007; IPCC, 2014; Nygren et al., 2020).
60 This context may strongly impact the LNAPL mobilization, the contamination lifetime, and the risk for
61 receptors. Moreover, an increase in a few degrees in the mean surface and groundwater temperature is
62 also expected (IPCC, 2014). This phenomenon may affect temperature-dependent mobilization and
63 (bio)degradation processes (Knauss et al., 2000; McAlexander and Sihota, 2019; Yadav et al., 2012;
64 Zeman et al., 2014), further modifying the LNAPL constituents partitioning and release into air and
65 groundwater.

66 Here we review and link literature primarily from the last two decades to form a basis for the
67 possible evolution of all the processes affecting LNAPL mobility, partitioning, and (bio)degradation in
68 the context of climate change. We focus mainly on the two factors that may have the most significant
69 effect on LNAPL: groundwater level variations and temperature changes. A better understanding of
70 likely transitions in the magnitude of the dominant processes provides a basis for better management
71 and mitigation of the risks associated with LNAPL contaminated sites.

72 **2. Historical View**

73 **2.1. LNAPL features**

74 Petroleum LNAPLs (e.g., diesel, gasoline, crude oil) can be long-term persistent sources of
75 groundwater and soil pollution that reach the SZ and USZ upon release. The LNAPL is characterized
76 by a hydrophobic and non-ionic nature in the presence of water and exhibits a lower density than water.
77 While LNAPL can correspond to a single chemical compound such as benzene, it is often a complex
78 mixture of several hundred components with different chemical properties (Güler, 2019; Gupta et al.,

79 2019). Branched and *n*-alkanes (mainly <C₂₅), cycloalkanes, alkenes, cycloalkenes, acetylenes and,
80 BTEX (benzene, toluene, ethylbenzene, xylenes) are common LNAPL components.

81 **2.2. LNAPL mobility, partitioning process, and biodegradation**

82 After the release of LNAPLs into the subsurface, the mobile phase infiltrates downward through
83 the soil porosity (Fig. 1i). During migration through the USZ, a significant part of the pollution can be
84 trapped as residual LNAPL ganglia by capillary forces or sorbed to soil grains. Many of these
85 components have a high vapor pressure and can directly volatilize into soil gas to form potentially
86 harmful VOC emissions (McCarthy and Johnson, 1993; Nambi and Powers, 2003; Patterson and Davis,
87 2009). If a sufficient volume of LNAPL is released, mobile LNAPL can reach and accumulate at the
88 water table (Illangasekare et al., 1995; Powers et al., 1994, 1992) (Fig. 1i). Mobile LNAPL then
89 propagates laterally in the direction of decreasing hydraulic gradient in the capillary fringe, forming
90 residual lenses (Schroth et al., 1995). Mobile and residual LNAPL provide a source of soluble
91 hydrocarbons to water infiltrating through the soil and to surrounding groundwater, forming a dissolved
92 plume of LNAPL constituents (Fig. 1i, Huntley and Beckett, 2002; Lee and Chrysikopoulos, 1998;
93 Mobile et al., 2012). Mechanical dispersion and diffusion combined with the advective groundwater
94 flux then lead to the transverse migration of dissolved phase constituents, increasing the risks to
95 receptors (e.g. drinking water supply) where groundwater is discharged (Picone et al., 2013; Yadav and
96 Hassanizadeh, 2011). It remains complex and challenging to predict the evolution of these LNAPL
97 contaminated environments over time, and the effectiveness of remediation techniques (Newell, 1995).

98 The native microorganisms of the soil also contribute to these variations in degrading LNAPL
99 components (Ortega-Calvo and Alexander, 1994; Zeman et al., 2014). The diversity of the microbial
100 community, microbial processes, and thus hydrocarbon components biodegradation is complex and
101 strongly varies with depth along with redox conditions, electron acceptors' availability, and LNAPL
102 composition (Garg et al., 2017; Sookhak Lari et al., 2019). Biodegradation mediated by microorganisms
103 often follows a redox succession: aerobic, anaerobic respiration, fermentation, or methanogenesis (Garg
104 et al., 2017; Gupta et al., 2019; Irianni-Renno et al., 2016). Works to identify the nature of the
105 microorganisms and the mechanisms controlling bacterial activity are in progress (Bruckberger et al.,

106 2021) and there is no doubt about their major contribution to the LNAPL natural attenuation rates (Rivett
107 and Sweeney, 2019).

108 **2.3. Effect of groundwater table variations at LNAPL sites**

109 Under 'steady-state' water table conditions, dissolution, volatilization processes, and transverse
110 migration of the dissolved LNAPL constituents are relatively limited because of the small vertical
111 dispersion, and the slow diffusion of dissolved LNAPL compounds (Chompusri et al., 2002; Dobson et
112 al., 2007; Gupta et al., 2019; Huntley and Beckett, 2002; Lenhard et al., 1993). Retention and mobility
113 of LNAPL in a saturated porous medium depend on the saturation of each phase in the USZ (air, water,
114 LNAPL). Hysteresis effect strongly driven by the variations of the water table level often occurs, as the
115 mobile LNAPL phase moves vertically along with the groundwater fluctuations (Gatsios et al., 2018;
116 ITRC, 2018; Kemplowski and Chiang, 1990; Steffy et al., 1998). Within the mobile LNAPL phase, the
117 LNAPL saturation is high and water is restricted to smaller pores and exhibits a low relative permeability
118 (Fig. 3). When the water table drops, the mobile LNAPL moves down with the water table level (Figs.
119 1ii, 3ii, Ballesterro et al., 1994; Steffy et al., 1998), causing the redistribution of the LNAPL and the
120 reconfiguration of the partitioning of LNAPL components between the different phases. A part of the
121 LNAPL remains as discontinuous residual LNAPL ganglia in the USZ (Charbeneau, 2007; Jeong and
122 Charbeneau, 2014; Kechavarzi et al., 2005; Kemplowski and Chiang, 1990; Lenhard et al., 1993). The
123 most volatile and soluble compounds of the LNAPL can volatilize or be leached by successive water
124 infiltration and contribute to the evolution of the dissolved plumes (Kechavarzi et al., 2005). The
125 subsequent rise of the water table (Fig. 1iii, 3ii-iii) results in upward redistribution of mobile LNAPL,
126 leaving behind some immobile entrapped LNAPL droplets in the SZ (Charbeneau, 2007; Lenhard and
127 Parker, 1990). The zone of the water table and LNAPL fluctuation is often called the smear zone. During
128 successive drainage/imbibition phases, the effect of capillary pressure, as well as the trapping of fluids
129 in the SZ and USZ, continuously modify the water flow paths (Sookhak Lari et al., 2016a). These
130 hysteresis effects accompanied by additional LNAPL-water interactions (groundwater and rainwater)
131 favor the mobilization of the contaminants (Parker and Lenhard, 1987; Van Geel and Sykes, 1997).
132 Hence, seasonal or pump-induced groundwater level fluctuations often lead to (i) significant

133 redistribution and spreading of the pollutants through the water table fluctuation zone (Fig. 1), (ii) a
134 decrease in the average LNAPL saturation and mass of the mobile LNAPL remaining afterward (Fig. 3,
135 Charbeneau, 2007; Kemblowski and Chiang, 1990; Lenhard et al., 1993; Lenhard and Parker, 1990;
136 Newell, 1995; Reddi et al., 1998; Van Geel and Sykes, 1997), and (iii) a decrease in LNAPL recovery
137 yield.

138 **3. Effects of groundwater table and temperature variations on LNAPL behavior**

139 **3.1. Impact of climate change on groundwater**

140 Climate and groundwater flow systems are in constant dynamic balance. Changes in surface
141 hydrological processes and vegetation cover in response to fluctuations of temperature and precipitation
142 patterns expected in the coming decades will impact the magnitude and the quality of groundwater
143 recharge. In consequence, groundwater levels will also be impacted (Illangasekare et al., 2015; Taylor
144 et al., 2013). In most of the world, the IPCC predicts by the end of the century significant global
145 warming, a decrease in precipitations in the mid-latitudes, and more intense and frequent extreme events
146 (heatwaves, droughts, heavy precipitations, (IPCC, 2018). The mean surface temperature of the globe is
147 expected to increase from 1.5°C to 2°C by 2100. However, the temperature can locally lead to much
148 stronger variations (up to 9°C), this is why higher temperature variabilities were considered in this work.
149 It has been shown that the mean shallow groundwater temperatures mimic variations of mean surface
150 temperature (Menberg et al., 2014; Taylor and Stefan, 2009). An increase in the local surface
151 temperature from 12°C to 20°C should, therefore, lead to a similar increase in mean shallow
152 groundwater temperatures. This may significantly impact groundwater quality (Menberg et al., 2014;
153 Taylor and Stefan, 2009) but also the soil moisture content, the microorganisms' activity, and thus, the
154 LNAPL degradation (McAlexander and Sihota, 2019; Zeman et al., 2014) and mobilization (Margesin
155 and Schinner, 2001; Picone et al., 2012; Yadav and Hassanizadeh, 2011).

156 The intensity and the temporal distribution of precipitation are expected to change around the
157 world (IPCC, 2014). Precipitation is likely to be less frequent from spring to autumn in most parts of
158 the world but will be probably more intense during winter (Dams et al., 2012; Goderniaux et al., 2011,

159 2009). In Europe (except in Scandinavia), a global decrease in the mean daily precipitations up to 23%
160 in summer, and an increase of 12.3% in winter is expected (Christensen and Christensen, 2007). On the
161 contrary, the duration and the intensity of meteorological droughts are expected to increase, as well as
162 the frequency and intensity of extreme precipitation events (+ 25% in Europe by 2100, IPCC, 2014).
163 These changes will affect both the dynamics and the quality of groundwater recharge, leading probably
164 to an intensification of groundwater level variations, an increase in the capillary fringe thickness, and
165 the occurrence of extremely high or low groundwater heads. More intensive pumping rates may also
166 contribute to more rapid and intense variations in groundwater levels. In the southern aquifers of the
167 western United States, the total recharge may decline by 20% by 2100 (Meixner et al., 2016). In Europe,
168 a global decrease in groundwater heads of 8 m can locally occur (Dams et al., 2012; Goderniaux et al.,
169 2011, 2009). Moreover, the rise in the mean surface temperature may cause an increase in irrigation and
170 evapotranspiration rates enhancing decreased groundwater heads, especially during summer and drought
171 events (Green et al., 2011). Such intensification of the groundwater-table fluctuations and global
172 decrease in the mean groundwater heads may favor the trapping and spreading of the LNAPL across the
173 smear zone, causing a greater exposure of the contaminant to attenuation and partitioning processes.
174 The next section, therefore, proposes to summarize current knowledge on the global effect of
175 groundwater level fluctuations and temperature on LNAPL behavior to discuss the potential evolution
176 of LNAPL contaminated sites in this context.

177 **3.2. LNAPL source zone mobility, partitioning, and depletion**

178 The composition and physical-chemical properties of the LNAPL are temperature-dependent.
179 Higher temperatures decrease the interfacial tensions, the viscosity, and the density of the LNAPL,
180 modifying the distribution and the diffusion rate of the organic contaminants through the soil
181 (Colombano et al., 2020; Sleep and Ma, 1997). A higher temperature also decreases the LNAPL soil-
182 water partition coefficients and LNAPL/water interfacial tension, favoring LNAPL mobility (Imhoff et
183 al., 1997; Sleep and Ma, 1997) and decreasing residual LNAPL saturations (Davis, 1994; Philippe et al.,
184 2020; She and Sleep, 1998; Sinnokrot et al., 1971). The vapor diffusion coefficient of gas also increases
185 with temperature (Davis, 1997; Knauss et al., 2000; Seager et al., 1963). In the context of climate change,

186 the earth's surface temperature could locally increase from 12°C to 20°C. The effect of this increase in
187 temperature on the main properties and partitioning coefficients of oil and LNAPL compounds were
188 calculated based on the available data of the literature and gathered in Tab. 1. The oil viscosity decreases
189 up to 41% over this temperature range, increasing the LNAPL mobility (Tab. 1). On the contrary, the
190 variation of the LNAPL density, soil-water partition coefficients, and LNAPL/water interfacial tensions
191 appear to be negligible over this range of temperatures (Gaito et al., 2012; Imhoff et al., 1997; Sleep and
192 Ma, 1997). Ten Hulscher and Cornelissen (1996) revealed that a decrease by 2-3% of the equilibrium
193 sorption constant can be expected under this range of temperatures for most organic pollutants, probably
194 favoring their desorption and remobilization into the air and water and making them more available for
195 degrading microorganisms (McAlexander and Sihota, 2019; Yadav and Hassanizadeh, 2011). However,
196 a striking opposite effect is, nevertheless, observed for BTEX (Tab. 1, David and Moldoveanu, 2019).
197 The effect of temperature on the sorption trends of the contaminants remains thus, difficult to predict,
198 especially because no information is available about the variations in K_{oc} (carbon-water partitioning
199 coefficient) and K_{ow} (octanol-water partitioning coefficient) for the other LNAPL compounds in the
200 investigated range of temperature (Tab. 1). A better understanding of these sorption processes between
201 10-20°C is, therefore, required since they may significantly limit or delay the spreading of the dissolved
202 constituents (Prommer et al., 2002). Calculations based on the literature data compilation show that such
203 an increase in temperature may, nevertheless, strongly increase the saturated vapor pressure of most
204 LNAPL compounds from 25% to 45% (Tab. 1), highly modifying their volatilization rates. In the light
205 of these results, it is clear that the expected temperature rise will probably greatly increase gas and VOC
206 surface emissions, and to a less extent the LNAPL mobility through the soil.

207 Changes in groundwater level also affect LNAPL volatilization and VOC emissions (Guo et al.,
208 2019; Illangasekare et al., 2014; McCarthy and Johnson, 1993; Picone et al., 2012; Qi et al., 2020; Soucy
209 and Mumford, 2017; Werner and Höhener, 2002). Rise and fall successions of the groundwater table
210 level cause the shortening or the lengthening of gas transport pathways from the dissolved LNAPL
211 plume to the surface (Fig. 1, Guo et al., 2019) and enhance mass transfers towards the dissolved LNAPL
212 plume and the soil gas phase (McCarthy and Johnson, 1993). When the groundwater table level

213 decreases, the soil water enriched in dissolved LNAPL components is partially drained (Fig. 1ii). The
214 dissolved LNAPL constituents in pore water are progressively exposed to an air phase, favoring the
215 transfer of volatiles constituents to the vapor phase (McCarthy and Johnson, 1993; Qi et al., 2020). This
216 increases VOC emissions and vapor intrusion risks, especially for shallow aquifers (Illangasekare et al.,
217 2014; McCarthy and Johnson, 1993; Picone et al., 2012; Qi et al., 2020; Thomson et al., 1997; Werner
218 and Höhener, 2002). Additionally, groundwater fluctuations can promote the advective transport of soil
219 gases, accelerating the transport of the vapor phase through the USZ and their release into the
220 atmosphere (Qi et al., 2020; Soucy and Mumford, 2017). During the rise of the groundwater, the increase
221 in the soil water saturation reduces the soil gas/LNAPL interfacial area, reducing gas diffusivities and
222 volatilization. Hence, low VOC emissions are sometimes temporarily observed (Petri et al., 2015; Yoon
223 et al., 2002). However, while the drop in the water table level can create a “suction effect” limiting the
224 flow of the gas, the upward movement of groundwater creates a “piston effect”, pushing the soil gases
225 enriched in VOC towards the surface (Fig. 1iii, Boyle and Witherington, 2007). The air trapped at this
226 moment with LNAPL ganglia in the smear zone below the water table creates a three-phase
227 LNAPL/air/water system (Fig. 1iii, Lenhard et al., 1993; Fry et al., 1995; Van Geel and Sykes, 1997;
228 Williams and Oostrom, 2000; Charbeneau, 2007; Dobson et al., 2007), further promoting the transfer of
229 entrapped and dissolved LNAPL constituents toward the vapor phase in the early time after the upward
230 movement of groundwater (Fig. 1iii, Soucy and Mumford, 2017). Given these studies, an intensification
231 of the groundwater fluctuations will enhance volatilization. A global decrease in the average water table
232 level in response to climate change will increase the global thickness of the USZ, probably favoring the
233 exposure of the LNAPL constituents to volatilization processes and the enrichment of the soil gas in
234 VOC. This may also significantly increase the exposure of the residual LNAPL compounds to the
235 leaching/weathering process by infiltrated meteoric water. The modification of the dynamic moisture
236 conditions induced by the infiltration of meteoric water resulting from rainfalls or irrigation causes the
237 leaching/the desorption and the downward aqueous transport of LNAPL constituents (Lee et al., 2001;
238 Newell, 1995). The increase in this leaching process may affect the chemical and the physical properties
239 of the residual LNAPL in causing a faster depletion in the most soluble constituents. However, the
240 contribution of this process also closely depends on the intensity and frequency of precipitation events

241 and will thus probably suffer severe local and temporal modifications in response to the expected change
242 in precipitation patterns and heavy precipitation frequency (IPCC, 2014). Previous studies showed that
243 the mobile LNAPL phase can be more subject to adsorption into the smear zone as the water level
244 fluctuates, preventing the soluble contaminants to be washed away by groundwater level fluctuations
245 (Yadav and Hassanizadeh, 2011; Yang et al., 2017). However, the influence of groundwater level
246 fluctuations and temperature on sorption was too poorly documented to conclude.

247 **3.3. Dissolved LNAPL plume**

248 Higher temperatures increase the aqueous solubility of the LNAPL (Margesin and Schinner,
249 2001). However, the aqueous solubility of most LNAPL components evolves only slightly over the 10-
250 20°C temperature range, and in different ways (Tab. 1). The effect of temperature will thus probably
251 remain limited since the water solubility of LNAPL remains low between 0 and 20°C (Tab. 1). On the
252 contrary, the increase in Henry's law constant of the LNAPL compounds by up to 51% is expected in
253 this range of temperature (Tab. 1), which will probably greatly favor the volatilization of most of the
254 dissolved LNAPL constituents.

255 Under fluctuating water table conditions, spatial-temporal variations of the dissolved LNAPL
256 constituents concentrations and the plume thickness are generally observed as a function of the increase
257 and decrease in the groundwater level (Davis et al., 1999). Below the water table, the entrapped LNAPL
258 ganglia form a thin continuous film of molecular thickness at the interface between gas and water in
259 these three-phases systems (Fenwick and Blunt, 1998). These films exhibit higher LNAPL-water
260 interfacial areas more available for dissolution than in a classical LNAPL/water system (Bradford et al.,
261 1999; Shojib, 2015). This results in the faster dissolution of the entrapped LNAPL compounds under
262 fluctuating groundwater table conditions (Shojib, 2015). Moreover, the advection is the dominant
263 transport pathway for the dissolved LNAPL constituents under fluctuating groundwater conditions
264 (Gupta et al., 2019). This enhances the depletion of the LNAPL source zone with the preferential
265 dissolution of the most soluble compounds, leading to a more rapid decrease in the LNAPL source
266 zone's longevity (Dobson et al., 2007; Gupta et al., 2019). However, this leads also to faster transport
267 and spreading of the dissolved LNAPL constituents in groundwater along the vertical and the horizontal

268 direction (Davis et al., 1999; Gupta et al., 2019; Yadav and Hassanizadeh, 2011). The pollution thus
269 reaches a more distant location, creating a larger polluted plume (Gupta et al., 2019; Sarikurt et al., 2017;
270 Zhou et al., 2015).

271 Despite a probably limited effect of the higher temperatures on the contaminants' aqueous
272 solubilities, more intense groundwater level fluctuations will probably greatly increase the
273 water/air/LNAPL interfaces, favoring the spreading and the enrichment of the groundwater dissolved
274 plume in LNAPL constituents in the climate change context. The increased contribution of the leaching
275 of residual LNAPL droplets in the USZ, may also further contribute to the dissolved plume, especially
276 for recent or not yet stabilized LNAPL, still rich in soluble compounds. Nevertheless, the correlation
277 between the amplitude and the frequency of the water level variations and the enrichment of the
278 dissolved and gaseous phase in LNAPL compounds is not clear enough (Davis et al., 1999; Eichert et
279 al., 2017; McAlexander and Sihota, 2019). It remains, therefore, difficult to predict to which extent a
280 rise or a drop of the water level of a known amplitude can affect dissolution and volatilization processes.
281 Yet, understanding today the effect of the amplitude of these fluctuations (when they exist) on the
282 LNAPL plume behavior on different sites could, therefore, help us to better predict the effects of climate
283 change. The spatial variability between monitoring wells in the same site suggests that other effects may
284 be at work such as local variations in the hydrogeological properties of the soil (soil heterogeneities), or
285 in the height of water table variations. The low spatial and temporal resolution of field studies does not
286 allow the conclusions to be drawn.

287 **3.4. Natural source zone depletion**

288 It has been demonstrated that the rise of temperature favors the (bio)degradation of the organic
289 pollutants (Askarani, 2020; Dagois et al., 2016; Margesin and Schinner, 2001; McAlexander and Sihota,
290 2019; Yadav et al., 2012; Yadav and Hassanizadeh, 2011; Zeman et al., 2014). Askarani (2020)
291 demonstrated that monitoring subsurface temperature is a viable technique to resolve LNAPL
292 attenuation rates for LNAPLs since both factors are correlated. Toluene biodegradation rates have been
293 shown to double for every 10°C increase in temperature (Yadav et al., 2012). At higher temperatures,
294 the permeability of the microbial cell membrane of LNAPL-degrading microorganisms is greater,

295 favoring the uptake of nutrients and organic components (Corseuil and Weber, 1994; Zeman et al.,
296 2014). The toxicity of the contamination is also reduced for the microorganisms since the low molecular
297 weight compounds are more easily and quickly volatilized at higher temperatures (Davis, 1997).

298 Comparison between experiments under steady-state and fluctuating water levels showed that
299 successive rises and drops of the water level and the ensuing partitioning of LNAPL components
300 strongly modify the LNAPL biodegradation rates (Dobson et al., 2007; Gupta et al., 2019; Ismail et al.,
301 2020; Rainwater et al., 1993; Van De Ven et al., 2021). Experiments by Rainwater et al., (1993) revealed
302 that a column subjected to cyclic water table variations (15 cm of variations each 48 h) exhibit 15% less
303 residual fuel contamination after 9 weeks than a static water level column. The extent of the
304 anaerobic/anoxic zones depends on redox conditions and the availability of electron acceptors, which
305 suffer spatial and temporal variations as a function of the rises and drops of the groundwater level
306 (Rezanezhad et al., 2014; Sinke et al., 1998; Van De Ven et al., 2021). Variations of the water table level
307 also temporarily affect soil moisture, modifying the oxygen diffusion rates in the vadose zone, and thus
308 aerobic biodegradation processes. This affects the biodegradability of the organic pollutants and the
309 ensuing gaseous emissions (Davis et al., 2005; Dobson et al., 2007; Gupta et al., 2019; Van De Ven et
310 al., 2021; Zhou et al., 2015). More generally, successive groundwater level variations naturally enhance
311 (i) the diffusion of oxygen (Dobson et al., 2007; Gupta et al., 2019; Haberer et al., 2012; Lenhard et al.,
312 1993; Vorenhout et al., 2004), (ii) the renewal of micronutrients through the soil and the water column
313 by advective transport (Rezanezhad et al., 2014; Schimel et al., 2007), (iii) the evacuation of the reaction
314 by-products accumulated during biodegradation (Nyer, 2000), (iv) the functional diversity and
315 flexibility of microorganisms themselves (Zhou et al., 2015). This naturally enhances the biochemical
316 and microbial dynamics, leading to higher microbial degradation rates of the dissolved, entrapped, and
317 residual organic contaminants (Dobson et al., 2007; Fry et al., 1997; Rezanezhad et al., 2014; Suthersan
318 et al., 2015). This process is further accentuated by the important spreading of the mobile LNAPL and
319 dissolved LNAPL compounds across the soil and the water column, making the LNAPL compounds
320 more available to the microorganisms (Dobson et al., 2007; Gupta et al., 2019; Zhou et al., 2015). The
321 intensification of groundwater fluctuations in response to climate change may thus conduce to greater

322 availability of carbon and nutrients to soil microorganisms, sustaining biodegradation of the LNAPL.
323 The global decrease in the mean groundwater heads and the ensuing increase in the USZ thickness may
324 also favor the exposure of the residual LNAPL phase to the air, favoring aerobic LNAPL
325 (bio)degradation processes.

326 It seems, therefore, relatively clear that an increase in temperature by a few degrees and an
327 intensification of water table level fluctuations will be beneficial to the activity of the microorganisms
328 at most contaminated sites, favoring the natural attenuation of contaminations. While this may reduce
329 the risks associated with the residual and mobile LNAPL phase, this may, however, enhance surface
330 emissions (mainly CO₂ and CH₄) (Fig. 1ii, iii, Mayer, 2005; Amos and Mayer, 2006; Sihota et al., 2013).
331 Indeed, the important source of gas resulting from the biodegradation of the dissolved LNAPL
332 constituents in groundwater may also promote the ebullition of gas bubbles in the SZ (Amos and Mayer,
333 2006; Rezaeehad et al., 2014; Sihota et al., 2013). This generates important vertical gas bubble flow
334 from the groundwater at the origin of advection-dominated conditions in the USZ (Soucy and Mumford,
335 2017). However, this “bubble-facilitated VOC transport” may probably have a limited impact on VOC
336 emissions on the surface as many of these VOCs are likely to be degraded by the increased bacterial
337 activity. Nevertheless, this could contribute to an increase in CO₂ and CH₄ surface emissions. These
338 attenuation rates may, therefore, be faster in the coming decades at most of the contaminated sites.
339 Intense biodegradation of the dissolved LNAPL constituent also sustains high concentration gradients,
340 maintaining high dissolution processes over time (Davis et al., 1999). This may contribute to the faster
341 natural attenuation of the contamination but without lowering the concentration of the dissolved
342 compounds in the early years after the contamination (Dobson et al., 2007; Gupta et al., 2019).
343 Moreover, above certain concentrations that depend on the bacterial strains and organic species, LNAPL
344 components become toxic for the microorganisms, reducing the efficiency of biodegradation (Gupta et
345 al., 2019). In some areas where important concentrations of dissolved LNAPL components are released,
346 the biodegradation rates may thus remain limited. The biodegradability of certain LNAPL compounds
347 exhibits also spatial-temporal variations depending on the availability of more easily biodegradable
348 organic species and the accommodation time of the microbial community to the less biodegradable and

349 toxic compounds (Sinke et al., 1998). This incubation time varies greatly between LNAPL compounds
350 (Wiedemeier et al., 1995). The extent of the effect of climate change on biodegradation rates may thus
351 be very inconsistent across sites. Finally, the changes in the mass of the dissolved LNAPL constituents
352 and the availability of electron acceptors are decreasing with the increasing sorption phenomenon (up
353 to -30%) under a fluctuating water level. This may impact biodegradation rates (Prommer et al., 2002).
354 A better understanding of the effects of climate change on these sorption effects is therefore crucial.
355 However, this implies a better integration of the soil properties at sites including composition, sorption
356 capacity, and soil heterogeneities. This is all the more important since the presence of soil
357 heterogeneities (*i.e.* more or less compacted layers) influences not only sorption processes but also soil
358 moisture contents, and gas diffusivities (Davis et al., 2005). These expected effects of climate change
359 on LNAPL contaminated sites are summarized in Tab. 2.

360 **4. Cases of different climatic conditions and contaminated sites properties**

361 Global climate models often give inconsistent predictions for precipitation patterns and
362 groundwater recharge (Goderniaux et al., 2011; Meixner et al., 2016; Smerdon, 2017). Hence,
363 uncertainties remain related to the difficulty to predict the effect of climate change on groundwater
364 resources. There is a lack of knowledge about the future evolution of precipitations and extreme events'
365 frequency and intensity and their consequences on the hydrological cycle, the anthropic activity
366 (especially water consumption), and groundwater resources (Meixner et al., 2016; Smerdon, 2017).
367 Furthermore, the effect of climate change on LNAPL may vary locally as a function of specific sites
368 properties but also between arid, cold, or humid coastal environments, where different precipitation and
369 groundwater recharge patterns are expected in the coming decades (Christensen and Christensen, 2007;
370 IPCC, 2014; Meixner et al., 2016). This paragraph, therefore, proposes to discuss the possible effects of
371 climate change on LNAPL with different climatic conditions. These expected effects of climate change
372 on LNAPL contaminated sites under these particular climatic conditions are summarized in Tab. 3

373 **4.1 Cold regions**

374 In cold environments (such as boreal environments), the environmental factors consist in low
375 temperatures ($<8^{\circ}\text{C}$), low soil nutrient contents and availability, and excess water distribution (rainfalls
376 > 900 mm/year) which is often responsible for low soil oxygen diffusivities (Rayner et al., 2007). Hence,
377 natural volatilization, dissolution, and biodegradation of petroleum hydrocarbons are generally reduced
378 to nearly negligible rates (Boethling et al., 2009; Rayner et al., 2007). Hydrocarbon pollutants can,
379 therefore, remain for long periods and be more damaging to the environment (Boethling et al., 2009). In
380 the climate change context, these areas could experience greater global warming than the rest of the
381 world ($+5$ to $+9^{\circ}\text{C}$, IPCC, 2014). Moreover, the increase in winter precipitations ($+ 30$ - 50% , Christensen
382 and Christensen, 2007; IPCC, 2014) and the reduction of the snow cover and soil frost can be expected
383 to enhance the groundwater recharge, leading to a rise in groundwater levels in winter (Okkonen et al.,
384 2010). On the contrary, warmer temperatures will enhance evapotranspiration rates, leading to a
385 decrease in groundwater recharge and heads in summer (Okkonen et al., 2010). This may have several
386 consequences on LNAPL. The increased temperature and snowmelt and decreased frost may contribute
387 to oxygen-rich water inputs (Okkonen et al., 2010), enhancing the LNAPL-degrading microorganism's
388 activity and biodegradation rates. Increased spreading of LNAPL across the soil and groundwater can
389 be expected due to more intense water table fluctuations. The warmer temperatures will increase LNAPL
390 viscosity (except for older contaminations where all soluble and volatile compounds have already been
391 remobilized; in this case, the change will be minimal) and LNAPL compounds volatility and solubility
392 (to a less extent). This may enhance the transfer of LNAPL constituents to the dissolved and the gaseous
393 phase, decreasing the contamination lifetime. For example, the vapor pressure of benzene increases up
394 to 70% between 5°C and 15°C (Sanemasa et al., 1982). It is also conceivable that more frequent flooding
395 events and surface-water intrusion occur from wetlands, increasing the risk of groundwater exposure to
396 new contaminations.

397 **4.2. Arid and semi-arid zones**

398 Arid and semi-arid areas are characterized by specific extremes environmental conditions,
399 including highly variable temperatures and important water table level and soil moisture content
400 dynamics. These conditions are generally favorable to the mobilization and the biodegradation of the

401 LNAPL (McAlexander and Sihota, 2019; Yadav and Hassanizadeh, 2011). In the context of climate
402 change, these arid regions are expected to become drier and warmer (IPCC, 2014). The expected
403 increase in temperature (+4 to +7°C, IPCC, 2014) may lead to a net rise in the evapotranspiration rate,
404 a strong decrease in soil moisture content, and a significant increase in the pressure on the groundwater
405 resources for drinking water, agricultural or industrial activities (Meixner et al., 2016; Taylor et al.,
406 2013). At the same time, the drop in precipitation in spring and summer and the declining snowpack
407 (the major part of the water table recharge in mountainous areas) may drastically reduce the groundwater
408 recharge (Meixner et al., 2016). Hence, a decrease in groundwater recharge up to -30% is expected in
409 some arid lands by 2100 (e.g. San Pedro Basin AZ, Sonora Mexico, Meixner et al., 2016). Several
410 consequences may, therefore, be expected for existing LNAPL contaminated sites: (i) greater spreading
411 of LNAPL across both the USZ and the SZ due to global falling water levels and greater level variations
412 tied with the encroachment catchment areas of pumping wells; (ii) greater volatility of LNAPL
413 compounds and an increase in VOC emissions in response to higher temperatures and LNAPL/air
414 surface areas in the SZ. The extremely hot temperatures in summer may also decrease nucleic acids,
415 proteins, and the enzyme activity of soil microorganisms (Corseuil and Weber, 1994). The increase of
416 droughts may dry the soil out, preventing the development of LNAPL-degrading microorganisms
417 (Dagois et al., 2016). More intense drought events and heatwaves may thus take over the microbial
418 population from the soil in these areas, decreasing significantly the LNAPL natural attenuation rates.
419 The expected increase in extreme precipitation events' frequency and intensity may also lead to an
420 increasing number of floods (IPCC, 2014). These events may accelerate riverbank erosion and damage
421 LNAPL transport infrastructures, and storage tanks, causing important new LNAPL spills. For example,
422 Colorado has more than 5,900 oil and gas wells within 500 feet of the state's rivers and streams. In 2013,
423 severe flooding occurred, damaging more than 2,650 oil and gas facilities (wells and storage tanks),
424 resulting in the spill of approximately 48,250 gallons of oil and condensate in the environment.

425 **4.3. Humid coastal areas**

426 Many LNAPL spills occurred in coastal environments (Gupta et al., 2019, 2018; Rice et al.,
427 1995). In coastal regions, groundwater tables often suffer highly dynamic conditions due to tidal effects.

428 These environments are particularly vulnerable to climate change. In the climate change context, the sea
429 level is expected to rise (1,7 mm/year) from 0.43 to 0.84 m by 2100 due to thermal expansion, melting
430 ice sheets and glaciers, and land water storage changes (IPCC, 2014). Most coastal areas -are supposed
431 to become wetter due to the increase in precipitations by the end of the century (Christensen and
432 Christensen, 2007; IPCC, 2014). These phenomena are already at work. Between 1991 and 2012, coastal
433 regions of the USA recorded an increase in precipitation and extreme precipitation events of 5-15% and
434 5-71% respectively (USGCRP, 2014). The sea levels have risen by approximately 15 cm since 1960 in
435 the western USA, and are now rising about 3,3 cm per decade (USGCRP, 2014). The increasing sea
436 level and the more frequent extreme precipitation and storm frequency and intensity are expected to
437 cause more frequent floods, which may greatly contribute to coastal erosion (IPCC, 2014). These
438 phenomena may have important consequences on LNAPL contaminations. First, the recharge of
439 adjacent coastal aquifer systems and average groundwater heads are expected to increase in coastal
440 humid environments (IPCC, 2014). This may significantly reduce the vadose assimilation space, or even
441 totally submerge residual LNAPL contaminants by groundwater flooding. This may limit VOC
442 emissions but favor the dissolution and the dilution of LNAPL compounds in groundwater. It may also
443 promote the spreading and the transfer of the dissolved contaminants and the mobile LNAPL to the sea
444 or connected rivers. This may, however, decrease soil gas diffusivities. The rise of the sea level can also
445 increase salt-water intrusion into groundwater (IPCC, 2014), impacting the microorganisms' activity and
446 the biodegradation rates of LNAPL components (Rezanezhad et al., 2019). Moreover, most of the
447 petroleum refineries and industries are located in coastal regions across the world (e.g of the California
448 coast, USA Rice et al., 1995). Therefore, the floods caused by the rising sea level, heavy precipitations,
449 and storms are expected to significantly damage infrastructures (Rahimi et al., 2020) such as petroleum
450 industries' storage or transportation facilities. Thus, despite the precautions taken to better manage the
451 risk of possible new spills or to stabilize existing contaminations in the last decades, new soil and
452 groundwater contamination may occur.

453 **5. Conclusions and perspectives**

454 Predicting the effect of climate change on groundwater is complex and often limited to very
455 local scales and particular climatic conditions. Climate change predictions on LNAPL sites are thus
456 uncertain and depend on these inconsistent various numerical models. However, according to current
457 global predictions, the higher amplitude of groundwater table variations and higher temperatures will
458 probably increase biodegradation processes, the LNAPL mobility, and spreading across the smear zone,
459 favoring the release of LNAPL compounds to the atmosphere and groundwater but decreasing the
460 LNAPL mass and its longevity. Outcomes will, nevertheless, vary greatly across arid, cold, or humid
461 coastal environments, where different effects of climate change are expected. For example, the expected
462 drop of the water table levels and soil moisture contents may decrease biodegradation rates in arid lands,
463 where extreme temperatures and droughts events are expected. In coastal areas, higher precipitations
464 and groundwater levels may lead to the submersion and the dilution of the LNAPL compounds in
465 groundwater and connected rivers. In colds areas, warmer temperatures may significantly increase the
466 mobility of LNAPL, dissolution, and volatilization processes. The particularities of each site, need,
467 therefore, to be considered.

468 Another difficulty comes from the differences between experimental, numerical, and field
469 studies carried out on LNAPL, where the time scale, the amplitude of groundwater level variations, the
470 porous medium type vary greatly between studies (Tab. 4, 5, Garg et al., 2017; Lari et al., 2016; Sookhak
471 Lari et al., 2019). There are relatively few field studies (28%) compared to laboratory experiments and
472 numerical modeling (Tab. 4). However, laboratory experiments and numerical works are simplified
473 models that neglected the soil composition and heterogeneities, the LNAPL chemical complexity (Tab.
474 5), or the amplitude of water table fluctuations. Although these properties are specific to each site, they
475 can generate discrepancies between field observations and the results of numerical models or laboratory
476 experiments. The amplitude of water table fluctuations may control the evolution of dissolved LNAPL
477 constituents' concentration (Teramoto and Chang, 2017), soil moisture content, gas diffusivity, and thus,
478 VOC fluxes (Qi et al., 2020). Variations in soil grain sizes, composition, or compaction determine the
479 permeability which is one of the main parameters affecting rainfall infiltration, thermal-physical
480 effective parameters, the migration path, the plume velocity, the entrapment, LNAPL saturation

481 distribution in the soil, gas soil moisture content, gaseous phase pathways, and gas diffusivities (Davis
482 et al., 2005; Huntley and Beckett, 2002; Illangasekare et al., 1995b; Lehmann et al., 2012; Powers et al.,
483 1998; Qi et al., 2020; Sarikurt et al., 2017; Sun, 2016). The behavior of an organic component in the
484 single-component conditions of laboratory experiments and numerical models is not always
485 representative of the behavior of the complex LNAPL mixtures present at most contaminated sites due
486 to the interactions existing between different organic species that may affect the solubility of each
487 compound (Lekmine et al., 2014; Vasudevan et al., 2016). This highlights the necessity of replacing the
488 current compartmentalized vision of these three-phase systems with more dynamic/real-time monitoring
489 of LNAPL integrated approaches that consider the full complexity of these contaminated sites.

490 Finally, the evolution of environmental standards and regulations over the last decades has led
491 to a dramatic reduction in LNAPLs releases (ITRC, 2018b, 2009). Remediation efforts and precautions
492 taken on industrial sites have stabilized and/or reduced the evolution and mobilization of the LNAPL
493 compounds (Askarani and Sale, 2020). Many of these LNAPL sites will be only slightly affected by a
494 slight increase in surface and groundwater temperature or higher water level variations. On the other
495 hand, for coastal or riverside sites, the increased risk of flooding associated with rising sea levels and
496 the frequency and intensity of extreme events could compromise these efforts and lead to the formation
497 of new sources of contamination. A better understanding of these risks may help to prevent and mitigate
498 their impacts. Understanding the effects of climate on current and future contaminated sites could
499 therefore have great environmental and economic benefits.

500 **Declaration of Competing Interest**

501 The authors declare that they have no known competing financial interests or personal relationships that
502 could have appeared to influence the work reported in this paper.

503 **Acknowledgments**

504 This work was supported by the French PIA project “Lorraine Université d’Excellence”, reference
505 ANR-15-IDEX-04-LUE, and the BRGM (the French Geological Survey). The authors would like to
506 thank Lorraine University and the BRGM. This work is included in the scientific program of the GISFI

507 research consortium dedicated to the knowledge and the development of remediation technologies for
508 degraded and polluted lands (Groupement d'Intérêt Scientifique sur les Friches Industrielles -
509 <http://www.gisfi.univ-lorraine.fr>).

510 **References**

- 511 Abraham, M.H., Matteoli, E., 1988. The temperature variation of the hydrophobic effect. *Journal of the*
512 *Chemical Society, Faraday Transactions 1: Physical Chemistry in Condensed Phases* 84, 1985–
513 2000.
- 514 Alazaiza, M.Y.D., Ramli, M.H., Coptly, N.K., Sheng, T.J., Aburas, M.M., 2020. LNAPL saturation
515 distribution under the influence of water table fluctuations using simplified image analysis
516 method. *Bull Eng Geol Environ* 79, 1543–1554. <https://doi.org/10.1007/s10064-019-01655-3>
- 517 Amos, R.T., Mayer, K.U., 2006. Investigating the role of gas bubble formation and entrapment in
518 contaminated aquifers: Reactive transport modelling. *Journal of contaminant hydrology* 87,
519 123–154.
- 520 Ashworth, R.A., Howe, G.B., Mullins, M.E., Rogers, T.N., 1988. Air-water partitioning coefficients of
521 organics in dilute aqueous solutions. *Journal of Hazardous Materials* 18, 25–36.
- 522 Askarani, K.K., 2020. DISSERTATION THERMAL MONITORING OF NATURAL SOURCE ZONE
523 DEPLETION. <https://doi.org/10.13140/RG.2.2.29924.53129>
- 524 Askarani, K.K., Sale, T.C., 2020. Thermal estimation of natural source zone depletion rates without
525 background correction. *Water Research* 169, 115245.
526 <https://doi.org/10.1016/j.watres.2019.115245>
- 527 Baedecker, M.J., Eganhouse, R.P., Bekins, B.A., Delin, G.N., 2011. Loss of volatile hydrocarbons from
528 an LNAPL oil source. *Journal of Contaminant Hydrology* 126, 140–152.
529 <https://doi.org/10.1016/j.jconhyd.2011.06.006>
- 530 Ballesterio, T.P., Fiedler, F.R., Kinner, N.E., 1994. An investigation of the relationship between actual
531 and apparent gasoline thickness in a uniform sand aquifer. *Groundwater* 32, 708–718.
- 532 Benioug, M., Golfier, F., Fischer, P., Oltean, C., Buès, M.A., Yang, X., 2019. Interaction between
533 biofilm growth and NAPL remediation: A pore-scale study. *Advances in water resources* 125,
534 82–97.
- 535 Boethling, R., Fenner, K., Howard, P., Klečka, G., Madsen, T., Snape, J.R., Whelan, M.J., 2009.
536 Environmental persistence of organic pollutants: guidance for development and review of POP
537 risk profiles. *Integrated Environmental Assessment and Management: An International Journal*
538 5, 539–556.
- 539 Boyle, R., Witherington, P., 2007. Guidance on evaluation of development proposals on sites where
540 methane and carbon dioxide are present. *NHBC and RSK Guidance on methane and carbon*
541 *dioxide* 4, 1–87.
- 542 Bradford, S.A., Vendlinski, R.A., Abriola, L.M., 1999. The entrapment and long-term dissolution of
543 tetrachloroethylene in fractional wettability porous media. *Water Resources Research* 35, 2955–
544 2964.
- 545 Bruckberger, M.C., Gleeson, D.B., Bastow, T.P., Morgan, M.J., Walsh, T., Rayner, J.L., Davis, G.B.,
546 Puzon, G.J., 2021. Unravelling Microbial Communities Associated with Different Light Non-
547 Aqueous Phase Liquid Types Undergoing Natural Source Zone Depletion Processes at a Legacy
548 Petroleum Site. *Water* 13, 898.
- 549 Budantseva, L.S., Lesteva, T.M., Nemstov, M.S., 1976. Deposited Doc. *Zhurnal Fizicheskoi Khimii*,
550 *VINITI* 50, 437–476.
- 551 Carruth, G.F., Kobayashi, R., 1973. Vapor pressure of normal paraffins ethane through n-decane from
552 their triple points to about 10 mm mercury. *Journal of Chemical and Engineering Data* 18, 115–
553 126.
- 554 Charbeneau, R., 2007. LNAPL Distribution and Recovery Model. *Distribution and Recovery of*
555 *Petroleum Hydrocarbon Liquids in Porous Media. Vol. 1. API Publication* 4760.

- 556 Chen, W., Tong, L., Zheng, X., Li, M., 2010. Influencing Factors of BTEX Volatilization, in: 2010 4th
557 International Conference on Bioinformatics and Biomedical Engineering. Presented at the 2010
558 4th International Conference on Bioinformatics and Biomedical Engineering (ICBBE), IEEE,
559 Chengdu, China, pp. 1–5. <https://doi.org/10.1109/ICBBE.2010.5516007>
- 560 Chompusri, S., Rivett, M.O., Mackay, R., 2002. LNAPL redistribution on a fluctuating water table:
561 column experiments. IAHS PUBLICATION 225–234.
- 562 Christensen, J.H., Christensen, O.B., 2007. A summary of the PRUDENCE model projections of
563 changes in European climate by the end of this century. *Climatic Change* 81, 7–30.
564 <https://doi.org/10.1007/s10584-006-9210-7>
- 565 Clough, S.R., 2014. Decane, in: *Encyclopedia of Toxicology (Third Edition)*. Academic Press, pp.
566 1144–1146.
- 567 Coates, M., Connell, D.W., Barron, D.M., 1985. Aqueous solubility and octan-1-ol-water partition
568 coefficients of aliphatic hydrocarbons. *Environmental science & technology* 19, 628–632.
- 569 Colombano, S., Davarzani, H., van Hullebusch, E.D., Ignatiadis, I., Huguenot, H., Zornig, C., Guyonnet,
570 D., 2020. In Situ Thermal Treatments and Enhancements: Theory and Case Study, in: van
571 Hullebusch, E.D., Huguenot, D., Pechaud, Y., Simonnot, M.-O., Colombano, S. (Eds.),
572 *Environmental Soil Remediation and Rehabilitation*. Springer International Publishing, Cham,
573 pp. 149–209. https://doi.org/10.1007/978-3-030-40348-5_3
- 574 Corseuil, H.X., Weber, W.J., 1994. Potential biomass limitations on rates of degradation of
575 monoaromatic hydrocarbons by indigenous microbes in subsurface soils. *Water Research* 28,
576 1415–1423.
- 577 Dagois, R., Schwartz, C., Coussy, S., Lorgeoux, C., Ouvrard, S., Faure, P., 2016. Climatic influence on
578 mobility of organic pollutants in Technosols from contrasted industrial activities. *Journal of*
579 *soils and sediments* 16, 1306–1315.
- 580 Dams, J., Salvadore, E., Van Daele, T., Ntegeka, V., Willems, P., Batelaan, O., 2012. Spatio-temporal
581 impact of climate change on the groundwater system. *Hydrology and Earth System Sciences*
582 16, 1517–1531.
- 583 David, V., Moldoveanu, S.C., 2019. Variation with temperature of octanol/water partition coefficient
584 for the homologous series from benzene to propylbenzene. *Separation Science Plus* 2, 457–464.
- 585 Davis, E.L., 1997. How heat can enhance in-situ soil and aquifer remediation: important chemical
586 properties and guidance on choosing the appropriate technique. U.S. EPA Issue paper 540/S–
587 97/502.
- 588 Davis, E.L., 1994. Effect of temperature and pore size on the hydraulic properties and flow of a
589 hydrocarbon oil in the subsurface. *Journal of Contaminant Hydrology* 16, 55–86.
- 590 Davis, G.B., Barber, C., Power, T.R., Thierrin, J., Patterson, B.M., Rayner, J.L., Wu, Q., 1999. The
591 variability and intrinsic remediation of a BTEX plume in anaerobic sulphate-rich groundwater.
592 *Journal of Contaminant Hydrology* 36, 265–290. [https://doi.org/10.1016/S0169-](https://doi.org/10.1016/S0169-7722(98)00148-X)
593 [7722\(98\)00148-X](https://doi.org/10.1016/S0169-7722(98)00148-X)
- 594 Davis, G.B., Johnston, C.D., Thierrin, J., Power, T.R., Patterson, B.M., 1993. Characterizing the
595 distribution of dissolved and residual NAPL petroleum hydrocarbons in unconfined aquifers to
596 effect remediation. *AGSO Journal of Geology and Geophysics* 14, 89–94.
- 597 Davis, G.B., Rayner, J.L., Trefry, M.G., Fisher, S.J., Patterson, B.M., 2005. Measurement and Modeling
598 of Temporal Variations in Hydrocarbon Vapor Behavior in a Layered Soil Profile. *Vadose Zone*
599 *Journal* 4, 225–239. <https://doi.org/10.2136/vzj2004.0029>
- 600 Dobson, R., Schroth, M.H., Zeyer, J., 2007. Effect of water-table fluctuation on dissolution and
601 biodegradation of a multi-component, light nonaqueous-phase liquid. *Journal of Contaminant*
602 *Hydrology* 94, 235–248. <https://doi.org/10.1016/j.jconhyd.2007.07.007>
- 603 Eichert, J., McAlexander, B., Lyverse, M., Michalski, P., Sihota, N., 2017. Spatial and temporal
604 variation in natural source zone depletion rates at a former oil refinery. *Vadose Zone Journal*
605 16, 1–16.
- 606 Fenwick, D.H., Blunt, M.J., 1998. Three-dimensional modeling of three phase imbibition and drainage.
607 *Advances in water resources* 21, 121–143.
- 608 Fry, N.K., Fredrickson, J.K., Fishbain, S., Wagner, M., Stahl, D.A., 1997. Population structure of
609 microbial communities associated with two deep, anaerobic, alkaline aquifers. *Applied and*

- 610 environmental microbiology 63, 1498–1504. <https://doi.org/10.1128/AEM.63.4.1498->
611 1504.1997
- 612 Fry, V.A., Istok, J.D., Semprini, L., O'Reilly, K.T., Buscheck, T.E., 1995. Retardation of dissolved
613 oxygen due to a trapped gas phase in porous media. *Ground water* 33, 391–399.
- 614 Gaito, S., Maki, M., Peters, C., 2012. LNAPL remediation technology bench-scale testing report.
615 (Technical report No. B0064410), Revitalizing Auto Communities Environmental Response
616 Trust (RACER). ARCADIS G&M of Michigan, LLC, Brighton, MI.
- 617 Garg, S., Newell, C.J., Kulkarni, P.R., King, D.C., Adamson, D.T., Renno, M.I., Sale, T., 2017.
618 Overview of Natural Source Zone Depletion: Processes, Controlling Factors, and Composition
619 Change. *Groundwater Monitoring & Remediation* 37, 62–81.
620 <https://doi.org/10.1111/gwmr.12219>
- 621 Gatsios, E., García-Rincón, J., Rayner, J.L., McLaughlan, R.G., Davis, G.B., 2018. LNAPL
622 transmissivity as a remediation metric in complex sites under water table fluctuations. *Journal*
623 *of Environmental Management* 215, 40–48. <https://doi.org/10.1016/j.jenvman.2018.03.026>
- 624 Goderniaux, P., Brouyère, S., Blenkinsop, S., Burton, A., Fowler, H.J., Orban, P., Dassargues, A., 2011.
625 Modeling climate change impacts on groundwater resources using transient stochastic climatic
626 scenarios. *Water Resources Research* 47. <https://doi.org/10.1029/2010WR010082>
- 627 Goderniaux, P., Brouyère, S., Fowler, H.J., Blenkinsop, S., Therrien, R., Orban, P., Dassargues, A.,
628 2009. Large scale surface–subsurface hydrological model to assess climate change impacts on
629 groundwater reserves. *Journal of Hydrology* 373, 122–138.
630 <https://doi.org/10.1016/j.jhydrol.2009.04.017>
- 631 Green, T.R., Taniguchi, M., Kooi, H., Gurdak, J.J., Allen, D.M., Hiscock, K.M., Treidel, H., Aureli, A.,
632 2011. Beneath the surface of global change: Impacts of climate change on groundwater. *Journal*
633 *of Hydrology* 405, 532–560.
- 634 Güler, C., 2019. Organic (Hydrocarbon) Contamination: Nonaqueous Phase Liquids, in: *GIS and*
635 *Geostatistical Techniques for Groundwater Science*. Elsevier, pp. 251–268.
636 <https://doi.org/10.1016/B978-0-12-815413-7.00018-3>
- 637 Guo, Y., 2015. Vapor intrusion at a site with an alternative pathway and a fluctuating groundwater table.
638 Arizona State University.
- 639 Guo, Y., Holton, C., Luo, H., Dahlen, P., Johnson, P.C., 2019. Influence of Fluctuating Groundwater
640 Table on Volatile Organic Chemical Emission Flux at a Dissolved Chlorinated-Solvent Plume
641 Site. *Groundwater Monitoring & Remediation* 39, 43–52.
- 642 Gupta, G.P.K., Yadav, B., Yadav, B.K., 2019. Assessment of LNAPL in Subsurface under Fluctuating
643 Groundwater Table Using 2D Sand Tank Experiments. *Journal of Environmental Engineering*
644 145, 04019048. [https://doi.org/10.1061/\(ASCE\)EE.1943-7870.0001560](https://doi.org/10.1061/(ASCE)EE.1943-7870.0001560)
- 645 Gupta, P.K., Ranjan, S., Kumar, D., 2018. Groundwater pollution by emerging industrial pollutants and
646 its remediation techniques. Chapter 2. Recent advances in environmental management, CRC
647 Press Taylor & Francis Group 1.
- 648 Gupta, P.K., Yadav, B.K., 2020. Three-dimensional laboratory experiments on fate and transport of
649 LNAPL under varying groundwater flow conditions. *Journal of Environmental Engineering*
650 146, 04020010.
- 651 Haberer, C.M., Rolle, M., Cirpka, O.A., Grathwohl, P., 2012. Oxygen transfer in a fluctuating capillary
652 fringe. *Vadose Zone Journal* 11, vzj2011.0056.
- 653 Hansch, C., Leo, A., Hoekman, D., 1985. Exploring QSAR hydro-phobic, electronic, and steric
654 constants., American Chemical Society. ed. Washington, DC.
- 655 Hansen, K.C., Zhou, Z., Yaws, C.L., Aminabhavi, T.M., 1993. Determination of Henry's law constants
656 of organics in dilute aqueous solutions. *Journal of Chemical and Engineering Data* 38, 546–550.
- 657 Huntley, D., Beckett, G.D., 2002. Persistence of LNAPL sources: relationship between risk reduction
658 and LNAPL recovery. *Journal of Contaminant Hydrology* 59, 3–26.
659 [https://doi.org/10.1016/S0169-7722\(02\)00073-6](https://doi.org/10.1016/S0169-7722(02)00073-6)
- 660 Illangasekare, T.H., Armbruster, E.J., Yates, D.N., 1995a. Non-Aqueous-Phase Fluids in Heterogeneous
661 Aquifers—Experimental Study. *Journal of Environmental Engineering* 121, 571–579.
662 [https://doi.org/10.1061/\(ASCE\)0733-9372\(1995\)121:8\(571\)](https://doi.org/10.1061/(ASCE)0733-9372(1995)121:8(571))
- 663 Illangasekare, T.H., Petri, B., Fucik, R., Sauck, C., Shannon, L., Sakaki, T., Smits, K., Cihan, A., Christ,
664 J., Schulte, P., 2014. Vapor intrusion from entrapped NAPL sources and groundwater plumes:

- 665 Process understanding and improved modeling tools for pathway assessment (Final report No.
666 SERDP Project ER-1687). COLORADO SCHOOL OF MINES GOLDEN.
- 667 Illangasekare, T.H., Ramsey, J.L., Jensen, K.H., Butts, M.B., 1995b. Experimental study of movement
668 and distribution of dense organic contaminants in heterogeneous aquifers. *Journal of*
669 *Contaminant Hydrology* 20, 1–25. [https://doi.org/10.1016/0169-7722\(95\)00045-W](https://doi.org/10.1016/0169-7722(95)00045-W)
- 670 Illangasekare, T.H., Smits, K.M., Fučík, R., Davarzani, H., 2015. From Pore to the Field: Upscaling
671 Challenges and Opportunities in Hydrogeological and Land–Atmospheric Systems, in: *Pore*
672 *Scale Phenomena: Frontiers in Energy and Environment*. World Scientific, pp. 163–202.
- 673 Imhoff, P.T., Frizzell, A., Miller, C.T., 1997. Evaluation of thermal effects on the dissolution of a
674 nonaqueous phase liquid in porous media. *Environmental science & technology* 31, 1615–1622.
- 675 IPCC, 2018. *Global Warming of 1.5°C*. IPCC.
- 676 IPCC, 2014. *IPCC fifth assessment synthesis report-climate change 2014 synthesis report*.
677 *Intergovernmental Panel on Climate Change: Geneva, Switzerland*.
- 678 Irianni-Renno, M., Akhbari, D., Olson, M.R., Byrne, A.P., Lefèvre, E., Zimbron, J., Lyverse, M., Sale,
679 T.C., De Long, S.K., 2016. Comparison of bacterial and archaeal communities in depth-resolved
680 zones in an LNAPL body. *Appl Microbiol Biotechnol* 100, 3347–3360.
681 <https://doi.org/10.1007/s00253-015-7106-z>
- 682 Ismail, R., Shafieyoun, S., Al-Raoush, R.I., 2020. Influence of Water Table Fluctuation on Natural
683 Source Zone Depletion in Hydrocarbon Contaminated Subsurface Environments, in:
684 *Proceedings of the International Conference on Civil Infrastructure and Construction (CIC*
685 *2020)*. Presented at the The International Conference on Civil Infrastructure and Construction,
686 Qatar University Press, pp. 654–658. <https://doi.org/10.29117/cic.2020.0084>
- 687 ITRC, 2018a. *LNAPL site management: LCSM evolution, decision process, and remedial technologies*.
688 *LNAPL-3. Interstate Technology & Regulatory Council., Washington, DC*.
- 689 ITRC, 2018b. *LNAPL site management: LCSM evolution, decision process, and remedial technologies*.
690 *LNAPL-3. Interstate Technology & Regulatory Council., Washington, DC*.
- 691 ITRC, 2009. *Evaluating LNAPL remedial technologies for achieving project goals*. Interstate
692 *Technology and Regulatory, Washington, DC*.
- 693 Jarsjö, J., Andersson-Sköld, Y., Fröberg, M., Pietroni, J., Borgström, R., Löf, Å., Kleja, D.B., 2020.
694 Projecting impacts of climate change on metal mobilization at contaminated sites: Controls by
695 the groundwater level. *Science of The Total Environment* 712, 135560.
696 <https://doi.org/10.1016/j.scitotenv.2019.135560>
- 697 Jeong, J., Charbeneau, R.J., 2014. An analytical model for predicting LNAPL distribution and recovery
698 from multi-layered soils. *Journal of Contaminant Hydrology* 156, 52–61.
699 <https://doi.org/10.1016/j.jconhyd.2013.09.008>
- 700 Kechavarzi, C., Soga, K., Illangasekare, T.H., 2005. Two-dimensional laboratory simulation of LNAPL
701 infiltration and redistribution in the vadose zone. *Journal of Contaminant Hydrology* 76, 211–
702 233. <https://doi.org/10.1016/j.jconhyd.2004.09.001>
- 703 Kembrowski, M.W., Chiang, C.Y., 1990. Hydrocarbon Thickness Fluctuations in Monitoring Wells.
704 *Groundwater* 28, 244–252. <https://doi.org/10.1111/j.1745-6584.1990.tb02252.x>
- 705 Knauss, K.G., Dibley, M.J., Leif, R.N., Mew, D.A., Aines, R.D., 2000. The aqueous solubility of
706 trichloroethene (TCE) and tetrachloroethene (PCE) as a function of temperature. *Applied*
707 *Geochemistry* 15, 501–512.
- 708 Lari, S.K., Davis, G.B., Johnston, C.D., 2016. Incorporating hysteresis in a multi-phase multi-
709 component NAPL modelling framework; a multi-component LNAPL gasoline example.
710 *Advances in Water Resources* 96, 190–201. <https://doi.org/10.1016/j.advwatres.2016.07.012>
- 711 Lee, C.-H., Lee, J.-Y., Cheon, J.-Y., Lee, K.-K., 2001. Attenuation of petroleum hydrocarbons in smear
712 zones: A case study. *Journal of Environmental Engineering* 127, 639–647.
- 713 Lee, J.-Y., Cheon, J.-Y., Lee, K.-K., Lee, S.-Y., Lee, M.-H., 2001. Factors affecting the distribution of
714 hydrocarbon contaminants and hydrogeochemical parameters in a shallow sand aquifer. *Journal*
715 *of contaminant Hydrology* 50, 139–158.
- 716 Lee, K.Y., Chrysikopoulos, C.V., 1998. NAPL pool dissolution in stratified and anisotropic porous
717 formations. *Journal of Environmental Engineering* 124, 851–862.

- 718 Legout, C., Molenat, J., Hamon, Y., 2009. Experimental and Modeling Investigation of Unsaturated
719 Solute Transport with Water-Table Fluctuation. *Vadose Zone Journal* 8, 21–31.
720 <https://doi.org/10.2136/vzj2007.0182>
- 721 Lehmann, P., Neuweiler, I., Vanderborght, J., Vogel, H.-J., 2012. Dynamics of Fluid Interfaces and
722 Flow and Transport across Material Interfaces in Porous Media—Modeling and Observations.
723 *Vadose Zone Journal* 11, vzj2012.0105.
- 724 Lekmine, G., Bastow, T.P., Johnston, C.D., Davis, G.B., 2014. Dissolution of multi-component LNAPL
725 gasolines: The effects of weathering and composition. *Journal of Contaminant Hydrology* 160,
726 1–11. <https://doi.org/10.1016/j.jconhyd.2014.02.003>
- 727 Lenhard, R.J., Johnson, T.G., Parker, J.C., 1993. Experimental observations of nonaqueous-phase liquid
728 subsurface movement. *Journal of Contaminant Hydrology* 12, 79–101.
729 [https://doi.org/10.1016/0169-7722\(93\)90016-L](https://doi.org/10.1016/0169-7722(93)90016-L)
- 730 Lenhard, R.J., Oostrom, M., Dane, J.H., 2004. A constitutive model for air–NAPL–water flow in the
731 vadose zone accounting for immobile, non-occluded (residual) NAPL in strongly water-wet
732 porous media. *Journal of Contaminant Hydrology* 71, 261–282.
733 <https://doi.org/10.1016/j.jconhyd.2003.10.014>
- 734 Lenhard, R.J., Parker, J.C., 1990. Estimation of free hydrocarbon volume from fluid levels in monitoring
735 wells. *Groundwater* 28, 57–67.
- 736 Lenhard, R.J., Rayner, J.L., Davis, G.B., 2017. A practical tool for estimating subsurface LNAPL
737 distributions and transmissivity using current and historical fluid levels in groundwater wells:
738 Effects of entrapped and residual LNAPL. *Journal of Contaminant Hydrology* 205, 1–11.
739 <https://doi.org/10.1016/j.jconhyd.2017.06.002>
- 740 Lenhard, R.J., Rayner, J.L., García-Rincón, J., 2019. Testing an analytical model for predicting
741 subsurface LNAPL distributions from current and historic fluid levels in Monitoring Wells: A
742 preliminary test considering hysteresis. *Water* 11, 2404.
- 743 Lenhard, R.J., Sookhak Lari, K., Rayner, J.L., Davis, G.B., 2018. Evaluating an analytical model to
744 predict subsurface LNAPL distributions and transmissivity from current and historic fluid levels
745 in groundwater wells: comparing results to numerical simulations. *Groundwater Monitoring &
746 Remediation* 38, 75–84.
- 747 Li, I.P., Lu, B.C., Chen, E.C., 1973. Vapor-Liquid equilibriums of binary systems containing n-hexane,
748 cyclohexane, and benzene at low temperatures. *Journal of Chemical and Engineering Data* 18,
749 305–309.
- 750 Margesin, R., Schinner, F., 2001. Biodegradation and bioremediation of hydrocarbons in extreme
751 environments. *Applied microbiology and biotechnology* 56, 650–663.
- 752 Mayer, A.S., 2005. *Soil and Groundwater Contamination: Nonaqueous Phase Liquids*. American
753 Geophysical Union.
- 754 McAlexander, B., Sihota, N., 2019. Influence of Ambient Temperature, Precipitation, and Groundwater
755 Level on Natural Source Zone Depletion Rates at a Large Semiarid LNAPL Site. *Groundwater
756 Monitoring & Remediation* 39, 54–65. <https://doi.org/10.1111/gwmr.12309>
- 757 McCarthy, K.A., Johnson, R.L., 1993. Transport of volatile organic compounds across the capillary
758 fringe. *Water Resources Research* 29, 1675–1683.
- 759 Meixner, T., Manning, A.H., Stonestrom, D.A., Allen, D.M., Ajami, H., Blasch, K.W., Brookfield, A.E.,
760 Castro, C.L., Clark, J.F., Gochis, D.J., Flint, A.L., Neff, K.L., Niraula, R., Rodell, M., Scanlon,
761 B.R., Singha, K., Walvoord, M.A., 2016. Implications of projected climate change for
762 groundwater recharge in the western United States. *Journal of Hydrology* 534, 124–138.
763 <https://doi.org/10.1016/j.jhydrol.2015.12.027>
- 764 Menberg, K., Blum, P., Kurylyk, B.L., Bayer, P., 2014. Observed groundwater temperature response to
765 recent climate change. *Hydrology and Earth System Sciences* 18, 4453–4466.
766 <https://doi:10.5194/hess-18-4453-2014>
- 767 Miller, M.M., Wasik, S.P., Huang, G.L., Shiu, W.Y., Mackay, D., 1985. Relationships between octanol-
768 water partition coefficient and aqueous solubility. *Environmental science & technology* 19,
769 522–529.
- 770 Mobile, M.A., Widdowson, M.A., Gallagher, D.L., 2012. Multicomponent NAPL Source Dissolution:
771 Evaluation of Mass-Transfer Coefficients. *Environ. Sci. Technol.* 46, 10047–10054.
772 <https://doi.org/10.1021/es301076p>

- 773 Nambi, I.M., Powers, S.E., 2003. Mass transfer correlations for nonaqueous phase liquid dissolution
774 from regions with high initial saturations. *Water Resources Research* 39.
775 <https://doi.org/10.1029/2001WR000667>
- 776 Nelson, H.D., De Ligny, C.L., 1968. The determination of the solubilities of some n-alkanes in water at
777 different temperatures, by means of gas chromatography. *Recueil des Travaux Chimiques des*
778 *Pays-Bas* 87, 528–544.
- 779 Newell, C.J., 1995. *Light Nonaqueous Phase Liquids*. United States Environmental Protection Agency,
780 Office of Research and Development, [and] Office of Solid Waste and Emergency Response.
- 781 Nyer, E.K., 2000. *In situ treatment technology*. CRC Press.
- 782 Nygren, M., Giese, M., Kløve, B., Haaf, E., Rossi, P.M., Barthel, R., 2020. Changes in seasonality of
783 groundwater level fluctuations in a temperate-cold climate transition zone. *Journal of*
784 *Hydrology X* 8, 100062.
- 785 Okkonen, J., Jyrkama, M., Kløve, B., 2010. A conceptual approach for assessing the impact of climate
786 change on groundwater and related surface waters in cold regions (Finland). *Hydrogeology*
787 *Journal* 18, 429–439. <https://doi.org/10.1007/s10040-009-0529-9>
- 788 Oostrom, M., Dane, J.H., Wietsma, T.W., 2007. A review of multidimensional, multifluid, intermediate-
789 scale experiments: Flow behavior, saturation imaging, and tracer detection and quantification.
790 *Vadose Zone Journal* 6, 610–637.
- 791 Ortega-Calvo, J.-J., Alexander, M., 1994. Roles of bacterial attachment and spontaneous partitioning in
792 the biodegradation of naphthalene initially present in nonaqueous-phase liquids. *Appl. Environ.*
793 *Microbiol.* 60, 2643–2646.
- 794 Parker, J.C., Lenhard, R.J., 1987. A model for hysteretic constitutive relations governing multiphase
795 flow: 1. Saturation-pressure relations. *Water Resources Research* 23, 2187–2196.
796 <https://doi.org/10.1029/WR023i012p02187>
- 797 Patterson, B.M., Davis, G.B., 2009. Quantification of vapor intrusion pathways into a slab-on-ground
798 building under varying environmental conditions. *Environmental science & technology* 43,
799 650–656.
- 800 Petri, B.G., Fučík, R., Illangasekare, T.H., Smits, K.M., Christ, J.A., Sakaki, T., Sauck, C.C., 2015.
801 Effect of NAPL source morphology on mass transfer in the vadose zone. *Groundwater* 53, 685–
802 698.
- 803 Philippe, N., Davarzani, H., Colombano, S., Dierick, M., Klein, P.-Y., Marcoux, M., 2020. Experimental
804 study of the temperature effect on two-phase flow properties in highly permeable porous media:
805 Application to the remediation of dense non-aqueous phase liquids (DNAPLs) in polluted soil.
806 *Advances in Water Resources* 146, 103783.
- 807 Picone, S., Grotenhuis, T., van Gaans, P., Valstar, J., Langenhoff, A., Rijnaarts, H., 2013. Toluene
808 biodegradation rates in unsaturated soil systems versus liquid batches and their relevance to
809 field conditions. *Applied microbiology and biotechnology* 97, 7887–7898.
- 810 Picone, S., Valstar, J., van Gaans, P., Grotenhuis, T., Rijnaarts, H., 2012. Sensitivity analysis on
811 parameters and processes affecting vapor intrusion risk. *Environmental Toxicology and*
812 *Chemistry* 31, 1042–1052.
- 813 Pierotti, R.A., Liabastre, A.A., 1972. The structure and properties of water solutions.
- 814 Pitzer, K.S., Scott, D.W., 1943. The thermodynamics and molecular structure of benzene and its methyl
815 derivatives1. *Journal of the American Chemical Society* 65, 803–829.
- 816 Powers, S.E., Abriola, L.M., Weber Jr, W.J., 1994. An experimental investigation of nonaqueous phase
817 liquid dissolution in saturated subsurface systems: Transient mass transfer rates. *Water*
818 *Resources Research* 30, 321–332.
- 819 Powers, S.E., Abriola, L.M., Weber Jr, W.J., 1992. An experimental investigation of nonaqueous phase
820 liquid dissolution in saturated subsurface systems: Steady state mass transfer rates. *Water*
821 *Resources Research* 28, 2691–2705.
- 822 Powers, S.E., Nambi, I.M., Curry Jr, G.W., 1998. Non-aqueous phase liquid dissolution in
823 heterogeneous systems: Mechanisms and a local equilibrium modeling approach - Powers -
824 1998 - *Water Resources Research - Wiley Online Library*. *Water Resources Research* 34, 3293–
825 3302.

- 826 Prommer, H., Barry, D.A., Davis, G.B., 2002. Modelling of physical and reactive processes during
827 biodegradation of a hydrocarbon plume under transient groundwater flow conditions. *Journal*
828 *of Contaminant Hydrology* 59, 113–131. [https://doi.org/10.1016/S0169-7722\(02\)00078-5](https://doi.org/10.1016/S0169-7722(02)00078-5)
- 829 Qi, S., Luo, J., O'Connor, D., Cao, X., Hou, D., 2020. Influence of groundwater table fluctuation on the
830 non-equilibrium transport of volatile organic contaminants in the vadose zone. *Journal of*
831 *Hydrology* 580, 124353. <https://doi.org/10.1016/j.jhydrol.2019.124353>
- 832 Rahimi, R., Tavakol-Davani, H., Graves, C., Gomez, A., Fazel Valipour, M., 2020. Compound
833 Inundation Impacts of Coastal Climate Change: Sea-Level Rise, Groundwater Rise, and Coastal
834 Watershed Precipitation. *Water* 12, 2776.
- 835 Rainwater, K., Mayfield, M.P., Heintz, C., Claborn, B.J., 1993. Enhanced in situ Biodegradation of
836 Diesel Fuel by Cyclic Vertical Water Table Movement: Preliminary Studies. *Water*
837 *Environment Research* 65, 717–725.
- 838 Rayner, J.L., Snape, I., Walworth, J.L., Harvey, P.McA., Ferguson, S.H., 2007. Petroleum–hydrocarbon
839 contamination and remediation by microbioventing at sub-Antarctic Macquarie Island. *Cold*
840 *Regions Science and Technology* 48, 139–153.
841 <https://doi.org/10.1016/j.coldregions.2006.11.001>
- 842 Reddi, L.N., Han, W., Banks, M.K., 1998. Mass loss from LNAPL pools under fluctuating water table
843 conditions. *Journal of Environmental Engineering* 124, 1171–1177.
- 844 Rezanezhad, F., Couture, R.-M., Kovac, R., O'Connell, D., Van Cappellen, P., 2014. Water table
845 fluctuations and soil biogeochemistry: An experimental approach using an automated soil
846 column system. *Journal of Hydrology* 509, 245–256.
847 <https://doi.org/10.1016/j.jhydrol.2013.11.036>
- 848 Rezanezhad, F., Shafieiyoun, S., Al-Raoush, R.I., Ismail, R.E., Ngueleu, S.K., Van Cappellen, P., 2019.
849 Influence of Salinity and NAPL Composition on Sulfate Application in the Contaminated
850 Subsurface Systems. *AGU Fall Meeting Abstracts* 21.
- 851 Rice, D.W., Grose, R.D., Michaelsen, J.C., Dooher, B.P., MacQueen, D.H., Cullen, S.J., Kastenberg,
852 W.E., Everett, L.G., Marino, M.A., 1995. California leaking underground fuel tank (LUFT)
853 historical case analyses. California State Water Resources Control Board.
- 854 Rivett, M., Sweeney, R., 2019. An introduction to natural source zone depletion at LNAPL sites.
855 (technical bulletin). University of Strathclyde, Glasgow.
- 856 Rivett, M.O., Tomlinson, D.W., Thornton, S.F., Thomas, A.O., Leharne, S.A., Wealthall, G.P., 2014.
857 An Illustrated Handbook of LNAPL Transport and Fate in the Subsurface, Civil And
858 Environmental Engineering. London.
- 859 Sabljčić, A., Güsten, H., Verhaar, H., Hermens, J., 1995. QSAR modelling of soil sorption. Improvements
860 and systematics of log KOC vs. log KOW correlations. *Chemosphere* 31, 4489–4514.
861 [https://doi.org/10.1016/0045-6535\(95\)00327-5](https://doi.org/10.1016/0045-6535(95)00327-5)
- 862 Sanemasa, I., Araki, M., Deguchi, T., Nagai, H., 1982. Solubility measurements of benzene and the
863 alkylbenzenes in water by making use of solute vapor. *Bulletin of the Chemical Society of Japan*
864 55, 1054–1062.
- 865 Sarikurt, D.A., Gokdemir, C., Coptu, N.K., 2017. Sherwood correlation for dissolution of pooled NAPL
866 in porous media. *Journal of Contaminant Hydrology* 206, 67–74.
867 <https://doi.org/10.1016/j.jconhyd.2017.10.001>
- 868 Schimel, J., Balsler, T.C., Wallenstein, M., 2007. Microbial stress-response physiology and its
869 implications for ecosystem function. *Ecology* 88, 1386–1394.
- 870 Schroth, M.H., Istok, J.D., Ahearn, S.J., Selker, J.S., 1995. Geometry and position of light nonaqueous-
871 phase liquid lenses in water-wetted porous media. *Journal of Contaminant Hydrology* 19, 269–
872 287. [https://doi.org/10.1016/0169-7722\(95\)00023-0](https://doi.org/10.1016/0169-7722(95)00023-0)
- 873 Seager, S.L., Geertson, L.R., Giddings, J.C., 1963. Temperature Dependence of Gas and Vapor
874 Diffusion Coefficients. *Journal of Chemical and Engineering Data* 8, 168–169.
- 875 She, H.Y., Sleep, B.E., 1998. The effect of temperature on capillary pressure-saturation relationships
876 for air-water and perchloroethylene-water systems. *Water Resources Research* 34, 2587–2597.
- 877 Shojib, M., 2015. Dissolution of Trapped Light Non-Aqueous Phase Liquid in the Presence of Trapped
878 Gas (thesis).


- 879 Sihota, N.J., Mayer, K.U., Toso, M.A., Atwater, J.F., 2013. Methane emissions and contaminant
880 degradation rates at sites affected by accidental releases of denatured fuel-grade ethanol. *Journal*
881 *of Contaminant Hydrology* 151, 1–15. <https://doi.org/10.1016/j.jconhyd.2013.03.008>
- 882 Sinke, A.J.C., Dury, O., Zobrist, J., 1998. Effects of a fluctuating water table: column study on redox
883 dynamics and fate of some organic pollutants. *Journal of Contaminant Hydrology* 33, 231–246.
884 [https://doi.org/10.1016/S0169-7722\(98\)00072-2](https://doi.org/10.1016/S0169-7722(98)00072-2)
- 885 Sinnokrot, A.A., Ramey Jr, H.J., Marsden Jr, S.S., 1971. Effect of temperature level upon capillary
886 pressure curves. *Society of Petroleum Engineers Journal* 11, 13–22.
- 887 Sleep, B.E., Ma, Y., 1997. Thermal variation of organic fluid properties and impact on thermal
888 remediation feasibility. *Soil and Sediment Contamination* 6, 281–306.
- 889 Smerdon, B.D., 2017. A synopsis of climate change effects on groundwater recharge. *Journal of*
890 *Hydrology* 555, 125–128. <https://doi.org/10.1016/j.jhydrol.2017.09.047>
- 891 Sookhak Lari, K., Davis, G.B., Johnston, C.D., 2016a. Incorporating hysteresis in a multi-phase multi-
892 component NAPL modelling framework; a multi-component LNAPL gasoline example.
893 *Advances in Water Resources* 96, 190–201. <https://doi.org/10.1016/j.advwatres.2016.07.012>
- 894 Sookhak Lari, K., Davis, G.B., Rayner, J.L., Bastow, T.P., Puzon, G.J., 2019. Natural source zone
895 depletion of LNAPL: A critical review supporting modelling approaches. *Water research* 157,
896 630–646.
- 897 Sookhak Lari, K., Johnston, C.D., Davis, G.B., 2016b. Gasoline multiphase and multicomponent
898 partitioning in the vadose zone: Dynamics and risk longevity. *Vadose Zone Journal* 15, 1–15.
- 899 Sookhak Lari, K., Rayner, J.L., Davis, G.B., Johnston, C.D., 2020. LNAPL Recovery Endpoints:
900 Lessons Learnt Through Modeling, Experiments, and Field Trials. *Groundwater Monitoring &*
901 *Remediation* 40, 21–29.
- 902 Soucy, N.C., Mumford, K.G., 2017. Bubble-Facilitated VOC Transport from LNAPL Smear Zones and
903 Its Potential Effect on Vapor Intrusion. *Environ. Sci. Technol.* 51, 2795–2802.
904 <https://doi.org/10.1021/acs.est.6b06061>
- 905 Staudinger, J., Roberts, P.V., 2001. A critical compilation of Henry's law constant temperature
906 dependence relations for organic compounds in dilute aqueous solutions. *Chemosphere* 44, 561–
907 576.
- 908 Steffy, D.A., Johnston, C., Barry, D.A., 1995. A field study of the vertical immiscible displacement of
909 LNAPL associated with a fluctuating water table. Presented at the Groundwater Quality:
910 Remediation and Protection, International Association of Hydrological Sciences, Prague, Czech
911 Republic.
- 912 Steffy, D.A., Johnston, C.D., Barry, D.A., 1998. Numerical simulations and long-column tests of
913 LNAPL displacement and trapping by a fluctuating water table. *Journal of Soil contamination*
914 7, 325–356.
- 915 Sun, S., 2016. Transient water table influence upon Light Non-Aqueous Phase Liquids (LNAPLs)
916 redistribution: laboratory and modelling studies. University of Birmingham.
- 917 Suthersan, S., Koons, B., Schnobrich, M., 2015. Contemporary management of sites with petroleum
918 LNAPL presence. *Groundwater Monitoring & Remediation* 35, 23–29.
- 919 Taylor, C.A., Stefan, H.G., 2009. Shallow groundwater temperature response to climate change and
920 urbanization. *Journal of Hydrology* 375, 601–612.
- 921 Taylor, R.G., Scanlon, B., Döll, P., Rodell, M., van Beek, R., Wada, Y., Longuevergne, L., Leblanc, M.,
922 Famiglietti, J.S., Edmunds, M., Konikow, L., Green, T.R., Chen, J., Taniguchi, M., Bierkens,
923 M.F.P., MacDonald, A., Fan, Y., Maxwell, R.M., Yechieli, Y., Gurdak, J.J., Allen, D.M.,
924 Shamsudduha, M., Hiscock, K., Yeh, P.J.-F., Holman, I., Treidel, H., 2013. Ground water and
925 climate change. *Nature Climate Change* 3, 322–329. <https://doi.org/10.1038/nclimate1744>
- 926 ten Hulscher, Th.E.M., Cornelissen, G., 1996. Effect of temperature on sorption equilibrium and
927 sorption kinetics of organic micropollutants - a review. *Chemosphere* 32, 609–626.
928 [https://doi.org/10.1016/0045-6535\(95\)00345-2](https://doi.org/10.1016/0045-6535(95)00345-2)
- 929 Teramoto, E.H., Chang, H.K., 2017. Field data and numerical simulation of btx concentration trends
930 under water table fluctuations: Example of a jet fuel-contaminated site in Brazil. *Journal of*
931 *Contaminant Hydrology* 198, 37–47. <https://doi.org/10.1016/j.jconhyd.2017.01.002>
- 932 Thomson, N.R., Sykes, J.F., Van Vliet, D., 1997. A numerical investigation into factors affecting gas
933 and aqueous phase plumes in the subsurface. *Journal of Contaminant Hydrology* 28, 39–70.

- 934 USGCRP, 2014. Climate change impacts in the United States. (U.S. Global Change Research Program).
- 935 Van De Ven, C.J., Scully, K.H., Frame, M.A., Sihota, N.J., Mayer, K.U., 2021. Impacts of water table
936 fluctuations on actual and perceived natural source zone depletion rates. *Journal of Contaminant*
937 *Hydrology* 238, 103771.
- 938 Van Geel, P.J., Sykes, J.F., 1997. The importance of fluid entrapment, saturation hysteresis and residual
939 saturations on the distribution of a lighter-than-water non-aqueous phase liquid in a variably
940 saturated sand medium. *Journal of Contaminant Hydrology* 25, 249–270.
941 [https://doi.org/10.1016/S0169-7722\(96\)00038-1](https://doi.org/10.1016/S0169-7722(96)00038-1)
- 942 Van Geel, P.J., Sykes, J.F., 1994. Laboratory and model simulations of a LNAPL spill in a variably-
943 saturated sand, 1. Laboratory experiment and image analysis techniques. *Journal of*
944 *Contaminant Hydrology* 17, 1–25. [https://doi.org/10.1016/0169-7722\(94\)90075-2](https://doi.org/10.1016/0169-7722(94)90075-2)
- 945 Vasudevan, M., Johnston, C.D., Bastow, T.P., Lekmine, G., Rayner, J.L., Nambi, I.M., Suresh Kumar,
946 G., Ravi Krishna, R., Davis, G.B., 2016. Effect of compositional heterogeneity on dissolution
947 of non-ideal LNAPL mixtures. *Journal of Contaminant Hydrology* 194, 10–16.
948 <https://doi.org/10.1016/j.jconhyd.2016.09.006>
- 949 Vasudevan, M., Suresh Kumar, G., Nambi, I.M., 2014. Numerical study on kinetic/equilibrium
950 behaviour of dissolution of toluene under variable subsurface conditions. *European Journal of*
951 *Environmental and Civil Engineering* 18, 1070–1093.
952 <https://doi.org/10.1080/19648189.2014.922902>
- 953 Vorenhout, M., van der Geest, H.G., van Marum, D., Wattel, K., Eijsackers, H.J., 2004. Automated and
954 continuous redox potential measurements in soil. *Journal of environmental quality* 33, 1562–
955 1567.
- 956 Werner, D., Höhener, P., 2002. The influence of water table fluctuations on the volatilisation of
957 contaminants from groundwater. *Groundwater Quality: Natural and enhanced restoration of*
958 *groundwater pollution*, Sheffield. IAHS Publ 275.
- 959 Wiedemeier, T.H., Wilson, J.T., Kampbell, D.H., Miller, R.N., Hansen, J.E., 1995. Technical Protocol
960 for Implementing Intrinsic Remediation with Long-Term Monitoring for Natural Attenuation
961 of Fuel Contamination Dissolved in Groundwater. Volume II. PARSONS ENGINEERING
962 SCIENCE INC DENVER CO.
- 963 Williams, M.D., Oostrom, M., 2000. Oxygenation of anoxic water in a fluctuating water table system:
964 an experimental and numerical study. *Journal of Hydrology* 230, 70–85.
965 [https://doi.org/10.1016/S0022-1694\(00\)00172-4](https://doi.org/10.1016/S0022-1694(00)00172-4)
- 966 Willingham, C.B., Taylor, W.J., Pignocco, J.M., Rossini, F.D., 1945. Vapor pressures and boiling points
967 of some paraffin, alkylcyclopentane, alkylcyclohexane, and alkylbenzene hydrocarbons.
968 *Journal of Research of the National Bureau of Standards* 35, 219–244.
- 969 Wilson, J.T., Sewell, G.W., Caron, D., Doyle, G., Miller, R.N., 1995. Intrinsic bioremediation of jet fuel
970 contamination at George Air Force Base, in: *Intrinsic Bioremediation*.
- 971 Yadav, B.K., Hassanizadeh, S.M., 2011. An overview of biodegradation of LNAPLs in coastal (semi)-
972 arid environment. *Water, Air, & Soil Pollution* 220, 225–239.
- 973 Yadav, B.K., Shrestha, S.R., Hassanizadeh, S.M., 2012. Biodegradation of Toluene Under Seasonal and
974 Diurnal Fluctuations of Soil-Water Temperature. *Water Air Soil Pollut* 223, 3579–3588.
975 <https://doi.org/10.1007/s11270-011-1052-x>
- 976 Yang, Y.S., Li, P., Zhang, X., Li, M., Lu, Y., Xu, B., Yu, T., 2017. Lab-based investigation of enhanced
977 BTEX attenuation driven by groundwater table fluctuation. *Chemosphere* 169, 678–684.
978 <https://doi.org/10.1016/j.chemosphere.2016.11.128>
- 979 Yoon, H., Kim, J.H., Liljestrang, H.M., Khim, J., 2002. Effect of water content on transient
980 nonequilibrium NAPL–gas mass transfer during soil vapor extraction. *Journal of Contaminant*
981 *Hydrology* 54, 1–18.
- 982 Zeman, N.R., Irianni Renno, M., Olson, M.R., Wilson, L.P., Sale, T.C., De Long, S.K., 2014.
983 Temperature impacts on anaerobic biotransformation of LNAPL and concurrent shifts in
984 microbial community structure. *Biodegradation* 25, 569–585. <https://doi.org/10.1007/s10532-014-9682-5>
- 986 Zhang, H., Ye, Y., Yang, X., 2021. How Does the Periodic Groundwater Table Fluctuation Impact on
987 Chlorinated Vapor Intrusion? *Geofluids* 2021.

988 Zhou, A., Zhang, Y., Dong, T., Lin, X., Su, X., 2015. Response of the microbial community to seasonal
989 groundwater level fluctuations in petroleum hydrocarbon-contaminated groundwater. *Environ*
990 *Sci Pollut Res* 22, 10094–10106. <https://doi.org/10.1007/s11356-015-4183-6>

991


992 **Figures**



993

994 Fig. 1. Conceptual model showing LNAPL mobilization and transformation processes in a contaminated
 995 site during water table fluctuations: (i) initial water table level during the oil spill; (ii) low water table
 996 level (dry season); (iii) high water table level (wet season). VOC: volatile organic carbon.


997



998

999 Fig. 2. Dominant processes involved in the LNAPL biodegradation and compounds partitioning between
 1000 the phases potentially present in the saturated and unsaturated zone. K_{ow} : octanol-water partitioning
 1001 coefficient. K_{oc} : carbon-water partitioning coefficient.

1002



1003

1004 Fig. 3. A conceptual representation of the fluctuations of LNAPL (S_n) and water (S_w) saturations of the
 1005 soil during variations of the water table between (i) an initial, (ii) a low, (iii) an intermediate, and (iv) a
 1006 high water table level (modified after ITRC, 2018; Rivett et al., 2014). The circular images a) to e) show
 1007 the distribution and the mobility of the mobile LNAPL phase in the porosity. GTW: groundwater table.

1008

1009 **Tables**

1010 Tab. 1. Main properties and partitioning coefficients of oil and different LNAPL components between
 1011 a temperature of 12 and 20°C.

Temperature (°C)	Vapor pressure (mmHg) ^a				Ref.
	12.0	14.0	17.0	20.0	
Benzene	50.4	55.9	64.9	75.1	(Willingham et al., 1945)
Toluene	13.9	15.6	18.4	21.7	(Pitzer and Scott, 1943)
m-Xylene	3.8	4.3	5.1	6.2	(Pitzer and Scott, 1943)
n-Hexane	83.8	92.1	105.9	121.4	(Willingham et al., 1945)
n-Heptane	22.4	25.0	29.5	34.7	(Carruth and Kobayashi, 1973; Willingham et al., 1945)
n-Decane	0.45	0.50	0.60	0.71	(Carruth and Kobayashi, 1973)
Cyclohexane	52.5	58.0	67.2	77.5	(Li et al., 1973)
Cyclopentane	185.0	201.8	229.2	259.6	(Willingham et al., 1945)
Henry's law constant (atm.m ³ /mol)					
Benzene	3.05E-03	3.38E-03	3.94E-03	4.60E-03	(Staudinger and Roberts, 2001)
Toluene	3.41E-03	3.79E-03	4.42E-03	5.14E-03	(Staudinger and Roberts, 2001)
m-Xylene	3.99E-03	4.43E-03	5.15E-03	5.97E-03	(Staudinger and Roberts, 2001)
n-Hexane	0.905	0.99	1.14	1.30	(Abraham and Matteoli, 1988)
n-Heptane	1.20	1.33	1.54	1.77	(Abraham and Matteoli, 1988)
n-Decane				5.15	(Clough, 2014)
Cyclohexane	0.11	0.12	0.13	0.15	(Ashworth et al., 1988)
Cyclopentane	9.03E-02	9.81E-02	0.11	0.13	(Hansen et al., 1993)
Solubility in water (mg/L)					
Benzene	1589.5	1581.7	1585.6	1597.3	(Sanemasa et al., 1982)
Toluene	510.6	512.9	516.5	520.1	(Sanemasa et al., 1982)
m-Xylene	156.6	157.4	158.7	160.0	(Sanemasa et al., 1982)
n-Hexane	10.4	10.5	9.4	10.6	^b
n-Heptane	2.1	2.1	2.2	2.3	(Nelson and De Ligny, 1968)
n-Decane				9.0E-03	(Clough, 2014)
Cyclohexane	86.7	88.0	81.2	70.0	(Budantseva et al., 1976; Pierotti and Liabastre, 1972)
Cyclopentane	341.1	341.7	304.8	249.0	(Pierotti and Liabastre, 1972)
Log K _{oc} (L/kg)					
Benzene	1.88	1.89	1.91	1.92	(Sabljic et al., 1995) ^c
Toluene	2.28	2.30	2.31	2.33	(Sabljic et al., 1995) ^c
m-Xylene				2.34	(Sabljic et al., 1995)
Hexane				3.34	ECHA ^d
Heptane				2.38	ECHA
Decane				4.16	ECHA
Cyclohexane					
Cyclopentane				2.53	ECHA
Log K _{ow}					
Benzene	2.20	2.21	2.24	2.25	(David and Moldoveanu, 2019)
Toluene	2.69	2.71	2.73	2.75	(David and Moldoveanu, 2019)
m-Xylene				3.20	(Sabljic et al., 1995)
Hexane				3.90	(Hansch et al., 1985) (25°C)
Heptane				4.66	(Miller et al., 1985) (23°C)
Decane				5.01	(Coates et al., 1985)
Cyclohexane				3.44	(Hansch et al., 1985) (25°C)
Cyclopentane				3.00	(Hansch et al., 1985) (25°C)
Density (g/cm ³)					
Oil (Voltesso 35)	0.859	0.859	0.858	0.858	(Sleep and Ma, 1997) ^e

Dynamic viscosity (cP)					
Oil (Voltesso 35)	33,5	29,0	23,7	19,6	(Sleep and Ma, 1997) ^f
Interfacial tension of oil-water system (mJ/m ²)					
Oil (Voltesso 35)	44.3	43.8	43.1	42.4	(Sleep and Ma, 1997) ^g

1012 ^a Calculated using Antoine Equation Parameters using data of the cited references.

1013 ^b Calculated from Henry's law constant and the vapor pressure.

1014 ^c Calculated from the log K_{ow} after the equation of Sabljic et al. (1995): $\log K_{oc} = 0.81 * \log K_{ow} + 0.10$.^{dc}

1015 ^d European Chemicals Agency (ECHA): <https://echa.europa.eu/fr/information-on-chemicals>. The data
1016 of each parameter and compound at the different temperatures were determined according to the data
1017 available in the respective references.

1018 ^e Calculated after the equation of Sleep and Ma (1997): $\rho_{oil} = 0.8610 - 1.1750 * 10^{-4} * T - 2.7738 * 10^{-6} * T^2$

1019 ^f Calculated after the equation of Sleep and Ma (1997): $\ln \mu_{oil} = 24.306 - 1.767 * 10^4 / T - 3.366 * 10^6 / T^2$

1020 ^g Calculated after the equation of Sleep and Ma (1997): $\gamma_{oil} = 47.226 - 0.244 * T$

1021

1022 Tab. 2. Summary of the main expected global effects of the increase in temperature and groundwater
 1023 table fluctuations on the LNAPL mobility, the dissolved plume, and natural attenuation rates under the
 1024 climate change context.

	Main effects of the increase in temperature from 12 to 20°C	Main effect of more intense groundwater level variations	Global expected effect of climate change
LNAPL source zone mobility, partitioning, and depletion	<ul style="list-style-type: none"> • Decreased LNAPL viscosity (up to 41%). • Sorption? • Increased saturated vapor pressures (up to 45%) 	<ul style="list-style-type: none"> • Greater spreading of the LNAPL across the SZ and USZ • Greater exposure of the LNAPL to the air, meteoric water, and groundwater • Accelerated diffusion and advective transport of soil gas 	<ul style="list-style-type: none"> • Increased global LNAPL mobility • Increased leaching of the residual LNAPL by infiltrated meteoric water • Increased volatilization from the mobile, residual LNAPL • Increased VOC surface emissions
Dissolved plume	<ul style="list-style-type: none"> • Low variation of the LNAPL compounds solubility • Increased Henry's law constant (up to 51%) 	<ul style="list-style-type: none"> • Greater LNAPL- meteoric and groundwater interfacial areas • Easier dissolved phase transportation by advection 	<ul style="list-style-type: none"> • Increased residual and entrapped LNAPL constituents' dissolution • Increased dissolved groundwater plume concentration • Greater spreading of the dissolved plume in groundwater • Increased volatilization from the dissolved phase
Natural attenuation	<ul style="list-style-type: none"> • Increased uptake of nutrients and organic components by microorganisms • Increased microorganisms' activity 	<ul style="list-style-type: none"> • Greater availability and renewal of carbon, oxygen, and micronutrients through the soil and the water column • Better evacuation of the reaction by-products accumulated during biodegradation • Greater functional diversity and flexibility of microorganisms 	<ul style="list-style-type: none"> • Increased LNAPL biodegradation and attenuation rates • Increased gaseous (CO₂, CH₄) surface emissions • Decreased LNAPL source zone longevity • Maintains strong dissolution processes • Increased short-term risks • Decreased long-term risks

1025

1026 Tab. 3. Summary of the main expected effects of climate change on LNAPL contaminations under
 1027 specific climatic conditions.

	Main current properties ^a	Main expected effect of climate change by 2100^a	Main expected effect of climate change on LNAPL
Cold regions	<ul style="list-style-type: none"> • Low temperatures (<8°C) • Low soil nutrient contents and availability • Excess water distribution (rainfalls> 900 mm/yr) • Low soil oxygen diffusivities • Very low LNAPL volatilization, dissolution, and biodegradation 	<ul style="list-style-type: none"> • Increased temperature (+5-9°C) and rainfalls (up to +50%) • Reduced snow cover and soil frost • Increased groundwater recharge, and heads in winter • Increased evapotranspiration, decreased groundwater recharge, and heads in summer • Increased groundwater level fluctuations • Higher oxygen inputs and diffusion in the soil and water • Strongly enhanced soil microbial activity 	<ul style="list-style-type: none"> • Strongly increased LNAPL viscosity, volatility, and solubility • Increased spreading of the pollution in the soil and water • Strongly enhanced LNAPL biodegradation • Higher VOC emissions and dissolved pollutants concentrations • Strongly decreased pollution longevity
Arid/semi-arid zones	<ul style="list-style-type: none"> • Highly variable and extremes temperatures (-10°C-60°C) • Scarce but intense rainfalls (mean rainfalls: 185-550 mm/yr) • Important water table level and soil moisture content fluctuations • High LNAPL mobilization and biodegradation 	<ul style="list-style-type: none"> • Increased temperature (+4-7°C) • Decreased snowpack and precipitations in spring and summer • Strongly increased evapotranspiration and groundwater use • Strongly decreased groundwater recharge (up to -30%) and heads • Increased groundwater level variations tied with the encroachment catchment areas of pumping wells • Strongly decreased soil moisture content and soil microbial activity • Increase extreme precipitation events and floods frequency and intensity 	<ul style="list-style-type: none"> • Increased LNAPL/air surface areas in the SZ • Increased LNAPL compounds volatility and VOC emissions • Increased spreading of the pollution in soil • Decreased LNAPL biodegradation • Increased risks of new LNAPL spills due to damage LNAPL transport and storage infrastructures during floods
Humid coastal areas	<ul style="list-style-type: none"> • High groundwater table dynamic due to tidal effects 	<ul style="list-style-type: none"> • Increased sea level (0.43-0.84 mm/yr) due to thermal expansion, melting ice sheets, glaciers, and land water storage changes • Increased precipitations (+10-20%) and extreme precipitation events (+10-50%) • Increased coastal erosion, flood events frequency, and intensity • Increased coastal aquifer and groundwater heads • Increase salt-water intrusion and groundwater salinity 	<ul style="list-style-type: none"> • Increase LNAPL/water surface contact • Increased pollutants dissolution and dilution in groundwater, connected rivers, and sea • Modification of some pollutants biodegradation rates due to changes in water salinity, soil moisture content, and the oxygen diffusivity • Increased risks of new LNAPL spills due to damage of coastal LNAPL transport and storage infrastructures during floods, storms

1028 ^a Predictions from IPCC (2014), Meixner et al. (2016), USGCRP (2014).

1029 Tab. 4. Main research papers from 1993 to 2021 focusing on the effect of temperature or groundwater
 1030 table fluctuations on the LNAPL transport and mobilization sorted according to the studied process and
 1031 the scientific approach.

Main process	References	Scientific approach
<i>Dissolution, transport, sorption</i>	Alazaiza et al., 2020; Chompusri et al., 2002; David and Moldoveanu, 2019; Dobson et al., 2007; Gupta et al., 2019; Gupta and Yadav, 2020; Kechavarzi et al., 2005; Lekmine et al., 2014; Lenhard et al., 1993; Schroth et al., 1995; Shojib, 2015; Steffy et al., 1998; Sun, 2016; Van Geel and Sykes, 1997, 1994; Vasudevan et al., 2016; Yang et al., 2017	<i>Laboratory experiments</i>
	Davis et al., 1999; Gatsios et al., 2018; J.-Y. Lee et al., 2001; Steffy et al., 1995; Teramoto and Chang, 2017	<i>Field monitoring</i>
	Jeong and Charbeneau, 2014; Lari et al., 2016; Lenhard et al., 2004; Mobile et al., 2012; Reddi et al., 1998; Teramoto and Chang, 2017; Vasudevan et al., 2014	<i>Numerical modeling</i>
<i>Biodegradation/Attenuation</i>	Dobson et al., 2007; Gupta et al., 2019; Ismail et al., 2020; Picone et al., 2013; Rainwater et al., 1993; Rezanezhad et al., 2014; Sinke et al., 1998; Van De Ven et al., 2021; Yadav et al., 2012	<i>Laboratory experiments</i>
	Askarani, 2020; Eichert et al., 2017; C.-H. Lee et al., 2001; McAlexander and Sihota, 2019; Sihota et al., 2013; Wilson et al., 1995; Zeman et al., 2014; Zhou et al., 2015	<i>Field monitoring</i>
	Prommer et al., 2002	<i>Numerical modeling</i>
<i>Volatilization, gas transport</i>	Chen et al., 2010; McCarthy and Johnson, 1993; Soucy and Mumford, 2017	<i>Laboratory experiments</i>
	Baedecker et al., 2011; Guo, 2015; Patterson and Davis, 2009	<i>Field monitoring</i>
	Picone et al., 2012; Qi et al., 2020; Thomson et al., 1997	<i>Numerical modeling</i>

1032

1033 Tab. 5. Main relevant LNAPL laboratory experiments on soil columns and numerical studies from 1993
 1034 to 2021 sorted according to the complexity of the porous media and LNAPL source composition used.

LNAPL composition		
LNAPL mixture complexity	Commonly used compounds	References
One component	Toluene, <i>n</i> -heptane, <i>n</i> -decane, or <i>n</i> -pentane	Chompusri et al., 2002; Gupta et al., 2019; Gupta and Yadav, 2020; Ismail et al., 2020; Picone et al., 2013; Shojib, 2015; Sinke et al., 1998; Soucy and Mumford, 2017; Steffy et al., 1998; Van Geel and Sykes, 1997, 1994; Yadav et al., 2012; Yang et al., 2017
2-4 components	BTEX, <i>n</i> -hexadecane, methylnaphthalene,	Chen et al., 2010; David and Moldoveanu, 2019; Dobson et al., 2007; Teramoto and Chang, 2017; Vasudevan et al., 2016; 2014
> 4 components	Fuel, isoparaffinic solvent, or mineral oils.	Alazaiza et al., 2020; Kechavarzi et al., 2005; Lekmine et al., 2014; Rainwater et al., 1993; Sun, 2016
Porous media composition		
Porous media complexity	Type	References
One homogeneous soil system /experiment	Fine, medium, or coarse silica/calcareous sand (90 µm-1,2 mm)	Alazaiza et al., 2020; Chompusri et al., 2002; Dobson et al., 2007; Gupta et al., 2019; Gupta and Yadav, 2020; Kechavarzi et al., 2005; McCarthy and Johnson, 1993; Rainwater et al., 1993; Schroth et al., 1995; Shojib, 2015; Sinke et al., 1998; Soucy and Mumford, 2017; Steffy et al., 1998; Van Geel and Sykes, 1997, 1994; Yadav et al., 2012; Yang et al., 2017.
	Mixture of clay, sand, and silt	Lenhard et al., 1993; Picone et al., 2013
	Natural homogenized soil	Chen et al., 2010; Ismail et al., 2020; Rezanezhad et al., 2014; Van De Ven et al., 2021
Heterogeneous soil system	Alternations of clay, fine to coarse silica sand layers	Huntley and Beckett, 2002; Illangasekare et al., 1995a; Jeong and Charbeneau, 2014; Powers et al., 1998; Qi et al., 2020; Sarikurt et al., 2017; Sun, 2016
	Fractured porous medium	Legout et al., 2009

1035