

Use of Ionic liquid + nanoparticles as media for fuel desulfurization

Fabrice Mutelet, Cesari Laetitia

▶ To cite this version:

Fabrice Mutelet, Cesari Laetitia. Use of Ionic liquid + nanoparticles as media for fuel desulfurization. 8th International Congress on Ionic Liquids, May 2019, Pekin, China. hal-03480338

HAL Id: hal-03480338 https://hal.univ-lorraine.fr/hal-03480338v1

Submitted on 4 Apr 2023 $\,$

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



ENSIC

Use of {ionic liquid + nanoparticles} as media for fuel desulfurization



Fabrice MUTELET, Laetitia CESARI

Laboratoire Réactions et Génie des Procédés (UMR CNRS 7274), Université de Lorraine, Ecole Nationale Supérieure des Industries Chimiques, 1 rue Grandville, 54000 Nancy, France



Results of extraction of sulfur containing compounds from gasoline oil using ILs indicate that such a process could be an attractive alternative to common desulfurization by hydrotreating. Indeed, the values of thiophene selectivity (about 1000) obtained with 1-ethyl-3-methylimidazolium thiocyanate [EMIM][SCN] or 1,3-dimethylimidazolium methylphosphonate [DMIM][MP] are large but the distribution factor values still remain to be improved (0.6 - 0.8 and 0.2 - 1.1 respectively). The aim of this study is to investigate the possible use of these ILs in presence of nanoparticles of TiO₂ or Fe₂O₃ as solvents for the separation problems frequently encountered in petroleum industry {aromatic sulfur compound + aliphatic hydrocarbon}.

Experimental Procedure



The liquid-liquid equilibria measurements of ternary mixtures have been performed in jacketed glass cells. The experimental set up consists of a cell with an internal volume of about 30 cm³ kept at constant temperature of 298.15 K using a thermostated bath. The ternary mixtures, with compositions inside the immiscible region of the system, are weighted using a METTLER analytical balance. All the mixtures were vigorously mixed using a teflon coated magnetic stirrer for 2h to reach a good contact between both phases and kept overnight in order to settle down.

Samples of both layers were taken from the cell using a syringe. The compositions of organic compounds such as n-heptane, thiophene were determined by gas chromatography. For determination of the ionic liquid composition, density measurements of both phases were performed at 298.15 K or 302.15 K with a vibrating tube densimeter (Anton Paar, model DMA601).

Thermodynamic study of the ternary systems {Thiophene or Pyridine / n-Heptane / IL} in the presence of nanoparticles



Figure 1. Effect of TiO_2 nanoparticles addition on the tie lines of ternary system {Thiophene + Heptane + [EMIM][SCN]} at 298.15 K. Nanopowder concentration in IL: 0.05 wt %: \blacklozenge and; 0.1 wt %: \bigtriangledown and -----. Mixture without nanoparticles: \blacksquare .



Figure 2. Effect of TiO₂ nanoparticles addition on the tie lines of ternary system {Thiophene + Heptane + [DMIM][MP]} at

In these ternary phase diagrams, the low thiophene concentration part should be considered in order to investigate deep desulfurization of fuels using ionic liquids.

[DMIM][MP] is also highly selective for thiophene but the solute distribution ratio is twice smaller than with [EMIM][SCN].

The capacity and the selectivity of $\{[EMIM][SCN] + nanoparticles\}$ for thiophene extraction from hydrocarbon solvent increases when the mass of nanoparticles increases from 0.05 wt % to 0.1 wt %.

The presence of nanoparticles in the ionic liquid phase increases the solute distribution ratio β of about 25 %.

2	



Figure 3. Effect of Fe_2O_3 nanoparticles addition on the tie lines of ternary system {Thiophene + Heptane + [EMIM][SCN]} at 298.15 K. Nanopowder concentration in IL: 0.05 wt %: \blacklozenge and; 0.1 wt %: \bigtriangledown and -----. Mixture without nanoparticles: \blacksquare .







Figure 4. Effect of Fe_2O_3 nanoparticles addition on the tie lines of ternary system {Thiophene + Heptane + [DMIM][MP]} at 298.15 K. Nanopowder concentration in IL: 0.05 wt %: \blacklozenge and; 0.1 wt %: \blacktriangledown and -----. Mixture without nanoparticles:





Figure 5. Solute distribution ratio β as function of solute mole fraction (thiophene) in hydrocarbon-rich phase, at 298.15 K for pure [EMIM][SCN] and its suspensions with TiO₂ and Fe₂O₃ nanopowders.



Figure 6. IR spectras of ILs and their suspensions with nanopowders.



Figure 7. Raman spectra of [DMIM][MP] and suspensions with nanoparticles.



No structural changes in the ILs are observed

The size of aggregates of nanoparticules strongly depends on the anion grafted on the cation (figure 8). The interactions between nanoparticules and ILs seem to be less favorable in [EMIM][SCN] than in [DMIM][MP]. Nanoparticules also aggregate to form a bigger gathering. For example, with TiO₂, the particules size distribution strongly decreases from d = 579 nm in [EMIM][SCN] to d = 243 nm in [DMIM][MP].

and [EMIM][SCN].

Conclusion

(Liquid + liquid) equilibrium data for the two ternary systems {thiophene + n-heptane + [EMIM][SCN]} and {thiophene + n-heptane + [DMIM][MP]} in the presence of nanoparticles at T = 298.15 K were determined. All ternary systems correspond to the Type 2 category, with partial or total immiscibility of the IL with the thiophene and the hydrocarbons. The presence of nanoparticles in the ionic liquid phase increases the solute distribution ratio β . In [DMIM][MP], the interactions with the nanoparticules are more favorable than in [EMIM][SCN].