

# Facile characterization of metallic impurities in detonation nanodiamonds through selective combustion using standard techniques

Killian Henry, Mélanie Emo, Sébastien Diliberto, Sebastien Hupont, Jean-Charles Arnault, Hugues Girard, Marc Dubois, B. Vigolo

## ▶ To cite this version:

Killian Henry, Mélanie Emo, Sébastien Diliberto, Sebastien Hupont, Jean-Charles Arnault, et al.. Facile characterization of metallic impurities in detonation nanodiamonds through selective combustion using standard techniques. Diamond and Related Materials, 2023, 140 (Part A), pp.110466. 10.1016/j.diamond.2023.110466 . hal-04227808


## HAL Id: hal-04227808 https://hal.univ-lorraine.fr/hal-04227808v1

Submitted on 4 Oct 2023

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

	-
2	through selective combustion using standard techniques
3	
4	Killian Henry <sup>1,2</sup> , Mélanie Emo <sup>1</sup> , Sébastien Diliberto <sup>1</sup> , Sébastien Hupont <sup>1</sup> , Jean-Charles
5	Arnault <sup>3</sup> , Hugues A. Girard <sup>3</sup> , Marc Dubois <sup>2</sup> , Brigitte Vigolo <sup>1,*</sup>
6	
7	1 Université de Lorraine, CNRS, Institut Jean Lamour, UMR 7198, allée André Guinier
8	54000 Nancy, France
9	2 Université Clermont Auvergne, CNRS, ICCF UMR 6296, 24 av. Blaise Pascal, F-63178
10	Aubière, France
11	3 Université Paris-Saclay, CEA, CNRS, NIMBE, 91191 Gif sur Yvette, France
12	* Corresponding author e-mail: Brigitte.Vigolo@univ-lorraine.fr
13	
14	Keywords: nanodiamonds; metallic impurities; impurity traces; standard techniques;
15	selective combustion

Facile characterization of metallic impurities in detonation nanodiamonds



## 16 Graphical abstract

17

18 Abstract Detonation nanodiamonds are  $sp^3$  carbon nanomaterials with narrow diameter 19 distribution. They have high potential of application in various fields like nanomedecine,

20 advanced composites and lubricants, photocatalysis. Detonation nanodiamonds unfortunately contain metallic and inorganic impurities of diverse nature which can act as "Trojan horses" 21 and even at weak content, they can significantly impact the nanodiamonds efficiency and the 22 23 searched performances. Detection and quantification as well as subsequent removal of these impurities is highly difficult due to the lack of tools available by scholars. In this work, we 24 25 propose a useful approach to detect and identify the inorganic impurities in detonation nanodiamonds. Our method which consists in a selective combustion of the nanodiamonds 26 results in concentrating these impurities is a one-step and simple method. This approach, 27 28 transferable to other kinds of carbon nanomaterials, is proved to be a valuable way allowing analysis of detonation nanodiamonds by standard characterization techniques such as X-ray 29 30 Photoelectron Spectroscopy, Fourier Transform Infra-Red and Raman spectroscopies or 31 Powder X-Ray Diffraction, available in any material science laboratory.

32

#### 33 1 Introduction

34 After their confidential synthesis in the 1960s, detonation nanodiamonds (DNDs) have become fascinating nanomaterials over the world in the last thirty years. The detonation 35 process is a powerful technique to produce NDs in high amount with a narrow distribution 36 size and of rather high crystallinity [1]. Typically, DNDs are synthetized from mixtures of 37 cyclotrimethylene trinitramine (RDX) and trinitrotoluene (TNT) leading to detonation 38 39 reaction; high pressure and temperature allow then the formation of nanometric diamond crystallites. DNDs combine excellent thermal, mechanical and optical properties as well a 40 high and chemically modifiable surface area [2-4]. DNDs are considered as ideal materials 41 42 for applications over broad fields such as field emission, molecular sensing, heterogeneous catalysis... [5-9]. Their development for bioapplications such as cancer therapy, 43 antimicrobial systems or drug delivery has increased in recent years. [10-18] Their use to 44

develop new slow neutron reflectors is another emerging research activity [19,20]; they have
the potential to achieve a breakthrough in condensed matter since they could provide the
unique technology to perfectly reflect slow neutrons. Pure DNDs could allow elastic or quasielastic scattering due to their low velocity and low thermal (cold) character making them
particularly of great interest for study of condensed matter like colloids, biological molecules,
polymers etc...

51 Unfortunately, DNDs contain a variety of inorganic impurities under the form of traces with a total content up to 2 - 3 wt.% [20–22]. Their origin is multiple: the reactor corrosion due to 52 53 the harsh conditions during the detonation synthesis, the post-synthesis treatments for their separation from the other carbonaceous by-products and their post-synthesis purification 54 [23,24]. These impurities, especially heavy metals, can have a negative impact on the DND 55 56 properties to be exploited and they lead to non-desired and non-controlled effects: radioactivity through neutron interaction, toxicity by release into bodies, non-controlled 57 optical phenomena... 58

59 The complete removal of these undesired metallic impurities within DNDs is currently not possible with efficacy [25–27]. Their detection by standard characterization techniques is 60 impossible because of the weak content of each noncarbon impurity (below the Limit Of 61 Detection, LOD). This difficulty renders it all the more difficult to develop efficient and 62 simple purification approaches. It is as well important to note that each manufacturer or 63 64 supplier has its own method of synthesis and post-purification, resulting in impurities of different natures and contents. There are multiple analytical methods suitable for direct 65 identification of elemental impurities such as X-ray fluorescence (XRF), atomic absorption 66 spectroscopy (AAS) or inductively coupled plasma-optical emission spectroscopy (ICP-67 OES),[24,28] but only a few techniques are sensitive enough to quantify ultra-traces of 68 elements like in DNDs: inductively coupled plasma-mass spectrometry (ICP-MS) [22,23], 69

neutron (NAA) and prompt-gamma activation analyses (PGAA)[20,21]. Unfortunately, such equipment are seldom available in common material research laboratories especially for neutron activation based methods since they belong to large scientific instruments. It clearly appears there is a need of developing a simple approach allowing a facile detection and identification of the noncarbon byproducts in DNDs.

75 In this work, we propose to concentrate the inorganic part from DND samples by selectively burning off the DNDs. These residues can be then characterized by means of standard 76 77 techniques whereas they fall below the LOD in the starting DNDs. Our approach, inspired 78 from the core principle of elemental analysis techniques [22–24], proposes a simple method which allows to clearly identify the inorganic elements in DNDs and also the compounds 79 80 (nature and crystalline phase) belonging to the DNDs. The proposed approach consists of 81 thermally gasified the DND samples under air at 600°C, just above their combustion temperature. During the DND's combustion process, the metal-based impurities possibly 82 undergone an oxidation reaction and their amount is finally substantially increased in the 83 84 outcome ashes. Their analysis is consequently strongly facilitated. Furthermore, this treatment can be easily used by any scholars. We clearly show in this work that such method 85 allows to overcome the long-term issue of detection and identification of the inorganic 86 compounds in DNDs by standard characterization techniques: like X-ray diffraction (XRD), 87 X-ray photoemission spectroscopy (XPS), Fourier Transform InfraRed (FTIR) and Raman 88 spectroscopies. The proposed approach provides a universally accessible tool for the 89 determination of the main DND's impurities and their relative quantification. The resulting 90 better knowledge of DNDs is useful for developing efficient purification methods and can 91 92 boost future applications of DNDs.

#### 94 2 Experimental Section

#### 95 2.1 Sample preparation

96 The used DNDs were provided by the Federal State Unitary Enterprise (FSUE) "Russian 97 Federal Nuclear Center – Academician E.I. Zababakhin All-Russian Research Institute of 98 Technical Physics" (RFNC-VNIIF institute, Snezhinsk, Russia). The production followed the 99 Technical Regulation TY 2-037-677-94, were the DND were synthesized using a 60/40 100 mixture of TNT/RDX, and washed multiple times by acids. According to the RFNC-VNIIF 101 institute, this procedure leads to nanoparticles with a mean diameter of 4-5 nm.

102 For the selective combustion of DND sample, approximately 1 g of the as-received powder was placed in a quartz boat then transferred into a quartz tube inside a tubular furnace. A 103 104 pump was fixed to one extremity of the tube to provide an air flow of around 100 mL/min. 105 The powder was therefore heated under air at 600 °C for one hour (10 °C/min), and then 106 cooled under ambient conditions until reaching room temperature. The outcome sample was referred to as ODND. Since the content of the inorganic impurities (after oxidation) are 107 108 around 1.8 wt.% (Figure 1f, insert), 1 g of starting DNDs gives rise to around 180 mg of residues which generates a sufficient quantity for several characterizations such as FTIR, 109 110 Raman spectroscopy, XPS and Transmission Electronic Microscopy (TEM) since for each of them only less than 10 mg of sample are required. 111

112

#### 113 2.2 Structural characterization

114 Powder XRD (PXRD) investigation was performed on a Bruker D8 advance diffractometer, 115 in the Bragg-Brentano geometry with a Cu-source ( $\lambda_{Cu} = 1.54060$  Å) equipped with a fast 1D 116 LynkEye detector. Phase identification was performed using the Diffrac.Eva software V6. 117 The thermogravimetric analysis (TGA) was carried out using a Setaram Setsys evolution 118 1750 Thermal Gravimetric Analyzer. After loading the DND powder (around 10 mg) in an alumina crucible, temperature was raised up to 900 °C under dry air at 5 °C/min with a
flowrate of 20 mL/min. For the cooling, the rate was of 20 °C/min.

For TEM and High Resolution TEM (HRTEM) analysis, DNDs were dispersed in ethanol 121 122 under sonication during 15 min. One droplet of the DND dispersion was deposited on a 200mesh-size holey carbon grid provided by Delta Microscopies. The TEM observations were 123 carried out using a JEOL JEM-ARM 200F Cold FEG apparatus equipped with a spherical 124 aberration (Cs) probe corrector working at an accelerating voltage of 200 kV. For the sake of 125 representativity of the sample, at least 50 images obtained at different locations on the sample 126 were taken. In the TEM figures shown in the paper, representative images of DNDs are 127 selected. Electron energy loss spectroscopy (EELS) and energy dispersive X-Ray 128 129 spectroscopy (EDX) experiments were performed in scanning transmission electron 130 microscopy (STEM) mode, as well as the high angle annular dark field (HAADF) images. X-131 maps and spectra were recorded on a Jeol spectrometer (SDD, Jeol DRY SD 30 GV). For EELS measurements, the spectrometer was set to an energy dispersion of 0.25 eV/channel to 132 collect C-K, N-K, O-K, Cr-L<sub>2.3</sub> and Fe-L<sub>2.3</sub> edges. 133

FTIR spectrometry was performed using a Nicolet 6700 FT-IR (Thermo Scientific)
spectrometer. Spectra were recorded in attenuated total reflectance (ATR; diamond crystal)
mode using 100 scans and a resolution of 2 cm<sup>-1</sup>.

The microRaman spectroscopy study was performed with a LabRAM HR 800 micro-Raman spectrometer. For the phase study for the ODND sample, a Torus diode laser with a wavelength of 532 nm provided by Laser Quantum was used. The energy received by the sample is around 4 mW/cm<sup>2</sup> at full power.

141 XPS spectra were collected on a Kratos Axis Ultra (Kratos Analytical, UK) spectrometer 142 equipped with a monochromatic Al K $\alpha$  (1486.6 eV). All spectra were recorded at a 90° 143 takeoff angle. The high-resolution regions were acquired with 0.1 eV step and 20 eV pass

144 energy (instrumental resolution better than 0.5 eV). For the analysis, the powders were fixed
145 onto a copper scotch tape. Curve fitting was performed using a combined Gaussian and
146 Lorentzian line profile after Shirley's background subtraction by Casa XPS software.

Regarding ICP-MS the quadrupole ICP-MS is an iCAPQ (ThermoElectron) classically 147 equipped with a cyclonic glass nebulization chamber (tuned in high matrix mode, with a 148 149 dwell time set to 40 ms) and a nanoparticle glass nebulizer (Glass Expansion). A collision cell is used to avoid molecular ions that could be formed in the argon plasma. Samples are 150 analyzed by external calibration in the range 5 to 150 ppb. All dilutions are performed by 151 weight. Barium, copper, aluminum, iron, zinc, calcium, sodium and lead standards solution 152 are obtained by dilution from a SPEX CertiPrep Claritas and 2 % hydrochloric acid purified 153 by sub-boiling distillation. Samples are constantly placed inside an ultrasonic bath. 154

155

#### 156 **3 Results and Discussion**

#### 157 **3.1** Concentration of inorganic impurities by selective combustion of DNDs

TEM observations show DNDs aggregates or chaplets of several hundreds of nm in size (Figures 1a-1b), as typically observed for the NDs synthesized by the detonation method [29–32]. An example of HRTEM image is depicted in Figure 1c. The insert exhibits lattice planes of the DNDs, showing the crystallized structure of the material [29,33,34]. The size distribution, over a total of 183 nanoparticles measured, follows a log normal distribution behavior centered around  $5.6 \pm 1.8$  nm, which is in agreement with the mean diameter of 4-5 nm given by the supplier (Figure 1d).

PXRD pattern of the studied DNDs exhibits the five reflections expected for the diamond
phase in the ICCD database (PDF#06-0675): (111) at 42°, (222) at 75°, (311) at 90°, (400) at

167  $120^{\circ}$  and (331) at 140°. By applying the Scherrer law on the (111) peak, a value of 4.2 nm

was found for the crystallite size, which is in accordance with the TEM analysis. The
experimental diffractogram of DNDs (black) matches quite well with the XRD pattern
simulated with CaRine software (red). The broad peak observed from 20-40° seems to belong
to the (002) reflection of a sp<sup>2</sup> layers surrounding the DND particles [35–37], as suggested on
upper left particle in Figure 1c.

Figure 1f exhibits the thermogram performed under air of the raw DNDs. After dehydration of the DNDs at around 120 °C, the major weight loss around 500°C corresponds to the DND complete combustion. Above 600 °C, the total amount of the inorganic impurities present in DNDs is around ~ 1.8 wt.% (inset Figure 1f). Those which are not already of an oxidized form have undergone an oxidation during TGA under air, which is confirmed by the weight gain observed in the 300-425 °C range.





Figure 1 a)-b) TEM images of detonation nanodiamonds at different magnifications and c) HRTEM image of the same sample, insert: zoom-in on a ND particle. d) Size distribution of DND with a log normal distribution function (black curve), calculated based on 183 particles. The mean diameter is note  $\langle D \rangle$ , while the standard deviation is abbreviated SD. e) PXRD

pattern (Cu, 1.5406 Å) of as-received DND. The black line is the experimental pattern, the red circles are the simulated pattern for diamond, based on CaRine software, green bars indicate the position of (hkl) planes from the ICCD #06-0675 file. f) Thermogram of DND under dry air. The insert is a zoom in the high temperature range showing the remaining mass after the complete consumption of the DNDs.

189

Figure 2 illustrates the developed selective combustion of detonation nanodiamond method.
Temperature is raised up to above the DND burnt off (*i.e.* 600°C) determined from TGA

192 (Figure 1f) and the remaining inorganic impurities are thus naturally concentrated.



193

194 Figure 2 Selective combustion of the detonation nanodiamonds leading to the outcome 195 ODND sample. DNDs are represented as grey solid circles surrounded by some graphite 196 layers (in black) and inorganic impurities (in brown). The resulting ashes (ODND) are 197 displayed in red.


198

### 199 **3.2** Determination of the main impurities in DND and ODND

The inorganic impurities (total amount of ~ 1.8 wt.%) present in the raw DND powder have many origins and they are of numerous natures. Their detection is consequently a tricky task since their respective content is below the LOD of most of the standard characterization techniques. Thanks to local techniques such as EDX and EELS analysis, some impurities, certainly those being present at the highest concentration in DNDs, could be detected. Although local, such scrutinized investigation is required before quantitative analysis by using ICP-MS which is indeed not possible in a blind manner.

#### 207 **3.2.1** The main inorganic impurities in DNDs

208 The TEM observation of inorganic impurities in DND was made possible by the use of high angle annular dark field (HAADF) images in scanning mode. Thus, EDX spectroscopy 209 210 analyses were performed to determine the elemental composition of these particles. Also, X-maps were acquired to localize precisely the inorganic elements. In Figure 3a, two brighter 211 spots are visible in the HAADF STEM, one is constituted of carbon (Figure 3b), while the 212 upper left particle is composed of two metallic elements: iron and chromium (Figures 3e-3f). 213 214 Also, oxygen is localized in the upper left particle, presuming a Cr/Fe-oxide based particle (Figures 3d-3f). The size of the observed particles in DND is typically of 30-40 nm. A 215 216 complementary EELS experiment was carried out in another region and signals of O K-edge, Cr and Fe L-edges were recorded, together with C and N K-edges (Figure S1, Supporting 217 Information). By investigated other areas of the DND sample, different particles were found 218 with distinct compositions (Figure S2, Supporting Information): one is composed of O, S and 219 220 Ba, while the other is constituted of O, Si, K, Cr and Fe. The fact that chromium and iron 221 were found in multiple particles seems to further confirm their distribution in the whole sample as the main impurities. Also, a large particle constituted of Si and O was observed 222 223 (Figure S3, Supporting Information), probably originating from fragments of laboratory 224 glassware used for the purification of DND.



225

Figure 3 a) High angle annular dark field (HAADF) STEM image of a selected area of the as-received DND, and b-f) corresponding EDX spectroscopy elemental mappings. Carbon signal is shown in yellow (b), nitrogen in light blue (c) and oxygen in red (d). Iron (e) and cobalt (f) are respectively represented by orange and green colors.

## **3.2.2** Determination of elements as impurities in ODND by local and bulk analysis

By TEM, the outcome residues appear as several spherical and elongated particles (Figures 232 4a-4c and Figures S5-S6, Supporting Information) of a size typically in the 20-40 nm range 233 (Figure S4, Supporting Information) in agreement with the non-carbon particle size observed 234 in DND sample (Figure 3). From the TEM observations made on several zones of the ODND 235 236 sample and the analysis of 50 micrographs, no nanodiamond was noticed. By EDX spectroscopy elemental mapping, silicon, chromium and iron could be detected in agreement 237 with DND analysis. Cr and Fe are most often localized within the same particles (Figure 4 238 239 and Figure S5, Supporting Information) and in some areas, chromium oxides are found without presence of iron (Figure S6, Supporting Information). Aluminum and titanium were 240 as well detected (Figures S5 and S6, Supporting Information). 241





Figure 4 a-c) TEM images of ODND at different magnifications. d) corresponding brightfield STEM image of c). e-h) EDX spectroscopy elemental mapping of O-, Si-, Cr- and Fe Kedges, respectively.

To confirm the presence of the above listed elements, a XPS analysis of DND and ODND 247 powders was performed, and shown in Figure 5. In DNDs (Figure 5a), only C, N, O and S 248 could be observed, while for ODND (Figure 5b) a few metallic elements were seen: Na, Al, 249 Si, Cr and Fe. The observed elements are in good agreement with EDX study above (Figure 250 4, Figures S4 and S5, Supporting Information). The fact that no traces of Ti was detected in 251 the XPS spectrum of ODND could signify its content is very weak. For Na, since the TEM 252 analysis is a local technique, observations were certainly done in the areas where it is not 253 present. 254





**Figure 5** XPS survey scans of a) DND and b) ODND.

To summarize from local (EDX spectroscopy) and bulk techniques (XPS), Si, Cr and Fe may be considered as the main metallic elements in DND. Na, Al and Ti seem to be present in weaker amount.

261

## 262 **3.2.3** Reliability of the selective combustion of nanodiamonds approach

Analysis from ICP-MS, shown below in Figure 6, provides the contents of the main heteroelements present in both DND and ODND samples. In agreement with EDX spectroscopy analysis, ICP-MS shows that Si, Cr and Fe are the main impurities in the DND sample. Cu, Al, Na, Pb, Ba, Ti and Ca are at least 5 times less concentrated than the three main elements. Zn is present as traces in DND (2.10<sup>-3</sup> wt.%).




Figure 6 ICP-MS elemental analysis of DND (grey) and ODND (red). The detected elements
are as function of their concentration in weight percent. For visibility purposes, a log-scale
was used.

273

Table 1 gives the content of the main elements in DND and ODND. The corresponding ratios
of each element with respect with Cr, the main impurity found, fall in the same range for both
samples, proving that ODND provides a reliable insight of the metallic impurities of DND.
These latter concentrated in the thermally treated DNDs make possible their further detection
and analysis by standard techniques, as shown in the following.
The impurities in DND samples supplied by the RFNC-VNIIF institute were investigated by

- other techniques, such as NAA [20], and AES [38], with the need of ICP-MS [23], and are in
- 281 good agreement with Table 1.


	DND		ODND	
Element	wt.%	Factor of dilution with respect to Cr	wt.%	Factor of dilution with respect to Cr
Cr	0.641		23.965	
Si	0.128	6	6.745	3.5
Fe	0.101	6	6.582	3.6
Cu	0.024	30	1.212	20
Al	0.025	20	1.033	24
Na	0.020	30	0.880	27
Pb	0.034	20	0.776	30
Ba	0.022	60	0.388	60
Ti	< 0.01	60	0.235	120
Ca	0.007	60	0.138	240
Zn	0.002	300	0.074	240

Table 1 Content of the elements found in DND and ODND from ICP-MS and their relativecontent with respect with Cr, the most concentrated heteroatom impurity.

## **3.3** DND impurity detection and determination of their nature and origin

Identification of the compounds in DND after being treated under air and determination of 287 the corresponding impurity nature in DND were first based on PXRD investigation. A typical 288 diffractogram of ODND is displayed in Figure 7 where numerous peaks are observable. For 289 their assignment, the elements already known to be present from XPS and EDX analyses and 290 the reported chemical treatments undergone by the used as-produced DNDs have been 291 292 considered. In the following, the main compounds determined in ODND are described one by one along with the results from different characterization methods complementary to PXRD 293 in order to ascertain their presence. 294

<sup>285</sup> 





**Figure 7** PXRD pattern of ODND, performed with a Cu source ( $\lambda_{Cu} = 1.5406$  Å). Five possible phases were indexed, and shown as colored stick: quartz SiO<sub>2</sub> (PDF 46-1045) in blue, barite BaSO<sub>4</sub> (PDF 83-2053) in orange, Cr<sub>1.8</sub>Fe<sub>0.2</sub>O<sub>3</sub> (PDF 04-006-8202) in black and chromium oxide Cr<sub>2</sub>O<sub>3</sub> (PDF 85-0730) in green.

### 301 **3.3.1** Silicon – SiO<sub>2</sub>

Silicon is one of the main elements detected in both DND and ODND by EDX spectroscopy and XPS. From EDX mapping, silicon was most often observed in the same area than that of oxygen, which seems to make clear that silicon oxide (SiO<sub>2</sub>) is present in both samples (Figure 4, Figures S3, S5 and S6, Supporting Information). The  $\alpha$ -quartz phase could be identified in ODND by PXRD (Figure 7), and further confirmed by Raman (Figure S7, Supporting Information) and FTIR spectroscopies (Figure S8, Supporting Information), where all Raman- and IR-actives bands of SiO<sub>2</sub> were observed.

#### 309 3.3.2 Chromium and iron – Cr<sub>2</sub>O<sub>3</sub>, Fe<sub>2</sub>O<sub>3</sub> and Cr<sub>2-x</sub>Fe<sub>x</sub>O<sub>3</sub>

Figure S6 clearly indicates there are areas were chromium oxides are not surrounded by iron, 310 being the sign of presence of pure chromium oxides, possibly Cr<sub>2</sub>O<sub>3</sub>, since it is the most 311 stable oxide form of chromium at 600°C [39]. Also, chromium oxides are commonly found 312 in literature as residual impurities of DNDs. BaCrO<sub>4</sub> is used as detonator/initiator for DND 313 synthesis and a mixture of H<sub>2</sub>SO<sub>4</sub> and CrO<sub>3</sub> or K<sub>2</sub>Cr<sub>2</sub>O<sub>7</sub> (Jones oxidation) have been reported 314 to be used as oxidant for post-synthesis purification by the supplier [23]. Thus, all chromium 315 residuals could have been altered during the combustion of the DND, leading to chromium 316 317 oxides.

Raman spectroscopy on DNDs thermally treated under air (Figures S9 and S10) have revealed the presence of  $Cr_2O_3$ , which is in agreement with the TEM observation (Figure S6, Supporting Information), but also the presence of the solid solution  $Cr_{2-x}Fe_xO_3$  characterized in the spectrum by the addition of three magnon peaks. This could explain the systematic presence of Fe alongside Cr and O during our TEM observation in the last section. This is not surprising since the detonation chamber is composed of steel alloys that might contain Cr, as well as other metals.

On the other side, FTIR spectroscopy (Figure S8) shows all the typical vibration modes of Cr<sub>2</sub>O<sub>3</sub>. Also, since the spectrum is composed of multiple overlapping contributions, some peaks might correspond to the vibration modes of Fe<sub>2</sub>O<sub>3</sub>. However, it is not possible to confirm if they belong to pristine material ( $\alpha$ - or  $\gamma$ -Fe<sub>2</sub>O<sub>3</sub>), the most probable origin of these peaks is due to the presence of iron in the Cr<sub>2-x</sub>Fe<sub>x</sub>O<sub>3</sub> solid-solution.

Therefore, the diffractogram of ODND in Figure 7 can be indexed by both  $Cr_2O_3$  and Cr<sub>2-x</sub>Fe<sub>x</sub>O<sub>3</sub>. However, it is impossible to know the exact level of iron substitution inside the compound, thus the  $Cr_{1.8}Fe_{0.2}O_3$  phase was chosen since it matches perfectly with the diffraction peaks observed.

#### 334 3.3.3 Barium – Barite BaSO<sub>4</sub>

Barite (BaSO<sub>4</sub>), *Pnma* (62), can be well identified by PXRD (Figure 7). It has already been reported as residual impurity after acidic-purification treatment [23,25]. As mentioned early, BaCrO<sub>4</sub> being a detonator/initiator during the detonation process certainly remains in DND. Its reaction with sulfuric acid by the post-synthesis purification treatment could explain the detection of BaSO<sub>4</sub> by PXRD [23,25].

340

#### 341 **3.4** Investigation of DNDs by standard and non-standard techniques

Table 2 summarizes the results found from the conducted in-depth analysis of DND and ODND by means of standard and non-standard methods as defined below. Characterization of the thermally DND treated under air by non-standard techniques leads to similar results than those found for as-produced DND and its characterization by standard techniques allows to determine the heteroatoms present in DND in a simple manner.

Table 2 Classification of the material characterization techniques depending on their
specificity of use and on their ability to detect and identify the impurities in DND and
ODND.

	Technique	Elements/Phase detected	
tion **	Technique	DND	ODND
ndarc izatic ues*	Inductively Coupled Plasma Mass	Cr, Si, Fe, Cu, Al, Na,	Cr, Si, Fe, Cu, Al, Na,
stan terj niq	Spectrometry (ICP-MS)	Pb, Ba, Ca, Ti, Zn	Pb, Ba, Ca, Ti, Zn
Non-standard characterization techniques*	Transmission Electron microscopy (TEM) / EDX- mapping	C, N, O, S, Si, Cr, Fe, Ba	C, N, O, Al, Si, Ti, Cr, Fe, Ba
tion **	X-ray diffraction (XRD)	$C_{diamond}$	$\begin{array}{c} SiO_2, BaSO_4, Cr_2O_3, \\ Fe_xCr_{2-x}O_3 \end{array}$
Standard characterization techniques**	Fourier Transform Infrared spectroscopy (FTIR) – ATR mode	C <sub>diamond</sub>	SiO <sub>2</sub> , Cr <sub>2</sub> O <sub>3</sub>
Sta rac chn	Raman spectroscopy	C <sub>diamond</sub>	$SiO_2$ , $Cr_2O_3$ , $Fe_xCr_{2-x}O_3$
chai	X-ray photoelectron spectrometry (XPS)	C, N, O, S	C, N, O, Cr, Fe, Al, Si, Na

350 \*A characterization technique is considered as non-standard if its accessibility is restrained because of, for 351 example, proposal submission process for very large instruments or a specific sample preparation required or 352 very long exposure time and a high which-how is required to run the experiments so that the material science 353 scholars cannot run the analysis themselves. \*\* A standard characterization technique requires an available equipment in common material laboratories.
 Such technique is easy to use without with simple sample preparation and fast result delivery with reasonable data treatment and fitting.

## 357 **4** Conclusion

In this work, we have developed an alternative approach which provides a useful tool to 358 overcome the long-standing issues of hidden metallic impurities in DNDs. The noncarbon 359 impurities could be concentrated by simply applied a combustion treatment to DND in air. 360 Both as-received and thermally treated under air DND samples were analyzed by means of 361 commonly available local and bulk characterization methods. The developed approach has 362 been proven to be reliable and allows to follow in a simple manner the inorganic element 363 content and their nature in DND samples. This process can be applied after any chemical 364 treatment or modifications of DND. The proposed approach could hence help scholars in 365 developing further applications of DNDs and it could become a universal process to 366 367 concentrate the metallic impurities contained of any kind of carbonaceous nanomaterial to overcome the limit of detection of standard characterization techniques. 368

369

## 370 Acknowledgments

- B.V. and K.H. would like to thank Lionel Aranda for his valuable help in TGA experiments.
- 372 The authors are grateful to ANR for the funding of this work with the project NERF (ANR-

373 20-CE08-0034).

## 374 **References**

- V.Y. Dolmatov, A.N. Ozerin, I.I. Kulakova, O.O. Bochechka, N.M. Lapchuk, V. Myllymäki, A.
  Vehanen, Detonation nanodiamonds: new aspects in the theory and practice of synthesis,
  properties and applications, Russ. Chem. Rev. 89 (2020) 1428.
  https://doi.org/10.1070/RCR4924.
- 379 [2] I.I. Kulakova, Surface chemistry of nanodiamonds, Phys. Solid State. 46 (2004) 636–643.
   380 https://doi.org/10.1134/1.1711440.
- [3] V.N. Mochalin, O. Shenderova, D. Ho, Y. Gogotsi, The properties and applications of
   nanodiamonds, Nature Nanotech. 7 (2012) 11–23. https://doi.org/10.1038/nnano.2011.209.

- G. Reina, L. Zhao, A. Bianco, N. Komatsu, Chemical Functionalization of Nanodiamonds:
  Opportunities and Challenges Ahead, Angewandte Chemie International Edition. 58 (2019)
  17918–17929. https://doi.org/10.1002/anie.201905997.
- M.L. Terranova, S. Orlanducci, M. Rossi, E. Tamburri, Nanodiamonds for field emission: state of
   the art, Nanoscale. 7 (2015) 5094–5114. https://doi.org/10.1039/C4NR07171A.
- E. Janitz, K. Herb, L.A. Völker, W.S. Huxter, C.L. Degen, J.M. Abendroth, Diamond surface
  engineering for molecular sensing with nitrogen—vacancy centers, J. Mater. Chem. C. 10
  (2022) 13533–13569. https://doi.org/10.1039/D2TC01258H.
- 391 [7] A.V. Shvidchenko, E.D. Eidelman, A.Ya. Vul', N.M. Kuznetsov, D.Yu. Stolyarova, S.I. Belousov,
  392 S.N. Chvalun, Colloids of detonation nanodiamond particles for advanced applications,
  393 Advances in Colloid and Interface Science. 268 (2019) 64–81.
  394 https://doi.org/10.1016/j.cis.2019.03.008.
- [8] N. Nunn, M. Torelli, G. McGuire, O. Shenderova, Nanodiamond: A high impact nanomaterial,
  Current Opinion in Solid State and Materials Science. 21 (2017) 1–9.
  https://doi.org/10.1016/j.cossms.2016.06.008.
- S. Navalón, A. Dhakshinamoorthy, M. Álvaro, H. García, Diamond Nanoparticles in
  Heterogeneous Catalysis, Chem. Mater. 32 (2020) 4116–4143.
  https://doi.org/10.1021/acs.chemmater.0c00204.
- 401 [10] A.S. Barnard, Predicting the impact of structural diversity on the performance of nanodiamond 402 drug carriers, Nanoscale. 10 (2018) 8893–8910. https://doi.org/10.1039/C8NR01688G.
- 403 [11] N. Bondon, L. Raehm, C. Charnay, R. Boukherroub, J.-O. Durand, Nanodiamonds for
  404 bioapplications, recent developments, J. Mater. Chem. B. 8 (2020) 10878–10896.
  405 https://doi.org/10.1039/D0TB02221G.
- 406 [12] M. Bilal, H. Cheng, R.B. González-González, R. Parra-Saldívar, H.M.N. Iqbal, Bio-applications and
   407 biotechnological applications of nanodiamonds, Journal of Materials Research and Technology.
   408 15 (2021) 6175–6189. https://doi.org/10.1016/j.jmrt.2021.11.037.
- 409 [13] S. Chauhan, N. Jain, U. Nagaich, Nanodiamonds with powerful ability for drug delivery and
  410 biomedical applications: Recent updates on in vivo study and patents, Journal of
  411 Pharmaceutical Analysis. 10 (2020) 1–12. https://doi.org/10.1016/j.jpha.2019.09.003.
- 412 [14] N. Prabhakar, J.M. Rosenholm, Nanodiamonds for advanced optical bioimaging and beyond,
   413 Current Opinion in Colloid & Interface Science. 39 (2019) 220–231.
- 414 https://doi.org/10.1016/j.cocis.2019.02.014.
  415 [15] R. Namdar, S. Nafisi, Nanodiamond applications in skin preparations, Drug Discovery Today. 23
  416 (2018) 1152–1158. https://doi.org/10.1016/j.drudis.2018.04.006.
- 417 [16] M. Barzegar Amiri Olia, P.S. Donnelly, L.C.L. Hollenberg, P. Mulvaney, D.A. Simpson, Advances
  418 in the Surface Functionalization of Nanodiamonds for Biological Applications: A Review, ACS
  419 Appl. Nano Mater. 4 (2021) 9985–10005. https://doi.org/10.1021/acsanm.1c02698.
- 420 [17] A.M. Schrand, S.A.C. Hens, O.A. Shenderova, Nanodiamond Particles: Properties and
  421 Perspectives for Bioapplications, Critical Reviews in Solid State and Materials Sciences. 34
  422 (2009) 18–74. https://doi.org/10.1080/10408430902831987.
- 423 [18] J.-X. Qin, X.-G. Yang, C.-F. Lv, Y.-Z. Li, K.-K. Liu, J.-H. Zang, X. Yang, L. Dong, C.-X. Shan,
  424 Nanodiamonds: Synthesis, properties, and applications in nanomedicine, Materials & Design.
  425 210 (2021) 110091. https://doi.org/10.1016/j.matdes.2021.110091.
- 426 [19] V. Nesvizhevsky, R. Cubitt, E. Lychagin, A. Muzychka, G. Nekhaev, G. Pignol, K. Protasov, A.
  427 Strelkov, Application of Diamond Nanoparticles in Low-Energy Neutron Physics, Materials. 3
  428 (2010) 1768–1781. https://doi.org/10.3390/ma3031768.
- V. Nesvizhevsky, U. Köster, M. Dubois, N. Batisse, L. Frezet, A. Bosak, L. Gines, O. Williams,
  Fluorinated nanodiamonds as unique neutron reflector, Carbon. 130 (2018) 799–805.
  https://doi.org/10.1016/j.carbon.2018.01.086.
- 432 [21] R.Yu. Yakovlev, N.N. Dogadkin, I.I. Kulakova, G.V. Lisichkin, N.B. Leonidov, V.P. Kolotov,
- 433 Determination of impurities in detonation nanodiamonds by gamma activation analysis

- 434 method, Diamond and Related Materials. 55 (2015) 77–86.
- 435 https://doi.org/10.1016/j.diamond.2015.03.010.
- 436 [22] D.P. Mitev, A.T. Townsend, B. Paull, P.N. Nesterenko, Direct sector field ICP-MS determination
  437 of metal impurities in detonation nanodiamond, Carbon. 60 (2013) 326–334.
  438 https://doi.org/10.1016/j.carbon.2013.04.045.
- 439 [23] D.P. Mitev, A.T. Townsend, B. Paull, P.N. Nesterenko, Screening of elemental impurities in
  440 commercial detonation nanodiamond using sector field inductively coupled plasma-mass
  441 spectrometry, J Mater Sci. 49 (2014) 3573–3591. https://doi.org/10.1007/s10853-014-8036-3.
- P.N. Nesterenko, D. Mitev, B. Paull, Chapter 5 Elemental analysis of nanodiamonds by
  inductively coupled plasma hyphenated methods, in: J.-C. Arnault (Ed.), Nanodiamonds,
  Elsevier, 2017: pp. 109–130. https://doi.org/10.1016/B978-0-32-343029-6.00005-2.
- [25] D.P. Mitev, A.T. Townsend, B. Paull, P.N. Nesterenko, Microwave-assisted purification of
  detonation nanodiamond, Diamond and Related Materials. 48 (2014) 37–46.
  https://doi.org/10.1016/j.diamond.2014.06.007.
- V.Yu. Dolmatov, A. Vehanen, V. Myllymäki, K.A. Rudometkin, A.N. Panova, K.M. Korolev, T.A.
  Shpadkovskaya, Deep purification of detonation nanodiamond material, J. Superhard Mater.
  35 (2013) 408–414. https://doi.org/10.3103/S1063457613060099.
- 451 [27] S.P. Hong, T.H. Kim, S.W. Lee, Plasma-assisted purification of nanodiamonds and their
  452 application for direct writing of a high purity nanodiamond pattern, Carbon. 116 (2017) 640–
  453 647. https://doi.org/10.1016/j.carbon.2017.02.040.
- 454 [28] Trace and Ultratrace Elemental Analysis, in: ACS Reagent Chemicals, American Chemical
   455 Society, Washington, DC, 2017. https://doi.org/10.1021/acsreagents.2006.20200501.
- 456 [29] V.N. Mochalin, O. Shenderova, D. Ho, Y. Gogotsi, The properties and applications of
  457 nanodiamonds, Nature Nanotech. 7 (2012) 11–23. https://doi.org/10.1038/nnano.2011.209.
- [30] V.Yu. Dolmatov, T. Fujimura, Physical and Chemical Problems of Modification of Detonation
  Nanodiamond Surface Properties, in: D.M. Gruen, O.A. Shenderova, A.Ya. Vul' (Eds.), Synthesis,
  Properties and Applications of Ultrananocrystalline Diamond, Springer Netherlands, Dordrecht,
  2005: pp. 217–230. https://doi.org/10.1007/1-4020-3322-2\_16.
- 462 [31] V. Danilenko, O.A. Shenderova, Chapter 5 Advances in Synthesis of Nanodiamond Particles,
  463 in: O.A. Shenderova, D.M. Gruen (Eds.), Ultananocrystalline Diamond (Second Edition), William
  464 Andrew Publishing, Oxford, 2012: pp. 133–164. https://doi.org/10.1016/B978-1-4377-3465465 2.00005-0.
- 466 [32] P.M.V. Baidakova, Methods of Characterization and Models of Nanodiamond Particles, in:
  467 Detonation Nanodiamonds, Jenny Stanford Publishing, 2013.
- 468 [33] A. Krueger, The structure and reactivity of nanoscale diamond, J. Mater. Chem. 18 (2008) 1485.
  469 https://doi.org/10.1039/b716673g.
- 470 [34] M. Baidakova, A. Vul', New prospects and frontiers of nanodiamond clusters, J. Phys. D: Appl.
  471 Phys. 40 (2007) 6300–6311. https://doi.org/10.1088/0022-3727/40/20/S14.
- 472 [35] J. Chen, S.Z. Deng, J. Chen, Z.X. Yu, N.S. Xu, Graphitization of nanodiamond powder annealed in
  473 argon ambient, Appl. Phys. Lett. 74 (1999) 3651–3653. https://doi.org/10.1063/1.123211.
- 474 [36] A.P. Puzyr, V.S. Bondar, A.A. Bukayemsky, G.E. Selyutin, V.F. Kargin, Physical and Chemical
  475 Properties of Modified Nanodiamonds, in: D.M. Gruen, O.A. Shenderova, A.Ya. Vul' (Eds.),
  476 Synthesis, Properties and Applications of Ultrananocrystalline Diamond, Springer Netherlands,
  477 Dordrecht, 2005: pp. 261–270. https://doi.org/10.1007/1-4020-3322-2\_20.
- 478 [37] V.Yu. Osipov, F.M. Shakhov, K.V. Bogdanov, K. Takai, T. Hayashi, F. Treussart, A. Baldycheva,
  479 B.T. Hogan, C. Jentgens, High-Quality Green-Emitting Nanodiamonds Fabricated by HPHT
  480 Sintering of Polycrystalline Shockwave Diamonds, Nanoscale Res Lett. 15 (2020) 209.
  481 https://doi.org/10.1186/s11671-020-03433-7.
- 482 [38] V.Yu. Dolmatov, 11 Synthesis and Post-Synthesis Treatment of Detonation Nanodiamonds, in:
   483 O.A. Shenderova, D.M. Gruen (Eds.), Ultrananocrystalline Diamond, William Andrew
  - 21

- 484 Publishing, Norwich, NY, 2006: pp. 347–377. https://doi.org/10.1016/B978-081551524-
- 485 1.50013-5.
- 486 [39] B.L. Chamberland, The chemical and physical properties of CrO <sub>2</sub> and tetravalent chromium
   487 oxide derivatives, Critical Reviews in Solid State and Materials Sciences. 7 (1977) 1–31.
- 488 https://doi.org/10.1080/10408437708243431.