



# Impurity Parallel-Velocity-Gradient (i-PVG) instability

M. Lesur, J. Bourgeois, Y. Kosuga

## ► To cite this version:

M. Lesur, J. Bourgeois, Y. Kosuga. Impurity Parallel-Velocity-Gradient (i-PVG) instability. 29th IAEA Fusion Energy Conference, Oct 2023, London, United Kingdom. hal-04630453

HAL Id: hal-04630453

<https://hal.univ-lorraine.fr/hal-04630453v1>


Submitted on 1 Jul 2024

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial - NoDerivatives 4.0 International License



INSTITUT  
JEAN LAMOUR

[www.ijl.univ-lorraine.fr](http://www.ijl.univ-lorraine.fr)



UNIVERSITÉ  
DE LORRAINE



institut  
universitaire  
de France

# Impurity Parallel-Velocity-Gradient (i-PVG) instability

M. Lesur, J. Bourgeois, Y. Kosuga

29<sup>th</sup> IAEA Fusion Energy Conference


October 19<sup>th</sup>, 2023



# Context: Parallel-Velocity-Gradient (PVG) instability



## Radial gradient of parallel flows

- May drive Parallel Velocity Gradient (PVG) instability (Kelvin-Helmholtz-like)
- In tokamaks:
  - Maybe observed in edge (CT-6B) ►  
(hints from fluctuation level & isotropy)
  - Magnetic shear is stabilizing [Catto '73]
  - PVG can be expected in
    - SOL ( $v_{\parallel} \sim c_s$ ) [Drake '92]
    - Near transport barriers [McCarthy '02]  
[Garbet '02]
    - w. strong // beam injection
    - Spherical tokamaks  
[Chapman '12], [Wang '15]
  - May couple with ITG  
[Newton, Barnes, Highcock '10-12], [Field '12]
  - In experiments, no clear-cut, direct identification yet




- In linear devices:


- Identified in experiments [Kaneko '03]



- Neglect role of ITG for now (cold ions)
- Fluid modeling [D'Angelo '65], [Kosuga '15], [Sasaki '20]



- Theory threshold agrees with observation on PANTA ►
- Drives inward particle flux [Kobayashi '16]




# Role of impurities?

Strong radial gradient of impurity parallel flows in tokamaks

- May drive impurity-PVG (i-PVG)

Injection and control of impurity flow planned in future linear device

- Can be used to investigate i-PVG



Linear, local theory of the i-PVG

- Gyrokinetic dispersion relation for slab geometry with weak magnetic shear [Guo '19]
- Here, simpler model: generalization of Hasegawa-Mima with equilibrium and perturbed  $v_{\parallel}$   
⇒ Parameter dependencies?

# Simplest i-PVG model

## Assumptions

- Homogeneous, constant B field
- Assume one impurity species (main ion  $s=i$ , impurity  $s=z$ )
- Cold ions
- Retain polarization drift for ions

⇒ System of 4 fluid equations (2 for  $s=i$ , 2 for  $s=z$ )

$$\frac{\partial n_s}{\partial t} + \nabla_{\perp} \cdot [n_s(\mathbf{u}_E + \mathbf{u}_{p,s})] + \nabla_{\parallel}(n_s u_{\parallel,s}) = 0$$

*polarisation*                                   *// compressibility*

$$\frac{\partial u_{\parallel,s}}{\partial t} + (\mathbf{u}_E + \mathbf{u}_{p,s}) \cdot \nabla_{\perp} u_{\parallel,s} + u_{\parallel,s} \nabla_{\parallel} u_{\parallel,s} = -\frac{q_s}{m_s} \nabla_{\parallel} \phi$$

closed by quasineutrality     $\sum_{s \neq e} Z_s n_s = n_e = n_0 \exp\left(\frac{e\phi}{T_e}\right)$

# Linear analysis

## Additional assumptions

- Neglect  $u_{p,s} \cdot \nabla_{\perp} n_{s,0}$  and  $u_{p,s} \cdot \nabla_{\perp} u_{\parallel,s,0}$  (order  $\omega/\omega_{c,s}$ )
- Neglect  $u_{\parallel,s,0} \nabla_{\parallel} \tilde{n}_s$  and  $u_{\parallel,s,0} \nabla_{\parallel} \tilde{u}_{\parallel,s}$  (order  $k_{\parallel} u_{\parallel,s,0}/\omega$ , assumed small)

⇒ Linearized system can be reduced to 2 coupled equations

for effective variables

$$\Phi = e\phi/T_e = \sum Z_s \tilde{n}_s / n_{e,0}$$

$$\tilde{u}_{\parallel} = \sum Z_s C_s \tilde{u}_{\parallel,s}$$

↑  
concentration

$$\bar{\rho}^2 = \sum_{s \neq e} C_s Z_s \rho_{c,s}^2$$

$$\partial_t (1 - \bar{\rho}^2 \nabla_{\perp}^2) \Phi + v_{*,e} \partial_y \Phi + \nabla_{\parallel} \tilde{u}_{\parallel} = 0$$

$$\partial_t \tilde{u}_{\parallel} - \overline{\nabla u_{\parallel}} \rho_{c,i} v_{T,i} \partial_y \Phi = -c_s^2 \nabla_{\parallel} \Phi$$

Hasegawa-Mima with  
« effective PVG »

« Effective PVG »

$$\overline{\nabla u_{\parallel}} = \sum_{s \neq e} C_s Z_s \frac{\partial u_{\parallel,s,0}}{\partial x}$$

## Dispersion relation

$$\omega^2 - \omega_{\text{iDW}} \omega - \frac{(k_{\parallel} c_s)^2}{1 + (k_{\perp} \bar{\rho})^2} \left( 1 - \frac{k_y}{k_{\parallel}} \frac{\nabla u_{\parallel}}{\bar{\omega}_c} \right) = 0$$


$$\omega_{\text{iDW}} = \frac{k_y v_{*,e}}{1 + (k_{\perp} \bar{\rho})^2}$$

$$\bar{\omega}_c = \sum_{s \neq e} C_s Z_s \omega_{c,s}$$

$$V = \nabla u_{\parallel,z,0} / \nabla u_{\parallel,i,0}$$

$L_n / \rho_{c,i}$	$\nabla u_{\parallel,i,0} / \omega_{c,i}$	$V$
10	0.1	2

$\rho_{c,i} k_x$	$\rho_{c,i} k_y$
0	0.7



[Bourgeois, in preparation]

# The i-PVG instability

## Instability condition

$$|\overline{\nabla u_{\parallel}}| > \overline{\nabla u_{\parallel}}_{\text{cr}}$$




OR

$$|\partial_x u_{\parallel,i,0}| > \nabla u_{i,\text{cr}}$$

with  $\overline{\nabla u_{\parallel}}_{\text{cr}}^2 = \frac{(c_s/L_{n,e})^2}{1 + (k_{\perp}\bar{\rho})^2}$

with  $\nabla u_{i,\text{cr}} = \frac{1}{C_i + V C_Z Z_Z} \overline{\nabla u_{\parallel}}_{\text{cr}}$


(equivalent)



# Maximum growthrate

$$\gamma_{max} = \frac{k_{\perp} v_{*,e}/2}{1 + k_{\perp}^2 \bar{\rho}^2} \left[ L_{n,e}^2 (1 + k_{\perp}^2 \bar{\rho}^2) \frac{\nabla u_{\parallel}^2}{c_s^2} - 1 \right]^{1/2}$$

(reached for  $k_{\parallel} = \frac{\nabla u_{\parallel}}{2\omega_c} k_y$  and  $k_x = 0$ )





# Effects of impurity close to PVG threshold

$L_n/\rho_{c,i}$	$\nabla u_{\parallel,i,0}/\omega_{c,i}$	$V$
10	<del>0.1</del> 0.08	2

⇒ Pure PVG stable as long as  $k_y < 0.75 \rho_{c,i}^{-1}$

## Maximum growthrate



# Summary & perspectives

## Local, linear analysis of the (ideal) impurity-PVG

- Qualitatively: characteristics similar to pure PVG (ex: asym. in  $k_y k_{\parallel}$  plane)
- Close to threshold, impurities can have strong impact even at low concen.

## Perspectives:

- Dissipative effects: resistivity, viscosity, drag *[Cuerva, in preparation]*
- Finite-Larmor-Radius effects
- Investigate nonlinear saturation and transport
- Coupling with ITG
- Global analysis with realistic boundary conditions

## Acknowledgements



- Scholarship by Kyushu University, joint research project in RIAM
- Grant-in-Aid for Scientific Research of JSPS of Japan (JP21H01066)
- Agence Nationale de la Recherche, project GRANUL (ANR-19-CE30-0005)
- Euratom research and training programmes, Grant Agreement No. 633053, project WP17-ENRCEA-02



institut  
universitaire  
de France

