

Supporting Information

Effect of Particle Size on the Origin of Electromechanical Response in BaTiO₃/PDMS Nanogenerators

Darya Meisak,^{*,†,‡} Artyom Plyushch,[‡] Martynas Kinka,[‡] Sergejus Balčiūnas,[‡] Vidmantas Kalendra,[‡] Sébastien Schaefer,[¶] Aleksej Zarkov,[†] Algirdas Selskis,[§] Jūras Banys,[‡] Vanessa Fierro,^{||} and Alain Celzard^{||,⊥}

[†]Faculty of Chemistry and Geosciences, Vilnius University, 03225 Vilnius, Lithuania

[‡]Faculty of Physics, Vilnius University, 10222 Vilnius, Lithuania

[¶]ICMN, UMR 7374, Université d'Orléans-CNRS, 45071 Orléans, France

[§]Center for Physical Science and Technology, 10257 Vilnius, Lithuania

^{||}CNRS, IJL, Université de Lorraine, 88051 Epinal, France

[⊥]Institut Universitaire de France (IUF), 75231 Paris, France

Corresponding Author*

Darya Meisak,^{†,‡}: darya.meisak@ff.vu.lt

1. XRD patterns of BTO/PDMS composites and BTO powders.
2. Frequency spectra of the dielectric permittivity.
3. Output current signals from the 23 vol.% BTO₂/PDMS composite at frequencies from 1 to 10 Hz.
4. Profiles of output current signals for BTO/PDMS composites.
5. Profiles of output voltage signals for BTO/PDMS composites.

1. XRD patterns of BTO/PDMS composites and BTO powders




Figure S1. XRD patterns for (a) 23, 30, and 40 vol.% BTO/PDMS composites and (b) BTO powders.

2. Frequency spectra of the dielectric permittivity




Figure S2. (a) Frequency dependencies of the real part of the dielectric permittivity at room temperature for 23, 30, and 40 vol.% BTO/PDMS composites. (b) Frequency dependencies of the imaginary part of the dielectric permittivity at different temperatures for the 40 vol.% BTO3/PDMS composite.

3. Output current signals from the 23 vol.% BTO2/PDMS composite at frequencies from 1 to 10 Hz




Figure S3. Output current signals generated by the 23 vol.% BTO2/PDMS sample at different frequencies from 1 to 10 Hz.

4. Profiles of output current signals for BTO/PDMS composites




Figure S4. Examples of output current signal profiles corresponding to a 20 N-blown at 5 Hz: (a) pure PDMS, (b) 30 vol.% BTO1/PDMS and (c) 23 vol.% BTO2/PDMS composites.

5. Profiles of output voltage signals for BTO/PDMS composites




Figure S5. Profiles of output voltage signals corresponding to a 20 N-blow at 5 Hz for all BTO/PDMS samples.